



PRODUCT DATA SHEET

PROD. #57
**SHIELD'S ALL AQUA COAT 100% ACRYLIC
 WATERPROOFING PAVER SEALER/FINISH**



PRODUCT DESCRIPTION



Shields All Aqua Coat 100% Acrylic Waterproofing Paver Sealer/Finish is a specially formulated, clear sealer/finish specifically designed for application to brick pavers, concrete floors, and other cementitious floor type substrates. Its special 100% acrylic resin formulation provides a durable finish that penetrates and seals the surface, while protecting the surface from powdering, oil and grease stains, and it resists moisture penetration. Easy to apply, it provides superior wear resistance, excellent adhesion, product versatility, and provides superior UV light resistance. Its rich gloss finish enhances the color of brick pavers, resists hot tire pick-up, seals and waterproofs the surface, and is VOC Compliant.

PRODUCT FEATURES	PRODUCT USES	PERFORMANCE QUALITIES	VOC COMPLIANCE												
<ul style="list-style-type: none"> 100% Acrylic Formula Durable Gloss Finish Excellent Sealing Qualities Wear Resistant Moisture Resistant Excellent Weathering Properties Excellent Product Versatility Easy To Apply 	<p><i>Suitable for the following properly prepared surfaces;</i> INTERIOR / EXTERIOR</p> <table border="0"> <tr> <td>Brick Pavers</td> <td>Garage Floors</td> </tr> <tr> <td>Pool & Patio Decks</td> <td>Driveways</td> </tr> <tr> <td>Concrete Floors</td> <td>Stucco</td> </tr> <tr> <td>Loading Docks</td> <td>Masonry</td> </tr> <tr> <td>Stone</td> <td>Wood Siding</td> </tr> <tr> <td>Decorative Brick</td> <td>Skip-Troweled Walls</td> </tr> </table> <p>Great For Both Interior & Exterior Use!</p>	Brick Pavers	Garage Floors	Pool & Patio Decks	Driveways	Concrete Floors	Stucco	Loading Docks	Masonry	Stone	Wood Siding	Decorative Brick	Skip-Troweled Walls	<p>Product Quality: Premium Product Use: Interior / Exterior Application: Brush, Roller Cover & Airless Spray Product System: Water-Based Finish: Gloss</p>	<p>AIM Yes OTC Yes CARB Yes SCAQMD Yes MPI # No LEED® 09CI Yes LEED® 09NC Yes LEED® 09CS Yes LEED® H Yes</p>
Brick Pavers	Garage Floors														
Pool & Patio Decks	Driveways														
Concrete Floors	Stucco														
Loading Docks	Masonry														
Stone	Wood Siding														
Decorative Brick	Skip-Troweled Walls														

SURFACE PREPARATION

General: The entire surface area to be painted should be clean, dry, sound, and free from dirt, grease, oils, waxes, mildew and any other surface contaminants that may adversely affect the performance of this coating material.

- Remove any loose, scaling, cracked or peeling paint from previously painted surfaces by hand scraping, sanding, wire brushing or by power tool cleaning methods, such as electric sanders or grinders, etc.
- For exterior surfaces, pressure wash the entire surface area using a unit with a minimum of 2000 psi of water pressure. More difficult areas should be hand scraped, sanded, wire brushed and/or power tool cleaned as mentioned above.
- The surface area to be coated should be porous. To test the porosity of the substrate, apply a few drops of water to the substrate. If the water does not absorb into the substrate immediately, it will need to be properly etched using a 1:3, Muriatic Acid:Water mixture, per gallon solution.
- Repair/replace any damaged and/or delaminated surface areas with the proper patching and/or building materials. Allow all patching materials to dry thoroughly before application of paint coatings.
- Apply touch-up paint to bare areas and/or repaint the surface area, as necessary, to achieve a uniform finish.
- Sand all rough paint edges smooth to adjacent surface area. Sand all glossy surfaces to dull existing finish.

Mildew - Treat surface areas affected by mildew with a commercial mildew removal and/or wash product carefully following manufacturer's application and safety directions. Rinse thoroughly with clean water, and allow a minimum of 24 hours to dry thoroughly.

NOTE: Allow all new concrete and masonry substrates to dry/cure for a minimum of 30 days before application of any paint coating, and in accordance with industry standards.

- WARNING!** If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and wet mop. Before you start, find out how you can protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-Lead, or log onto www.epa.gov/lead.

PRODUCT ANALYSIS DATA

PIGMENT: 0.00%

VEHICLE: 100.00%

MORE DETAILED PRODUCT ANALYSIS DATA IS AVAILABLE UPON REQUEST.

TECHNICAL DATA

- COLORS:** Clear
- TINTING:** Universal Colorants Up To 2 oz./Gal.
- VEHICLE TYPE:** 100% Acrylic
- VISCOSITY:** 13-15 Sec. / #2 Zahn Cup
- GLOSS @ 60°:** Gloss / 81 units ± 1
- FLASH POINT:** N/A
- VOC:** Not to Exceed 50 g/l – 0.42 lb/gal
(Meets AIM, OTC, CARB & SCAQMD Standards)
- SOLIDS:** By Volume: 18.36% ± 2%
By Weight: 20.01% ± 2%
- COVERAGE:** 200 – 400 Sq. Ft. / Gal.
(Depending on Application & Surface Porosity.)
- MIL FILM:** Estimated @ 300 Sq. Ft. / Gal.
Wet: 5.3 mils Dry: 1.0 mils
- DRY TIME:** (@ 70° F & 50% Relative Humidity)
To Touch: 35 – 45 Minutes
Recoat: 4 Hours, or after overnight dry.
Light Foot Traffic: 4-6 Hours
Vehicle traffic: 72 Hours
- CLEAN UP:** Warm Soapy Water
- THINNING:** Clean Water

RECOMMENDED PRIMER COATINGS

Although formulated to be self-priming, the following Richard's products are recommended primer coatings for this finish coating material.

- **New Gypsum Drywall / Plaster:**
 - Self-Priming
- **New Wood:**
 - Self-Priming
- **New Masonry**
 - Self-Priming
- **Previously Painted Surfaces:**
 - Self-Priming

APPLICATION EQUIPMENT

- **Brush Application:** Apply using a quality nylon, polyester, or combination nylon/polyester bristle brush.
- **Roller Application:** Apply using a smooth - medium nap synthetic or lamb's wool roller cover, depending on the texture and surface porosity.
- **Spray Application:**
 - **Pump:** Gas or Electric Airless Sprayer
 - **Pressure:** Minimum 1500 – 2000 PSI
 - **Tip:** 0.011 – 0.013 Reversible
 - **Hose:** ¼ inch (6.3 mm) - ⅜ inch (10 mm)

PACKAGING & WEIGHT PER GALLON

- **Packaging:**

Quarts – N/A	Gallons – 4/case
2 Gallons – N/A	5 Gallons - Each
- **Weight Per Gallon:** 8.43 lbs.

CLEAN UP & THINNING INSTRUCTIONS

Clean Up: Clean up any minor spills and splatters immediately with warm soapy water, as well as all painting tools and airless equipment. More serious spills should be contained and removed with inert absorbent material. Dispose of contaminated absorbent, container, and unused contents in accordance with local, state and federal regulations.

Thinning: Stir thoroughly and apply as it comes from the container. Thinning is not necessary. However, if thinning is required, you may add clean water up to ½ pint per gallon.

WARRANTY & LIMITATIONS

The technical information contained herein is accurate to the best of our knowledge. All warranties are excluded, whether expressed or implied, by operation of law or otherwise, including all implied warranties of merchantability or fitness for a particular purpose. Seller shall not be liable, directly or indirectly, under any circumstances for consequential, incidental, special or any other type of damages arising or resulting for any reason under the sale, handling, or use of goods sold. Seller's liability hereunder, and buyer's exclusive remedy hereunder, for negligence or any other reason, is expressly limited to reimbursement of the purchase price of the materials sold after proof of purchase is provided to the seller. Notice of any alleged failure or defect in the material must be given to the seller in writing by certified U.S. mail within 15 days of noticing the problem. Failure to give the required notice within the time provided constitutes a waiver of any claim. The Manufacturer is not responsible for any misrepresentation made by the Dealer.

REV 10-13

PRODUCT APPLICATION – General

Shield's All 100% Acrylic Waterproofing Paver Sealer/Finish may be easily applied with a quality brush, roller or airless spray equipment, as follows;

- Stir thoroughly in a spiral up and down motion before and during application to keep product completely mixed.
- For best results, apply two (2) finish coats and allow to dry thoroughly between coat applications.
- Always paint to a natural break in the surface, such as a corner or edge.
- When applying by brush, apply a smooth and generous coat on smaller surface areas, such as cutting-in larger surfaces and painting trim.
- When applying by roller cover, apply an even and generous coat in a "W" or crisscross motion, avoiding any excessive respreading or reworking.
- When applying by airless spray equipment, use a unit with a minimum of 2000 psi of pressure, with a 0.011 – 0.013 fluid spray tip.
- If applying with a low-pressure pump-up sprayer, spray coating evenly, working in sections, until entire surface area is coating
- During spray application, it is recommended to back-roll the surface area to ensure proper adhesion, an even coat application, and to work coating into surface pores.
- Maintain a wet edge during application by brushing, rolling or spraying into previously applied coating area.
- Apply when surface and ambient temperatures are above 55° F and below 90° F.
- Avoid exterior paint application when weather conditions are threatening, and late in the day when there is a threat of moisture condensing on wet paint.

PRODUCT LIMITATIONS

- Not for use in corrosive or chemical environments.
- Not for use in areas subject to intense heat.
- Not for use on below grade substrates.

PRECAUTIONARY & SAFETY INFORMATION

CAUTIONS: Avoid prolonged contact with skin, and breathing of dust, vapors and/or spray mists. Causes eye irritation. **USE WITH ADEQUATE VENTILATION!** Ensure fresh air entry during application and drying. If you experience eye water, headache or dizziness, or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriately fitted respirator, (NIOSH approved), during and after application. Follow respirator manufacturer's directions for respirator use. Avoid contact with eyes, skin and clothing. Use chemical safety glasses, goggles or a face shield for proper eye protection. Wash thoroughly after handling and before eating or smoking. Close container after each use. **DO NOT TAKE INTERNALLY!**

FIRST AID: In case of skin contact, wash thoroughly with plenty of warm soapy water. For eye contact, flush with plenty of water for 15 minutes and get medical attention immediately. If you experience difficulty breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately. If swallowed, do not induce vomiting, get medical attention immediately.

KEEP OUT OF REACH OF CHILDREN!