



PRODUCT DATA SHEET
PROD. #650 SERIES
RICH SHIELD PREMIUM 100% ACRYLIC
FLAT HOUSE PAINT



PRODUCT DESCRIPTION

Rich Shield Premium 100% Acrylic Flat House Paint is a premium quality interior and exterior flat house paint. Its special 100% acrylic formulation provides excellent adhesion, superior durability, excellent color retention, and superior weather resistance. Easy to apply, it provides excellent coverage that resists fading, streaking, and lap marks, is non-yellowing, mildew and sulfide stain resistant, and offers a soft flat finish. It offers excellent product versatility which makes it ideal for both interior and exterior uses, is formulated to meet, equal and/or exceed Federal Specification TT-P-19D for both quality and performance, and is VOC Compliant. Mildew Resistant - This paint contains agents that inhibit the growth of mildew on the surface of this paint film.

| PRODUCT FEATURES | PRODUCT USES | PERFORMANCE QUALITIES | VOC COMPLIANCE |
|--|---|---|---|
| <ul style="list-style-type: none"> 100% Acrylic Formula Smooth Flat Finish Superior Durability Weather Resistant Excellent Coverage Sulfide Stain Resistant Mildew Resistant Excellent Product Versatility VOC Compliant Easy To Apply | <p><i>Suitable for the following properly prepared surfaces;</i> INTERIOR / EXTERIOR Gypsum Drywall Masonry Wallboard Stucco Plaster Concrete Block Ceilings Aluminum Wood Trim & Doors Galvanized Metal Wood Siding Ferrous Metal Fences Vinyl Siding Great For Both Interior & Exterior Use!</p> | <p>Product Quality: Premium / Better Product Use: Interior / Exterior Application: Brush, Roller Cover, Airless Spray Product System: Water-Based Finish: Flat</p> | <p>AIM Yes OTC Yes CARB No SCAQMD No MPI # No LEED® 09CI No LEED® 09NC No LEED® 09CS No LEED® H No</p> |

SURFACE PREPARATION

General: The entire surface area to be painted should be clean, dry, sound, and free from dirt, grease, oils, waxes, mildew and any other surface contaminants that may adversely affect the performance of this coating material.

- Remove any loose, scaling, cracked or peeling paint from previously painted surfaces by hand scraping, sanding, wire brushing or by power tool cleaning methods, such as electric sanders or grinders, etc.
- For exterior surfaces, pressure wash the entire surface area using a unit with a minimum of 2000 psi of water pressure. More difficult areas should be hand scraped, sanded, wire brushed and/or power tool cleaned as mentioned above.
- Repair/replace any damaged and/or delaminated surface areas with the proper patching and/or building materials. All patching materials should be allowed to dry thoroughly before application of paint coatings.
- Lightly sand smooth all rough paint edges to adjacent surface area. Sand all glossy surfaces to effectively dull existing finish.
- Prime or spot prime all bare and/or new surface areas with Manufacturer's properly specified primer/sealer compatible to the surface type and before application of finish coating.

Mildew - Surface areas affected by mildew should be treated with a commercial mildew removal and/or wash product carefully following manufacturer's application and safety directions. Rinse thoroughly with clean water, and allow a minimum of 24 hours to dry thoroughly.

- WARNING!** If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and wet mop. Before you start, find out how you can protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-Lead, or log onto www.epa.gov/lead.

PRODUCT ANALYSIS DATA

PIGMENT: 47.37%

VEHICLE: 52.63%

MORE DETAILED PRODUCT ANALYSIS DATA IS AVAILABLE UPON REQUEST.

TECHNICAL DATA

- COLORS:** White & Tint Bases
 650 White 651 Tint Base
 652 Deep Base 653-A Accent Base
- TINTING:** Universal Colorants
- VEHICLE TYPE:** Acrylic
- VISCOSITY:** 100 KU ± 3
- GLOSS @ 60°:** Flat / 0 – 5 units
- FLASH POINT:** 232° F
- VOC:** Not to Exceed 100 g/l – 0.84 lb/gal
 (Meets AIM & OTC Standards)
- SOLIDS:** By Volume: 43.73% ± 2%
 By Weight: 62.08% ± 2%
- COVERAGE:** 300 – 400 Sq. Ft. / Gal.
 (Depending on Application & Surface Porosity.)
- MIL FILM:** Estimated @ 350 Sq. Ft. / Gal.
Wet: 4.6 mils **Dry:** 2.0 mils
- DRY TIME:** (@ 70° F & 50% Relative Humidity)
 To Touch: 1 – 2 Hours
 Recoat: 4 – 6 Hours, or after overnight dry.
- CLEAN UP:** Warm Soapy Water
- THINNING:** Clean Water

RECOMMENDED PRIMER COATINGS

Although formulated to be self-priming on previously painted surfaces in good condition, the following Richard's products are recommended primer coatings for this finish coating material. However, recommended Richard's primer coatings are not limited to the products listed below.

- **New Gypsum Drywall / Plaster:**
 - 7-11, PPS Latex Primer/Sealer Undercoater
 - 7-22, PPS Universal Alkyd Primer/Sealer Undercoater
 - 7-44, PPS Universal Acrylic Primer/Sealer Stain Killer
- **New Wood:**
 - 7-22, PPS Universal Alkyd Primer/Sealer Undercoater
 - 7-44, PPS Universal Acrylic Primer/Sealer Stain Killer
- **New Masonry**
 - 56, Signature Series Waterborne Epoxy Ester Bonding Liquid
 - 1414, Rich Flex Alkali Resistant Acrylic Masonry Primer
- **New Non-Ferrous, Aluminum & Galvanized Metal:**
 - 1017, Rust Shield Zinc Chromate Metal Primer
 - 1215/1220, Rust Shield II 100% Acrylic DTM Gray/White Metal Primers
- **New Ferrous Metal:**
 - 1015, Rust Shield Red Oxide Metal Primer
 - 1018, Rust Shield Rust Inhibitive Metal Primer
 - 1120, Industrial Coatings Universal Primer
- **Previously Painted Surfaces:**
 - Self-Priming

APPLICATION EQUIPMENT

- **Brush Application:** Apply using a quality nylon, polyester, or combination nylon/polyester bristle brush.
- **Roller Application:** Apply using a 3/8" - 1 1/4" nap synthetic or lamb's wool roller cover, depending on the texture and surface porosity.
- **Spray Application:**
 - **Pump:** Gas or Electric Airless Sprayer
 - **Tip:** 0.017" – 0.019" Reversible
 - **Pressure:** Minimum 2000 psi
 - **Hose:** 1/4 inch (6.3 mm) - 3/8 inch (10 mm)

PACKAGING & WEIGHT PER GALLON

- | | | |
|---------------------|-----------------|------------------|
| • Packaging: | Quarts – 6/case | Gallons – 4/case |
| | 2 Gallons – N/A | 5 Gallons - Each |
- **Weight per Gallon:** 12.57 lbs.

CLEAN UP & THINNING INSTRUCTIONS

Clean Up: Clean up any minor spills and spatters immediately with warm soapy water, as well as all painting tools and airless equipment. More serious paint spills should be contained and removed with inert absorbent material. Dispose of contaminated absorbent, container, and unused contents in accordance with local, state and federal regulations.

Thinning: Stir thoroughly and apply as it comes from the container. Thinning is not necessary. However, if thinning is required, you may add clean water up to 1/2 pint per gallon.

WARRANTY & LIMITATIONS

The technical information contained herein is accurate to the best of our knowledge. All warranties are excluded, whether expressed or implied, by operation of law or otherwise, including all implied warranties of merchantability or fitness for a particular purpose. Seller shall not be liable, directly or indirectly, under any circumstances for consequential, incidental, special or any other type of damages arising or resulting for any reason under the sale, handling, or use of goods sold. Seller's liability hereunder, and buyer's exclusive remedy hereunder, for negligence or any other reason, is expressly limited to reimbursement of the purchase price of the materials sold after proof of purchase is provided to the seller. Notice of any alleged failure or defect in the material must be given to the seller in writing by certified U.S. mail within 15 days of noticing the problem. Failure to give the required notice within the time provided constitutes a waiver of any claim. The Manufacturer is not responsible for any misrepresentation made by the Dealer.

REV 07-13

PRODUCT APPLICATION – General

Rich Shield Premium 100% Acrylic Flat House Paint may be easily applied with a quality brush, roller cover, or airless spray equipment as follows;

- Stir thoroughly in a spiral up and down motion before and during application to keep product completely mixed.
- For best results, it is recommended to apply two (2) finish coats.
- To assure color uniformity always intermix multiple containers of custom tinted and stock colors. Apply a small test sample to verify color.
- Always paint to a natural break in the surface, such as a corner or edge.
- When applying by brush, apply a smooth and generous coat on smaller surface areas, such as cutting-in larger surfaces and painting trim.
- When applying by roller cover, apply an even and generous coat in a "W" or crisscross motion, avoiding any excessive respraying or reworking.
- When applying by airless spray equipment use a unit with a minimum of 2000 psi of pressure, with a 0.017" – 0.019" fluid spray tip.
- During spray application, it is recommended to back-roll the surface area to ensure proper adhesion, an even coat application.
- Maintain a wet edge during application by brushing, rolling or spraying into previously applied coating area.
- Apply when surface and ambient temperatures are above 55° F and below 90° F.
- Avoid exterior paint application when weather conditions are threatening, and late in the day when there is a threat of moisture condensing on wet paint.

PRODUCT LIMITATIONS

- Not for use in corrosive or chemical environments.
- Not for use in areas subject to intense heat.
- Not for use on below grade substrates.

PRECAUTIONARY & SAFETY INFORMATION

CAUTIONS: Avoid prolonged contact with skin, and breathing of dust, vapors and/or spray mists. Causes eye irritation. **USE WITH ADEQUATE VENTILATION!** Ensure fresh air entry during application and drying. If you experience eye water, headache or dizziness, or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriately fitted respirator, (NIOSH approved), during and after application. Follow respirator manufacturer's directions for respirator use. Avoid contact with eyes, skin and clothing. Use chemical safety glasses, goggles or a face shield for proper eye protection. Wash thoroughly after handling and before eating or smoking. Close container after each use. **DO NOT TAKE INTERNALLY!**

FIRST AID: In case of skin contact, wash thoroughly with plenty of warm soapy water. For eye contact, flush with plenty of water for 15 minutes and get medical attention immediately. If you experience difficulty breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately. If swallowed, do not induce vomiting, get medical attention immediately.

KEEP OUT OF REACH OF CHILDREN!