



## PRODUCT TECHNICAL DATA INFORMATION

PRODUCT NO.: LB-1037

PAINTER'S PRIDE SEMI-GLOSS ALKYD DRYFALL

---

---

### PRODUCT DESCRIPTION

**Richard's Painter's Pride Semi-Gloss Alkyd DryFall** is a specialty coating formulated for spray application by the professional painting contractor only. Designed primarily for use in commercial, institutional and industrial type applications, it offers excellent coverage and high-hide characteristics. It is intended for use on ceiling and/or wall areas whereby the height is sufficient, (10 feet or more), for any product over spray to dry by the time it reaches the floor, then to be simply swept away with a broom, or vacuumed up. It's unique formulation and semi-gloss finish offers superior durability, excellent coverage, reduces dirt pickup, and has excellent washability. **FOR INTERIOR USE ONLY!**

**RUST PREVENTATIVE COATING FOR USE ON METAL SUBSTRATES ONLY!**

---

---

### SUGGESTED PRODUCT USE

*SUITABLE FOR APPLICATION TO THE FOLLOWING PROPERLY PREPARED SURFACES:*

METAL \* METAL CEILING BEAMS \* TRUSSES \* TEXTILE MILLS \* OFFICE COMPLEXES  
WAREHOUSES \* HOTELS \* INDUSTRIAL PLANTS \* FACTORIES \* RETAIL STORES

---

---

### PRODUCT FEATURES

HIGH-HIDING \* SUPERIOR DURABILITY \* OVER SPRAY DRIES BEFORE HITTING FLOOR \* REDUCES DIRT PICKUP  
PRODUCT VERSATILITY \* COMMERCIAL USE ONLY

---

---

### PRODUCT SPECIFICATION DATA

* <b>COLORS:</b>	White
* <b>FINISH:</b>	Semi-Gloss
* <b>FLASH POINT:</b>	<b>106° F.</b>
* <b>METHOD USED:</b>	<b>T.C.C.</b>
* <b>COATING V.O.C.:</b>	<b>Not To Exceed 4.17 LB/GAL. - (500 GRAMS/LTR.)</b>
* <b>SOLIDS:</b>	By Volume: 40.83% ± 2% By Weight: 60.52% ± 2%
* <b>RECOMMENDED MIL FILM:</b>	Wet: 5.3 mils - (Estimated at 300 Square Feet Per Gallon). Dry: 2.2 mils - (Estimated at 300 Square Feet Per Gallon).
* <b>ESTIMATED COVERAGE:</b>	Covers approximately 250 - 350 square feet per gallon, depending on type of application and the porosity of the surface area to be painted. (Estimated coverage figures do not include loss from overspray, surface irregularities, porosity and material loss when mixing.
* <b>CLEAN UP:</b>	<b>Mineral Spirits</b>
* <b>THINNING:</b>	<b>Do Not Thin</b>
* <b>ESTIMATED DRY TIME:</b>	At 77° F and 50% humidity, dries to the touch in approximately 30 minutes to 1 hour, for recoat in 4 - 6 hour, or after overnight dry, depending on drying conditions.

---

---

### PRODUCT ANALYSIS DATA

PIGMENT: 43.96%

VEHICLE: 56.04%

*MORE DETAILED PRODUCT ANALYSIS DATA IS AVAILABLE UPON FORMAL REQUEST.*

## SURFACE PREPARATION

**GENERAL:** The entire surface area should be clean, dry, sound and free from all dirt, grease, oils, waxes, mildew and any other surface contaminants. Bare metal surfaces should be solvent cleaned in accordance with **SSPC-SP 1** specifications pertaining to surface preparation for the solvent cleaning of steel and metal surfaces for removing all visible oil, grease, soil, drawing and cutting compounds and other soluble contaminants from the surface. Remove any loose scale, chalked, cracked, peeling paint, loose mil scale and loose rust by hand scraping, sanding, or wire brush cleaning in accordance with **SSPC-SP 2** specifications pertaining to hand tool cleaning, or **SSPC-SP 3** specifications pertaining to power tool cleaning of loose, non-adherent material on metal surfaces as set forth by the *Steel Structures Painting Council*. Repair/replace any damaged and/or delaminated surface areas.

**WARNING!** If you scrape, sand, or remove old paint, you may release lead dust. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD, or log on to [www.epa.gov/lead](http://www.epa.gov/lead)

---

---

## PRODUCT APPLICATION

**Richard's Painter's Pride Semi-Gloss Alkyd DryFall** is formulated primarily for spray application only. It may be applied with a quality brush and/or roller for touch-up application only. Mix thoroughly before use. When applying with an airless sprayer, it is recommended to use a unit with a minimum of 2000 psi of pressure, with a 0.0017 - 0.0019 fluid spray tip. *Certain Colors May Require Multiple Coat Applications.* Adjust pressure as needed and allow for normal spray application losses and surface irregularities. Apply when surface and ambient temperature is above 55° F and below 90° F. **KEEP FROM FREEZING!**

---

---

## PRECAUTIONS

**CAUTION: FLAMMABLE! CONTAINS VM&PNAPHTHA! KEEP OUT OF REACH OF CHILDREN! MAY AFFECT BRAIN & NERVOUS SYSTEM CAUSING DIZZINESS, HEADACHES OR NAUSEA!** Keep away from heat, sparks and open flames. **INSURE PROPER CROSS-VENTILATION UNTIL COATING HAS DRIED!** Where ventilation is inadequate, use a suitable respirator. Turn off main gas valve until after coating has dried, then have pilot lights relighted by a responsible person. Avoid prolonged contact with skin and breathing of vapors and/or spray mists. When spraying this material, use an **OSHA** approved cartridge respirator. Use chemical safety glasses, goggles, or a face shield for proper eye protection. Wash thoroughly after handling and before eating or smoking. Close container after each use. **DO NOT TAKE INTERNALLY!**

**FIRST AID:** In case of skin contact, wash thoroughly with plenty of warm soapy water. For eye contact, flush with plenty of water for 15 minutes, **SEEK IMMEDIATE MEDICAL ATTENTION!** If affected by inhalation, move immediately to fresh air. If swallowed, **DO NOT INDUCE VOMITING, SEEK IMMEDIATE MEDICAL ATTENTION!**

**NOTICE:** Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the content herein may be harmful or fatal.

---

---

## MIXING INSTRUCTIONS & PACKAGING

Stir thoroughly and apply as it comes from the container. **No Thinning Is Necessary!**

\* Pint Cans: N/A

\* Quart Cans: N/A

\* Gallon Cans: 4 Per Case

\* Two Gallon Cans: N/A

\* Five Gallon Cans: Each

\* Weight Per Gallon: 9.98 lbs.

---

---

ALL TECHNICAL DATA INFORMATION CONTAINED HEREIN IS ACCURATE TO THE BEST OF OUR KNOWLEDGE. ALL WARRANTIES ARE EXCLUDED, WHETHER EXPRESSED OR IMPLIED BY OPERATION OF LAW OR OTHERWISE, INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. SELLER SHALL NOT BE LIABLE, (DIRECTLY OR INDIRECTLY), UNDER ANY CIRCUMSTANCES FOR CONSEQUENTIAL, INCIDENTAL, SPECIAL OR ANY OTHER TYPE OF DAMAGES ARISING OR RESULTING FOR ANY REASON UNDER THE SALE, HANDLING, OR USE OF GOODS SOLD. SELLER'S LIABILITY HEREUNDER, AND BUYER'S EXCLUSIVE REMEDY HEREUNDER, FOR NEGLIGENCE OR ANY OTHER REASON, IS EXPRESSLY LIMITED TO REIMBURSEMENT OF THE PURCHASE PRICE OF THE MATERIALS SOLD AFTER PROOF OF PURCHASE IS PROVIDED TO THE SELLER. NOTICE OF ANY ALLEGED FAILURE OR DEFECT IN THE MATERIALS MUST BE GIVEN TO THE SELLER IN WRITING BY CERTIFIED U.S. MAIL WITHIN 15 DAYS OF FIRST NOTICING THE PROBLEM. FAILURE TO GIVE THE REQUIRED NOTICE WITHIN THE TIME PROVIDED CONSTITUTES A WAIVER OF ANY CLAIM. THE MANUFACTURER IS NOT RESPONSIBLE FOR ANY MISREPRESENTATION MADE BY THE DEALER.

Any additional information regarding our products and/or pricing is available through **Richard's Paint Mfg. Co., Inc.**, or through its local area **Richard's Representative**.

REV 9-09