



## PRODUCT TECHNICAL DATA INFORMATION

PRODUCT NO.: SG-60

SKID-GUARD NON-SKID ADDITIVE

---

---

### PRODUCT DESCRIPTION

**Richard's Skid-Guard Non-Skid Additive** are state-of-the-art polyethylene granules specifically designed as a non-skid additive for all types of floor coatings. Its special formulation provides a more durable and safe non-skid surface for both interior and exterior floor surfaces. It will not alter the color and the overall performance of the product being used. Once added to the paint coating, these lightweight granules stay suspended much longer than traditional sand texture additives, and they don't break-down as fast, thus offering better overall performance, durability, and product versatility. **FOR INTERIOR & EXTERIOR USES!**

---

### SUGGESTED PRODUCT USE

*SUITABLE FOR APPLICATION TO THE FOLLOWING PROPERLY PREPARED SURFACES:*

**PATIOS • STAIRWAYS • SHOWERS • WALKWAYS • POOL DECKS • LOADING RAMPS & DOCKS  
WOOD DECKS • BALCONIES • CATWALKS • INTERIOR & EXTERIOR WALLS**

---

### PRODUCT FEATURES

**LIGHTWEIGHT • EXCELLENT DURABILITY • STAYS SUSPENDED • EXCELLENT PERFORMANCE PROPERTIES  
EXCELLENT PRODUCT VERSATILITY • EASY TO USE • EXCELLENT NON-SKID PROPERTIES**

---

### PRODUCT SPECIFICATION DATA

• <b>APPEARANCE:</b>	White Powder
• <b>FINISH:</b>	N/A
• <b>FLASH POINT:</b>	>200° F
• <b>METHOD USED:</b>	T.C.C.
• <b>COATING V.O.C.:</b>	N/A
• <b>SOLIDS:</b>	By Volume: N/A By Weight: N/A
• <b>ESTIMATED COVERAGE:</b>	Coverage varies depending on amount of additive added to coating product being used, the method of application, and the porosity of the surface area to be painted.
• <b>CLEAN UP:</b>	N/A
• <b>THINNING:</b>	N/A
• <b>ESTIMATED DRY TIME:</b>	N/A

---

### PRODUCT ANALYSIS DATA

PIGMENT: 100.00%

VEHICLE: 0.00%

*MORE DETAILED PRODUCT ANALYSIS DATA IS AVAILABLE UPON FORMAL REQUEST.*

## **SURFACE PREPARATION**

Follow the surface preparation specifications listed on the product label of the paint material that will be used.

---

## **PRODUCT APPLICATION**

Follow the application specifications of the paint product being used. If two (2) finish coats are to be applied, Skid Guard may be used in both finish coats, or one finish coat application.

---

## **PRECAUTIONS**

**CAUTION: KEEP OUT OF REACH OF CHILDREN!** Avoid prolonged contact with skin and breathing of vapors and/or spray mists. When spraying this material, use an **OSHA** approved cartridge respirator. Use chemical safety glasses, goggles, or a face shield for proper eye protection. Close container after each use. **DO NOT TAKE INTERNALLY!**

**FIRST AID:** In case of skin contact, wash thoroughly with plenty of soap and water. For eye contact, flush thoroughly with plenty of water for 15 minutes and **Seek Immediate Medical Attention!** If affected by inhalation, move immediately to fresh air.

If swallowed, **Do Not Induce Vomiting! Seek Immediate Medical Attention!**

---

## **MIXING INSTRUCTIONS & PACKAGING**

Depending on desired texture, normal recommended mixture is 1 pint can of SG-60 to 1 gallon of paint product. Stir the paint product thoroughly, then pore into a separate 1.5 or 2 gallon container. Add the SG-60 to the paint product stirring granules into the product while poring. Continue to stir granules into the product until thoroughly mixed with the paint product. Apply paint product in accordance with products label directions.

\* **Pint Cans:** 6 Per Case

\* **Quart Cans:** N/A

\* **Gallon Cans:** 4 Per Case

\* **Two Gallon Cans:** Each

\* **Five Gallon Cans:** Each

\* **Weight Per Gallon:** 4.50 lbs.

---

ALL TECHNICAL DATA INFORMATION CONTAINED HEREIN IS ACCURATE TO THE BEST OF OUR KNOWLEDGE. ALL WARRANTIES ARE EXCLUDED, WHETHER EXPRESSED OR IMPLIED BY OPERATION OF LAW OR OTHERWISE, INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. SELLER SHALL NOT BE LIABLE, (DIRECTLY OR INDIRECTLY), UNDER ANY CIRCUMSTANCES FOR CONSEQUENTIAL, INCIDENTAL, SPECIAL OR ANY OTHER TYPE OF DAMAGES ARISING OR RESULTING FOR ANY REASON UNDER THE SALE, HANDLING, OR USE OF GOODS SOLD. SELLER'S LIABILITY HEREUNDER, AND BUYER'S EXCLUSIVE REMEDY HEREUNDER, FOR NEGLIGENCE OR ANY OTHER REASON, IS EXPRESSLY LIMITED TO REIMBURSEMENT OF THE PURCHASE PRICE OF THE OF THE MATERIALS SOLD AFTER PROOF OF PURCHASE IS PROVIDED TO THE SELLER. NOTICE OF ANY ALLEGED FAILURE OR DEFECT IN THE MATERIALS MUST BE GIVEN TO SELLER IN WRITING BY CERTIFIED U.S. MAIL WITHIN 15 DAYS OF FIRST NOTICING THE PROBLEM. FAILURE TO GIVE THE REQUIRED NOTICE WITHIN THE TIME PROVIDED CONSTITUTES A WAIVER OF ANY CLAIM. THE MANUFACTURER IS NOT RESPONSIBLE FOR ANY MISREPRESENTATION MADE BY THE DEALER.

Any additional information regarding our products and/or pricing is available through **Richard's Paint Mfg. Co., Inc.**, or through its local area **Richard's Representative**.