



PRODUCT TECHNICAL DATA INFORMATION

PRODUCT NO.: SR-1250

PAINTER'S PRIDE WALL GUARD "FIRST COAT"
ALKYD MODIFIED DRYWALL PRIMER/SEALER

PRODUCT DESCRIPTION

Richard's Painter's Pride Wall Guard "First Coat" Drywall Primer/Sealer is specially formulated for use on interior wallboard and drywall surfaces that exhibit a yellowish bleed and/or discoloration due to the use of recycled paper currently being used in the manufacture of these types of substrates. Its special alkyd modified acrylic formulation helps prevent the bleeding from affecting finish coat applications. It provides excellent coverage, applies easily, has excellent sealing qualities, product versatility and creates a more suitable surface for the application of both latex and oil-based finish paint coatings. **FOR INTERIOR USE ONLY!**

SUGGESTED PRODUCT USE

SUITABLE FOR APPLICATION TO THE FOLLOWING PROPERLY PREPARED SURFACES:

DRYWALL * PLASTER * CEILINGS * WOOD * MASONRY * SHEETROCK

PRODUCT FEATURES

EASY TO APPLY * SPECIAL FORMULATION * RESISTS YELLOW BLEED THROUGH
PRODUCT VERSATILITY * FAST DRY * CONTAINS NO LEAD PIGMENTS

PRODUCT SPECIFICATION DATA

* COLORS:	White
* FINISH:	Flat
* FLASH POINT:	101° F.
* METHOD USED:	T.C.C.
* COATING V.O.C.:	Not To Exceed - .83 LB/GAL. - (100 GRAMS/LTR.)
* SOLIDS:	By Volume: 40.76% ± 2% By Weight: 60.58% ± 2%
* RECOMMENDED MIL FILM:	Wet: 4.6 mils - (estimated at 350 Square Feet Per Gallon). Dry: 1.9 mils - (Estimated at 350 Square Feet Per Gallon).
* ESTIMATED COVERAGE:	Covers approximately 300 - 400 square feet per gallon, depending on the type of application and the porosity of the surface to be painted.
* CLEAN UP:	Water
* THINNING:	Clean Water
* ESTIMATED DRY TIME:	Dries to the touch in approximately 30 minutes to 1 hour, for recoat in approximately 2 - 4 hours, or after allowing to dry overnight, depending on conditions.

PRODUCT ANALYSIS DATA

PIGMENT: 50.80%

VEHICLE: 49.20%

MORE DETAILED PRODUCT ANALYSIS DATA IS AVAILABLE UPON FORMAL REQUEST.

SURFACE PREPARATION

GENERAL: The entire surface area to be painted should be clean, dry, sound and free from all dirt, grease, oils, waxes, mildew and any other surface contaminants. New masonry and/or cementitious surfaces should be tested for "alkali" content before paint application. When applying to wood surfaces, it is recommended to test a small surface area for any signs of "tannic acid bleed". Remove any loose scale, chalked, cracked or peeling paint from previously painted surfaces by hand scraping, sanding, wire brushing and/or power tool cleaning. **Mildew** - Surface areas affected by mildew should be washed with a commercial mildew removal product carefully following manufacturer's application and safety directions. Rinse thoroughly with clean water, and allow a minimum of 24 hours to dry thoroughly.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD, or log on to www.epa.gov/lead.

PRODUCT APPLICATION

Richard's Painter's Pride Wall Guard "First Coat" Drywall Primer/Sealer may be easily applied with a good quality brush, roller, or airless spray equipment. For best results, it is recommended to apply by brush and/or roller to effectively work primer into surface pores. If applying with a brush, apply a smooth and generous coat application on/in small surface areas, such as trim or cutting-in larger surface areas. If applying with a roller cover, apply an even and generous coat application in a "M" or crisscross motion, avoiding any excessive respreading or reworking. Maintain a wet edge during application by brushing/rolling into previously applied coating areas. If applying by airless spray equipment, it is recommended to use a unit with a minimum of 2000 psi of pressure, with a 0.015 - 0.019 fluid spray tip. During spray application, the surface area should be back-rolled to insure proper adhesion, an even coat application and to effectively work primer into surface pores. Allow primer/sealer to dry thoroughly before applying recommended finish coatings. Apply when surface and ambient temperatures are above 55° F. and below 90° F. **Keep From Freezing!**

PRECAUTIONS

CAUTION: KEEP OUT OF REACH OF CHILDREN! Keep away from heat, sparks and open flames. **USE WITH ADEQUATE VENTILATION!** Where ventilation is inadequate, use a suitable respirator. Avoid prolonged contact with skin and breathing of vapors and/or spray mists. When spraying this material, use an **OSHA** approved cartridge respirator. Use chemical safety glasses, goggles, or a face shield for proper eye protection. Wash thoroughly after handling and before eating or smoking. Close container after each use.

DO NOT TAKE INTERNALLY!

FIRST AID: In case of skin contact, wash thoroughly with plenty of warm soapy water. For eye contact, flush with plenty of water for 15 minutes, **SEEK IMMEDIATE MEDICAL ATTENTION!** If affected by inhalation, move immediately to fresh air. If swallowed,

DO NOT INDUCE VOMITING, SEEK IMMEDIATE MEDICAL ATTENTION!

MIXING INSTRUCTIONS & PACKAGING

Stir thoroughly and apply as it comes from the container. **No Thinning Is Necessary!** However, if thinning is required, you may add **Clean Water** up to ½ pint per gallon.

* Pint Cans: N/A

* Quart Cans: N/A

* Gallon Cans: 4 Per Case

* Two Gallon Cans: N/A

* Five Gallon Cans: Each

* Weight Per Gallon: 12.60 lbs.

ALL TECHNICAL DATA INFORMATION CONTAINED HEREIN IS ACCURATE TO THE BEST OF OUR KNOWLEDGE. ALL WARRANTIES ARE EXCLUDED, WHETHER EXPRESSED OR IMPLIED BY OPERATION OF LAW OR OTHERWISE, INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. SELLER SHALL NOT BE LIABLE, (DIRECTLY OR INDIRECTLY), UNDER ANY CIRCUMSTANCES FOR CONSEQUENTIAL, INCIDENTAL, SPECIAL OR ANY OTHER TYPE OF DAMAGES ARISING OR RESULTING FOR ANY REASON UNDER THE SALE, HANDLING, OR USE OF GOODS SOLD. SELLER'S LIABILITY HEREUNDER, AND BUYER'S EXCLUSIVE REMEDY HEREUNDER, FOR NEGLIGENCE OR ANY OTHER REASON, IS EXPRESSLY LIMITED TO REIMBURSEMENT OF THE PURCHASE PRICE OF THE MATERIALS SOLD AFTER PROOF OF PURCHASE IS PROVIDED TO THE SELLER. NOTICE OF ANY ALLEGED FAILURE OR DEFECT IN THE MATERIALS MUST BE GIVEN TO THE SELLER IN WRITING BY CERTIFIED U.S. MAIL WITHIN 15 DAYS OF FIRST NOTICING THE PROBLEM. FAILURE TO GIVE THE REQUIRED NOTICE WITHIN THE TIME PROVIDED CONSTITUTES A WAIVER OF ANY CLAIM. THE MANUFACTURER IS NOT RESPONSIBLE FOR ANY MISREPRESENTATION MADE BY THE DEALER.

Any additional information regarding our products and/or pricing is available through **Richard's Paint Mfg. Co., Inc.**, or through its local area **Richard's Representative**.

REV. 6/09