



PRODUCT TECHNICAL DATA INFORMATION

PRODUCT NO.: 1430 COARSE TEXTURE

ALKALI RESISTANT ACRYLIC TEXTURED
MASONRY FINISH

PRODUCT DESCRIPTION

Richard's Alkali Resistant Acrylic Textured Masonry Finish is a specially formulated acrylic heavy texture finish coating designed for application to above grade cementitious substrates, such as Stucco, Concrete Block, etc. Its special formulation allows for excellent alkali and efflorescence resistance, minimizes surface defects, provides excellent durability, resists fading and resists sagging, is mildew resistant, provides superior coverage and is easy to apply. **Mildew Resistant** - This paint contains agents which inhibit the growth of mildew on the surface of this paint film. **FOR INTERIOR & EXTERIOR USE!**

SUGGESTED PRODUCT USES

SUITABLE FOR APPLICATION TO THE FOLLOWING PROPERLY PREPARED SUBSTRATES:

CONCRETE * PLASTER * CEMENT COMPOSITION BOARD * MASONRY * CEMENT * BRICK * BLOCK * STUCCO
ALL CEMENTITIOUS & MASONRY TYPE SUBSTRATES

PRODUCT FEATURES

100% ACRYLIC * EASE OF APPLICATION * PREVENTS ALKALI BURN * FAST DRYING * LOW ODOR
PRODUCT VERSATILITY * EASY CLEAN UP * MINIMIZES SURFACE DEFECTS * EXCELLENT DURABILITY

PRODUCT SPECIFICATION DATA

* COLORS:	White Only
* FINISH:	Flat
* FLASH POINT:	N/A
* METHOD USED:	T.C.C.
* COATING V.O.C.:	0.83 LB/GAL. - (100 GRAMS/LTR.)
* SOLIDS:	By Volume: 46.59% ± 2% By Weight: 52.53% ± 2%
* RECOMMENDED MIL FILM:	Wet: 22.9 Mils - (Estimated At 70 Square Feet Per Gallon). Dry: 10.7 Mils - (Estimated At 70 Square Feet Per Gallon).
* ESTIMATED COVERAGE:	Covers approximately 60 - 70 square feet per gallon, depending on type of application and the porosity of the surface.
* CLEAN UP:	Water
* THINNING:	Clean Water
* ESTIMATED DRY TIME:	Dries to the touch in approximately 2 - 4 hours, for re-coat after 4 hours or overnight dry, depending on conditions.

PRODUCT ANALYSIS DATA

PIGMENT: 31.32%

VEHICLE: 68.68%

MORE DETAILED PRODUCT ANALYSIS DATA IS AVAILABLE UPON FORMAL REQUEST.

SURFACE PREPARATION

The entire surface area to be painted should be clean, dry, sound and free from all dirt, dust, grease, oils, waxes, mildew, curing agents and any other surface contaminants. Remove any loose scale, chalked, cracked and peeling paint from previously painted surfaces by hand scraping, sanding, wire brushing and/or power tool cleaning. Repair all surface imperfections and cracks before application of coating. All cracks greater than 1/32" are to be routed open, dusted clean, sealed with **Richard's 1414, Alkali Resistant Masonry Primer** and allowed to dry properly. Pack the crack opening the properly recommended **Richard's Seal-Flex Elastomeric Masonry Patching Compound** and allow to dry. Spot prime all repaired crack areas with above reference masonry primer. Cracks less than 1/32" should be detailed with **Richard's 1414, Alkali Resistant Masonry Primer** and allowed to dry. Sand smooth all rough paint edges, as well as all rough surfaces. Prime all bare and/or new surface areas with the above referenced masonry primer before application of this finish coating.

Mildew - Surface areas affected by mildew should be washed with a commercial mildew removal product carefully following manufacturer's application and safety directions. Rinse thoroughly with clean water, and allow a minimum of 24 hours to dry thoroughly.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD, or log on to www.epa.gov/lead

PRODUCT APPLICATION

Richard's Alkali Resistant Acrylic Textured Masonry Finish is specifically designed for spray application with a hopper type texture spray system, or an airless sprayer designed for texture spraying, such as the Graco TexSpray GM1030. Apply coating in such a manner as to yield a minimum 10 mil wet film build. It may also be troweled for various designs or troweled and back-rolled with a texture roller cover to achieve different texture styles. Always maintain a wet edge and avoid excessive respreading and reworking. Avoid painting outside weather conditions are threatening and late in the afternoon when there is a threat of moisture condensing on wet paint. Apply when surface and ambient temperatures are above 55° F and below 90° F. **KEEP FROM FREEZING!**

PRECAUTIONS

CAUTION: KEEP OUT OF REACH OF CHILDREN! Avoid prolonged contact with skin and breathing of vapors and or spray mists. **USE WITH ADEQUATE VENTILATION!** Where ventilation is inadequate, use a suitable respirator. When spraying this material, use an **OSHA** approve cartridge respirator. Use chemical safety glasses, goggles, or a face shield for proper eye protection.

Wash thoroughly after handling and before eating or smoking. Close container after each use. **DO NOT TAKE INTERNALLY!**

FIRST AID: In case of skin contact, wash thoroughly with plenty of soap and water. For eye contact, flush thoroughly with plenty of water for 15 minutes, **Seek Immediate Medical Attention!** If affected by inhalation, move immediately to fresh air. If swallowed, **Do Not Induce Vomiting! Seek Immediate Medical Attention!**

MIXING INSTRUCTIONS & PACKAGING

Stir thoroughly and apply as it comes from the container. **No Thinning Is Necessary!** However, if thinning is required, you may add **Clean Water** up to 1/2 pint per gallon.

* **Pint Cans:** N/A

* **Quart Cans:** N/A

* **Gallon Cans:** N/A

* **Two Gallon Cans:** N/A

* **Five Gallon Cans:** Each

* **Weight Per Gallon:** 9.62 lbs.

ALL TECHNICAL DATA INFORMATION CONTAINED HEREIN IS ACCURATE TO THE BEST OF OUR KNOWLEDGE. ALL WARRANTIES ARE EXCLUDED, WHETHER EXPRESSED OR IMPLIED BY OPERATION OF LAW OR OTHERWISE, INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. SELLER SHALL NOT BE LIABLE, (DIRECTLY OR INDIRECTLY), UNDER ANY CIRCUMSTANCES FOR CONSEQUENTIAL, INCIDENTAL, SPECIAL OR ANY OTHER TYPE OF DAMAGES ARISING OR RESULTING FOR ANY REASON UNDER THE SALE, HANDLING, OR USE OF GOODS SOLD. SELLER'S LIABILITY HEREUNDER, AND BUYER'S EXCLUSIVE REMEDY HEREUNDER, FOR NEGLIGENCE OR ANY OTHER REASON, IS EXPRESSLY LIMITED TO REIMBURSEMENT OF THE PURCHASE PRICE OF THE MATERIALS SOLD AFTER PROOF OF PURCHASE IS PROVIDED TO THE SELLER. NOTICE OF ANY ALLEGED FAILURE OR DEFECT IN THE MATERIALS MUST GIVEN TO SELLER IN WRITING BY CERTIFIED U.S. MAIL WITHIN 15 DAYS OF FIRST NOTICING THE PROBLEM. FAILURE TO GIVE THE REQUIRED NOTICE WITHIN THE TIME PROVIDED CONSTITUTES A WAIVER OF ANY CLAIM. THE MANUFACTURER IS NOT RESPONSIBLE FOR ANY MISREPRESENTATION MADE BY THE DEALER.

Any additional information regarding our products and/or pricing is available through **Richard's Paint Mfg. Co., Inc.**, or through its local area **Richard's Representative**.