



PRODUCT TECHNICAL DATA INFORMATION

PRODUCT NO.: 350 SERIES

RICH CLASSIC ACRYLIC HOUSE PAINT

PRODUCT DESCRIPTION

Richard's Rich Classic Acrylic House Paint is an acrylic house paint formulated for both interior and exterior application. Easy to apply, it provides superior coverage, offers superior durability, and is mildew resistant. It provides superior washability, resistance to soiling and has superior weatherability. **MILDEW RESISTANT** - This paint contains agents which inhibit the growth of mildew on the surface of this paint film. **FOR INTERIOR & EXTERIOR USES!**

SUGGESTED PRODUCT USE

SUITABLE FOR APPLICATION TO THE FOLLOWING PROPERLY PREPARED SURFACES:

**DRYWALL * STUCCO * CEILINGS * MASONRY * CEMENT BLOCK * BRICK * ASBESTOS SHINGLES
INT./EXT. WOOD SIDING & WOOD TRIM**

PRODUCT FEATURES

**EXCELLENT COVERAGE * MILDEW RESISTANT * SUPERIOR DURABILITY * SUPERIOR WEATHERABILITY
NON-YELLOWING * EASY TO APPLY * CONTAINS NO LEAD PIGMENTS**

PRODUCT SPECIFICATION DATA

* COLORS:	White & Tint Bases
* FINISH:	Flat
* FLASH POINT:	232° F.
* METHOD USED:	T.C.C.
* COATING V.O.C.:	Not To Exceed - .83 LB/GAL. - (100 GRAMS/LTR.)
* SOLIDS:	By Volume: 38.00% ± 2% By Weight: 58.52% ± 2%
* RECOMMENDED MIL FILM:	Wet: 4.6 mils - (Estimated at 350 Square Feet Per Gallon). Dry: 1.7 mils - (Estimated at 350 Square Feet Per Gallon).
* ESTIMATED COVERAGE:	Covers approximately 300 - 400 square feet per gallon, depending on the type of application and the porosity of the surface area to be painted.
* CLEAN UP:	Warm Soapy Water
* THINNING:	Clean Water
* ESTIMATED DRY TIME:	Dries to the touch in approximately 1 - 2 hours, for recoat in 4 - 6 hours or after overnight dry, depending on conditions.

PRODUCT ANALYSIS DATA

PIGMENT: 47.89%

VEHICLE: 52.11%

MORE DETAILED PRODUCT ANALYSIS DATA IS AVAILABLE UPON FORMAL REQUEST.

SURFACE PREPARATION

GENERAL: The entire surface area to be painted should be clean, dry, sound and free from all dirt, grease, oils, waxes, mildew and any other surface contaminants. Remove any loose scale, chalked, cracked and/or peeling paint from previously painted surfaces by hand scraping, sanding, wire brushing and/or power tool cleaning, such as power washing or commercial sandblasting. Repair/replace any damaged and/or delaminated surface areas. Lightly sand all rough paint edges smooth to the adjacent surface area. Glossy surfaces should be lightly sanded so to effectively dull the existing sheen level. Spot prime all bare and/or new surface areas with the properly recommended primer/sealer and surfaces that show signs of chalkiness should be properly sealed with the Manufacturer's recommended chalky surface sealer.

Mildew - Surface areas affected by mildew should be washed with a commercial mildew removal product carefully following manufacturer's application and safety directions. Rinse thoroughly with clean water, and allow a minimum of 24 hours to dry thoroughly.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD, or log on to www.epa.gov/lead.

Special Note: All "NEW" cementitious surfaces, such as Stucco, Cement Block, Masonry, Poured Concrete, etc., should be allowed at least 30 days to properly dry and cure, in accordance with industry standards. This will reduce the high levels of acidity and alkalinity that are associated with new cementitious substrates. *Richard's Paint Mfg. Co., Inc.* will not be held liable for product failure if these types of substrates are painted too soon.

PRODUCT APPLICATION

Richard's Rich Classic Acrylic House Paint may be easily applied with a quality brush, roller, or airless spray equipment. If applying with a brush, apply a smooth and generous coat application on/in small surface areas, such as painting trim or cutting-in larger surface areas. If applying with a roller cover, apply an even and generous coat application in an "M" or crisscross motion, avoiding any excessive respreading or reworking. Always maintain a wet edge during paint application by brushing/rolling into previously applied coating area. If applying with an airless sprayer, it is recommended to use a unit with a minimum of 2000 psi of pressure, with a 0.017 - 0.019 fluid spray tip. During spray application, it is recommended to back-roll the surface area to ensure proper adhesion and an even coat application. If applying two finish coat applications, allow the first coat to dry thoroughly. Apply when surface and ambient temperatures are above 55° F and below 90° F. Avoid paint application outside when weather conditions are threatening and late in the afternoon when there is a threat of moisture condensing on wet paint. **KEEP FROM FREEZING!**

PRECAUTIONS

CAUTION: KEEP OUT OF REACH OF CHILDREN! Avoid prolonged contact with skin and breathing of vapors and/or spray mists. **USE WITH ADEQUATE VENTILATION!** Where ventilation is inadequate, use a suitable respirator. When spraying this material, use an **OSHA** approved cartridge respirator. Use chemical safety glasses, goggles, or a face shield for proper eye protection. Wash thoroughly after handling and before eating or smoking. Close container after each use. **DO NOT TAKE INTERNALLY!**

FIRST AID: In case of skin contact, wash thoroughly with plenty of soap and water. For eye contact, flush thoroughly with plenty of water for 15 minutes, **Seek Immediate Medical Attention!** If affected by inhalation, move immediately to fresh air. If swallowed,

Do Not Induce Vomiting, Seek Immediate Medical Attention!

MIXING INSTRUCTIONS & PACKAGING

Stir thoroughly and apply as it comes from the container. **No Thinning Is Necessary!** However, if thinning is required, you may add clean water up to ½ pint per gallon.

* **Pint Cans:** N/A

* **Quart Cans:** 6 Per Case

* **Gallon Cans:** 4 Per Case

* **Two Gallon Cans:** Each

* **Five Gallon Cans:** Each

* **Weight Per Gallon:** 12.12 lbs.

ALL TECHNICAL DATA INFORMATION CONTAINED HEREIN IS ACCURATE TO THE BEST OF OUR KNOWLEDGE. ALL WARRANTIES ARE EXCLUDED, WHETHER EXPRESSED OR IMPLIED BY OPERATION OF LAW OR OTHERWISE, INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. SELLER SHALL NOT BE LIABLE, (DIRECTLY OR INDIRECTLY), UNDER ANY CIRCUMSTANCES FOR CONSEQUENTIAL, INCIDENTAL, SPECIAL OR ANY OTHER TYPE OF DAMAGES ARISING OR RESULTING FOR ANY REASON UNDER THE SALE, HANDLING, OR USE OF GOODS SOLD. SELLER'S LIABILITY HEREUNDER, AND BUYER'S EXCLUSIVE REMEDY HEREUNDER, FOR NEGLIGENCE OR ANY OTHER REASON, IS EXPRESSLY LIMITED TO REIMBURSEMENT OF THE PURCHASE PRICE OF THE MATERIALS SOLD AFTER PROOF OF PURCHASE IS PROVIDED TO THE SELLER. NOTICE OF ANY ALLEGED FAILURE OR DEFECT IN THE MATERIALS MUST BE GIVEN TO THE SELLER IN WRITING BY CERTIFIED U.S. MAIL WITHIN 15 DAYS OF FIRST NOTICING THE PROBLEM. FAILURE TO GIVE THE REQUIRED NOTICE WITHIN THE TIME PROVIDED CONSTITUTES A WAIVER OF ANY CLAIM. THE MANUFACTURER IS NOT RESPONSIBLE FOR ANY MISREPRESENTATION MADE BY THE DEALER.

Any additional information regarding our products and/or pricing is available through **Richard's Paint Mfg. Co., Inc.**, or through its local area **Richard's Representative**.