



PRODUCT TECHNICAL DATA INFORMATION

PRODUCT NO.: 5800 SERIES

RICH-SPEC ULTRA-FLAT
INTERIOR LATEX WALL PAINT

PRODUCT DESCRIPTION

Richard's Rich-Spec Ultra-Flat Interior Latex Wall Paint is a quality professional grade interior latex wall coating developed for use by the professional painting contractor. It is specially formulated to provide superior coverage and touch-up qualities, is self-priming, and is non-yellowing. Its ease of application and product versatility allow for application to a variety of interior substrates, has good washability and durability, and is formulated to meet low VOC requirements for today's latex paint coatings. **FOR INTERIOR USE ONLY!**

SUGGESTED PRODUCT USE

SUITABLE FOR APPLICATION TO THE FOLLOWING PROPERLY PREPARED SURFACES:

CEILINGS * DRYWALL * WALLBOARD * PLASTER * MASONRY

PRODUCT FEATURES

ULTRA-FLAT FINISH * EASE OF APPLICATION * SELF-PRIMING * LOW V.O.C.
GOOD COVERAGE * GOOD TOUCH-UP QUALITIES * NON-YELLOWING * PRODUCT VERSATILITY

PRODUCT SPECIFICATION DATA

* COLORS:	White & Tinting Bases
* FINISH:	Flat
* FLASH POINT:	232° F
* METHOD USED:	T.C.C.
* COATING V.O.C.:	Not To Exceed - .42 LB/GAL. - (50 GRAMS/LTR.)
* SOLIDS:	By Volume: 30.50% ± 2% By Weight: 50.21% ± 2%
* RECOMMENDED MIL FILM:	Wet: 4.6 mils - (Estimated at 350 Square Feet Per Gallon). Dry: 1.4 mils - (Estimated at 350 Square Feet Per Gallon).
* ESTIMATED COVERAGE:	Covers approximately 300 - 400 square feet per gallon, depending on the type of application and the porosity of the surface to be painted.
* CLEAN UP:	Water
* THINNING:	Clean Water
* ESTIMATED DRY TIME:	Dries to the touch in approximately 1 - 2 hours, for recoat in 4 - 6 hours, or after overnight dry, depending on conditions.

PRODUCT ANALYSIS DATA

PIGMENT: 43.13%

VEHICLE: 56.87%



MORE DETAILED PRODUCT ANALYSIS DATA IS AVAILABLE UPON FORMAL REQUEST.

RICHARD'S PAINT MANUFACTURING COMPANY, INC. • 200 PAINT STREET • ROCKLEDGE, FL 32955
Tel: 321-636-6200 • Fax:: 321-633-0866 • Toll Free: 800-432-0983 • Web Site: www.richardspaint.com

SURFACE PREPARATION

GENERAL: The entire surface areas to be painted should be clean, dry, sound and free from all dirt, grease, oils, waxes, mildew and any other surface contaminants. Remove any loose scale, chalked, cracked or peeling paint from previously painted surface areas by hand scraping, sanding, wire brushing and/or power tool cleaning. Repair/replace any damaged and/or delaminated surface areas such as, nail holes, gouges, cracks, etc. with the properly recommended patching compounds. Lightly sand smooth all rough paint edges and surface repairs to adjacent surface area and lightly sand all glossy surface areas to effectively dull existing sheen levels. Prime and/or spot prime all bare and/or new surface areas with the Manufacturer's properly specified primer/sealers compatible to the surface type before application of finish coating.

Mildew - Surface areas affected by mildew should be washed with a commercial mildew removal product carefully following manufacturer's application and safety directions. Rinse thoroughly with clean water, and allow a minimum of 24 hours to dry thoroughly.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD, or log on to www.epa.gov/lead.

PRODUCT APPLICATION

Richard's Rich-Spec Vinyl Acrylic Ultra-Flat Interior Latex Wall Paint may be easily applied with a quality brush, roller, or airless spray equipment. If applying with a brush, apply a smooth and generous coat application on/in small surface areas, such as painting trim and cutting-in larger surface areas. If applying with a roller cover, apply an even and generous coat application in an "M" or crisscross motion, avoiding any excessive re-spreading and/or reworking. Always maintain a wet edge during paint application by brushing/rolling into previously applied coating area. If applying by airless spray equipment, it is recommended to use a unit with a minimum of 2000 psi of pressure, with a 0.017 - 0.019 fluid spray tip. During spray application, it is recommended to back-roll/brush the surface area to insure proper adhesion and an even coat application. If applying two (2) finish coats, allow the first coat application to dry thoroughly. Apply when surface and ambient temperatures are above 55° F and below 90° F. **KEEP FROM FREEZING!**

PRECAUTIONS

CAUTION: KEEP OUT OF REACH OF CHILDREN! Avoid prolonged contact with skin and breathing of vapors and/or spray mists. **USE WITH ADEQUATE VENTILATION!** Where ventilation is inadequate, use a suitable respirator. When spraying this material, use an OSHA approved cartridge respirator. Use chemical safety glasses, goggles, or a face shield for proper eye protection. Wash thoroughly after handling and before eating or smoking. Close container after each use. **DO NOT TAKE INTERNALLY!**

FIRST AID: In case of skin contact, wash thoroughly with plenty of soap and water. For eye contact, flush thoroughly with plenty of water for 15 minutes, **Seek Immediate Medical Attention!** If affected by inhalation, move immediately to fresh air. If swallowed, **Do Not Induce Vomiting, Seek Immediate Medical Attention!**

MIXING INSTRUCTIONS & PACKAGING

Stir thoroughly and apply as it comes from the container. **Thinning Is Not Necessary!** However, if thinning is required, you may add clean water up to ½ pint per gallon.

* Pint Cans: N/A

* Quart Cans: N/A

* Gallon Cans: 4 Per Case

* Two Gallon Cans: N/A

* Five Gallon Cans: Each

* Weight Per Gallon: 11.66 lbs.

ALL TECHNICAL DATA INFORMATION CONTAINED HEREIN IS ACCURATE TO THE BEST OF OUR KNOWLEDGE. ALL WARRANTIES ARE EXCLUDED, WHETHER EXPRESSED OR IMPLIED BY OPERATION OF LAW OR OTHERWISE, INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. SELLER SHALL NOT BE LIABLE, (DIRECTLY OR INDIRECTLY), UNDER ANY CIRCUMSTANCES FOR CONSEQUENTIAL, INCIDENTAL, SPECIAL OR ANY OTHER TYPE OF DAMAGES ARISING OR RESULTING FOR ANY REASON UNDER THE SALE, HANDLING, OR USE OF GOODS SOLD. SELLER'S LIABILITY HEREUNDER, AND BUYER'S EXCLUSIVE REMEDY HEREUNDER, FOR NEGLIGENCE OR ANY OTHER REASON, IS EXPRESSLY LIMITED TO REIMBURSEMENT OF THE PURCHASE PRICE OF THE MATERIALS SOLD AFTER PROOF OF PURCHASE IS PROVIDED TO THE SELLER. NOTICE OF ANY ALLEGED FAILURE OR DEFECT IN THE MATERIALS MUST BE GIVEN TO SELLER IN WRITING BY CERTIFIED U.S. MAIL WITHIN 15 DAYS OF FIRST NOTICING THE PROBLEM. FAILURE TO GIVE THE REQUIRED NOTICE WITHIN THE TIME PROVIDED CONSTITUTES A WAIVER OF ANY CLAIM. THE MANUFACTURER IS NOT RESPONSIBLE FOR ANY MISREPRESENTATION MADE BY THE DEALER.

Any additional information regarding our products and/or pricing is available through **Richard's Paint Mfg. Co., Inc.**, or through its local area **Richard's Representative**.