



PRODUCT TECHNICAL DATA INFORMATION

PRODUCT NO.: 6-3500 SERIES

ULTRA-FLAT VINYL ACRYLIC WALL PAINT

PRODUCT DESCRIPTION

Richard's Ultra-Flat Vinyl Acrylic Wall Paint is a professional quality latex wall coating that has been formulated for use on a variety of interior and exterior substrates. It provides excellent coverage, superior touch-up qualities, is non-yellowing. It is self priming on specified substrates, offers superior durability, is mildew resistant, resists streaking and lap marks, has excellent color retention and is easy to apply. **Mildew Resistant** - This paint contains agents which inhibit the growth of mildew on the surface of this paint film.

FOR INTERIOR & EXTERIOR USE!

SUGGESTED PRODUCT USE

SUITABLE FOR APPLICATION TO THE FOLLOWING PROPERLY PREPARED SURFACES:

DRYWALL * PLASTER * CEILINGS * MASONRY * BRICK * CEMENT BLOCK * STUCCO

PRODUCT FEATURES

**EXCELLENT COVERAGE * PROFESSIONAL QUALITY * NON-YELLOWING * SUPERIOR TOUGH-UP * MILDEW RESISTANT
SELF PRIMING * MILDEW RESISTANT * SUPERIOR DURABILITY * PRODUCT VERSATILITY**

PRODUCT SPECIFICATION DATA

* COLORS:	White, Tint Base
* FINISH:	Flat
* FLASH POINT:	232° F.
* METHOD USED:	T.C.C.
* COATING V.O.C.:	Not To Exceed 1.25 LB/GAL. - (150 GRAMS/LTR.)
* SOLIDS:	By Volume: 30.86% ± 2% By Weight: 49.88% ± 2%
* RECOMMENDED MIL FILM:	Wet: 4.6 mils - (Estimated @ 350 Square Feet Per Gallon). Dry: 1.4 mils - (Estimated @ 350 Square Feet Per Gallon).
* ESTIMATED COVERAGE:	Covers approximately 300 - 400 square feet per gallon, depending on the type of application and the porosity of the surface area to be painted.
* CLEAN UP:	Water
* THINNING:	Clean Water
* ESTIMATED DRY TIME:	Dries to the touch in approximately 1 hour, for recoat in approximately 4 - 6 hours or after overnight dry, depending on conditions.

PRODUCT ANALYSIS DATA

PIGMENT: 40.01%

VEHICLE: 59.99%

MORE DETAILED PRODUCT ANALYSIS DATA IS AVAILABLE UPON FORMAL REQUEST.

SURFACE PREPARATION

GENERAL: The entire surface area to be painted should be clean, dry, sound and free from all dirt, grease, oils, waxes, mildew and any other surface contaminants that may cause paint failure. Remove any loose scale, chalked, cracked or peeling paint from previously painted surfaces by hand scraping, sanding, wire brushing and/or power tool cleaning, depending upon the surface type. Repair/replace any damaged and/or delaminated surface areas. Prime all bare and/or new surface areas with Manufacturer's properly specified primers/sealers suitable for that surface type.

Mildew - Surface areas affected by mildew should be washed with a commercial mildew removal product carefully following manufacturer's application and safety directions. Rinse thoroughly with clean water, and allow a minimum of 24 hours to dry thoroughly.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD, or log on to www.epa.gov/lead.

PRODUCT APPLICATION

Richard's Ultra-Flat Vinyl Acrylic Wall Paint may be easily applied with a quality brush, roller, or airless spray equipment. For best results, it is recommended to apply two finish coats. If applying with a brush, apply a smooth and generous coat application on/in smaller surface areas, such as painting trim or cutting-in larger surface areas. If applying by roller cover, apply an even and generous coat application in an "M" or crisscross motion, avoiding any excessive respreading or reworking. Always maintain a wet edge during application by brushing/rolling into previously applied coating area. If applying by airless spray equipment, it is recommended to use a unit with a minimum of 2000 psi of pressure with a 0.017 - 0.019 fluid spray tip. During spray application, the surface area should be back-rolled to ensure proper adhesion and an even coat application. Avoid paint application outside when weather conditions are threatening, or late in the afternoon when there is threat of moisture condensing on wet paint. Apply when surface and ambient temperatures are above 55° F and below 90° F. **KEEP FROM FREEZING!**

PRECAUTIONS

CAUTION: KEEP OUT OF REACH OF CHILDREN! Avoid prolonged contact with skin and breathing of vapors and/or spray mists. **USE WITH ADEQUATE VENTILATION!** Where ventilation is inadequate, use a suitable respirator. When spraying this material, use an OSHA approved cartridge respirator. Use chemical safety glasses, goggles, or a face shield for proper eye protection. Wash thoroughly after handling and before eating or smoking. Close container after each use. **DO NOT TAKE INTERNALLY!**

FIRST AID: In case of skin contact, wash thoroughly with plenty of soap and water. For eye contact, flush thoroughly with plenty of water for 15 minutes, **Seek Immediate Medical Attention!** If affected by inhalation, move immediately to fresh air. If swallowed, **Do Not Induce Vomiting, Seek Immediate Medical Attention!**

MIXING INSTRUCTIONS & PACKAGING

Stir thoroughly and apply as it comes from the container. **No Thinning Is Necessary!** However, if thinning is required, you may add **Clean Water** up to ½ pint per gallon.

* Pint Cans: N/A

* Quart Cans: N/A

* Gallon Cans: 4 Per Case

* Two Gallon Cans: N/A

* Five Gallon Cans: Each

* Weight Per Gallon: 11.54 lbs.

ALL TECHNICAL DATA INFORMATION CONTAINED HEREIN IS ACCURATE TO THE BEST OF OUR KNOWLEDGE. ALL WARRANTIES ARE EXCLUDED, WHETHER EXPRESSED OR IMPLIED BY OPERATION OF LAW OR OTHERWISE, INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. SELLER SHALL NOT BE LIABLE, (DIRECTLY OR INDIRECTLY), UNDER ANY CIRCUMSTANCES FOR CONSEQUENTIAL, INCIDENTAL, SPECIAL OR ANY OTHER TYPE OF DAMAGES ARISING OR RESULTING FOR ANY REASON UNDER THE SALE, HANDLING, OR USE OF GOODS SOLD. SELLER'S LIABILITY HEREUNDER, AND BUYER'S EXCLUSIVE REMEDY HEREUNDER, FOR NEGLIGENCE OR ANY OTHER REASON, IS EXPRESSLY LIMITED TO REIMBURSEMENT OF THE PURCHASE PRICE OF THE MATERIALS SOLD AFTER PROOF OF PURCHASE IS PROVIDED TO THE SELLER. NOTICE OF ANY ALLEGED FAILURE OR DEFECT IN THE MATERIALS MUST BE GIVEN TO THE SELLER IN WRITING BY CERTIFIED U.S. MAIL WITHIN 15 DAYS OF FIRST NOTICING THE PROBLEM. FAILURE TO GIVE THE REQUIRED NOTICE WITHIN THE TIME PROVIDED CONSTITUTES A WAIVER OF ANY CLAIM. THE MANUFACTURER IS NOT RESPONSIBLE FOR ANY MISREPRESENTATION MADE BY THE DEALER.

Any additional information regarding our products and/or pricing is available through **Richard's Paint Mfg. Co., Inc.**, or through its local area **Richard's Representative**.