



## PRODUCT TECHNICAL DATA INFORMATION

PRODUCT NO.: 615

### RICH WALL PREMIUM ACRYLIC CEILING PAINT

---

---

#### PRODUCT DESCRIPTION

Richard's Rich Wall Premium Acrylic Ceiling Paint has been specifically formulated to renew old ceilings and wall surfaces. Its special "Spatter Free" formulation provides a unique flat finish that actually minimizes surface defects, resists soiling, provides excellent coverage, is non-yellowing and is easy to apply. It may be tinted to pastel shades of color, dries overnight to a plaster hard-like finish that provides excellent durability, and is easily applied to both new and previously painted surfaces. **MILDEW RESISTANT** - This paint contains agents which inhibit the growth of mildew on the surface of this paint film. **FOR INTERIOR USE ONLY!**

---

---

#### SUGGESTED PRODUCT USE

*SUITABLE FOR APPLICATION TO THE FOLLOWING PROPERLY PREPARED SURFACES:*

**PLASTERED WALLS & CEILINGS \* DRYWALL \* MASONRY \* ACOUSTICAL CEILING TILES  
SKIP-TROWELED WALLS & CEILINGS**

---

---

#### PRODUCT FEATURES

**SPATTER FREE FORMULA \* MINIMIZES SURFACE DEFECTS \* EASY TO APPLY \* EXCELLENT COVERAGE  
NON-YELLOWING \* SPOT RESISTANT \* CONTAINS NO LEAD PIGMENTS**

---

---

#### PRODUCT SPECIFICATION DATA

|                                |   |
|--------------------------------|---|
| * <b>COLORS:</b>               | Ceiling White - (May be tinted up to 2 oz. with 888 Universal Colorant).  |
| * <b>FINISH:</b>               | Flat  |
| * <b>FLASH POINT:</b>          | <b>232° F.</b>  |
| * <b>METHOD USED:</b>          | <b>T.C.C.</b>   |
| * <b>COATING V.O.C.:</b>       | <b>Not To Exceed - 1.25 LB/GAL. - (150 GRAMS/LTR.)</b>  |
| * <b>SOLIDS:</b>               | By Volume: 30.34% ± 2%<br>By Weight: 49.36% ± 2%  |
| * <b>RECOMMENDED MIL FILM:</b> | Wet: 4.6 mils - (Estimated at 350 Square Feet Per Gallon).<br>Dry: 1.4 mils - (Estimated at 350 Square Feet Per Gallon).                        |
| * <b>ESTIMATED COVERAGE:</b>   | Covers approximately 300 - 400 square feet per gallon, depending on the type of application and the porosity of the surface area to be painted. |
| * <b>CLEAN UP:</b>             | <b>Warm Soapy Water</b>   |
| * <b>THINNING:</b>             | <b>Clean Water</b>  |
| * <b>ESTIMATED DRY TIME:</b>   | Dries to the touch in approximately 1 - 2 hours, for recoat in 4 - 6 hours or after overnight dry, depending on conditions.                     |

---

---

#### PRODUCT ANALYSIS DATA

**PIGMENT: 39.92%**

**VEHICLE: 60.08%**

***MORE DETAILED PRODUCT ANALYSIS DATA IS AVAILABLE UPON FORMAL REQUEST.***

## SURFACE PREPARATION

**GENERAL:** The entire surface area to be painted should be clean, dry, sound and free from all dirt, grease, oils, waxes, mildew and any other surface contaminants. Remove any loose scale, chalked, cracked or peeling paint from previously painted surface areas by hand scraping, sanding, wire brushing and/or power tool cleaning. Previously painted surfaces that exhibit signs of serious deterioration should be completely stripped to expose a more suitable surface for the application of paint coatings. Repair/replace any damaged and/or delaminated surface areas. Lightly sand smooth all rough paint edges to the adjacent surface area. Glossy surfaces should be sanded lightly to effectively dull any existing sheen levels. Prime all bare and/or new surface areas with the Manufacturer's properly specified primers/sealers compatible to the surface type before application of finish coating.

**Mildew** - Surface areas affected by mildew should be washed with a commercial mildew removal product carefully following manufacturer's application and safety directions. Rinse thoroughly with clean water, and allow a minimum of 24 hours to dry thoroughly.

**WARNING!** If you scrape, sand, or remove old paint, you may release lead dust. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD, or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

---

---

## PRODUCT APPLICATION

**Richard's Rich Wall Premium Acrylic Ceiling Paint** may be easily applied with a quality brush, roller, or airless spray equipment. For best results, it is recommended to apply by brush and/or roller cover. If applying with a brush, apply a smooth and generous coat application on smaller surface areas, such as cutting-in larger surface areas. If applying with a roller cover, apply an even and generous coat application in an "M" or crisscross motion, avoiding any excessive respreading or reworking. Always maintain a wet edge during paint application by brushing/rolling into previously applied coating area. If applying with an airless sprayer, it is recommended to use a unit with a minimum of 2500 psi of pressure, with a 0.017 - 0.019 fluid spray tip. During spray application, it is recommended to back-roll/brush the surface area to insure proper adhesion and an even coat application. On walls or ceilings that have incurred water stains, those surface areas should be properly primed with **Richard's #25 Series, Holzout Alkyd Primer/Sealer Stain Killer** before applying finish paint coating. Apply when surface and ambient temperatures are above 55° F and below 90° F. **KEEP FROM FREEZING!**

---

---

## PRECAUTIONS

**CAUTION: KEEP OUT OF REACH OF CHILDREN!** Avoid prolonged contact with skin and breathing of vapors and/or spray mists. **USE WITH ADEQUATE VENTILATION!** Where ventilation is inadequate, use a suitable respirator. When spraying this material, use an OSHA approved cartridge respirator. Use chemical safety glasses, goggles, or a face shield for proper eye protection. Wash thoroughly after handling and before eating or smoking. Close container after each use. **DO NOT TAKE INTERNALLY!**

**FIRST AID:** In case of skin contact, wash thoroughly with plenty of soap and water. For eye contact, flush thoroughly with plenty of water for 15 minutes, **Seek Immediate Medical Attention!** If affected by inhalation, move immediately to fresh air. If swallowed, **Do Not Induce Vomiting, Seek Immediate Medical Attention!**

---

---

## MIXING INSTRUCTIONS & PACKAGING

Stir thoroughly and apply as it comes from the container. **No Thinning Is Necessary!** However, if thinning is required, you may clean water up to 1/2 pint per gallon.

\* Pint Cans: N/A

\* Quart Cans: N/A

\* Gallon Cans: 4 Per Case

\* Two Gallon Cans: N/A

\* Five Gallon Cans: N/A

\* Weight Per Gallon: 11.54 lbs.

---

---

ALL TECHNICAL DATA INFORMATION CONTAINED HEREIN IS ACCURATE TO THE BEST OF OUR KNOWLEDGE. ALL WARRANTIES ARE EXCLUDED, WHETHER EXPRESSED OR IMPLIED BY OPERATION OF LAW OR OTHERWISE, INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. SELLER SHALL NOT BE LIABLE, (DIRECTLY OR INDIRECTLY), UNDER ANY CIRCUMSTANCES FOR CONSEQUENTIAL, INCIDENTAL, SPECIAL OR ANY OTHER TYPE OF DAMAGES ARISING OR RESULTING FOR ANY REASON UNDER THE SALE, HANDLING, OR USE OF GOODS SOLD. SELLER'S LIABILITY HEREUNDER, AND BUYER'S EXCLUSIVE REMEDY HEREUNDER, FOR NEGLIGENCE OR ANY OTHER REASON, IS EXPRESSLY LIMITED TO REIMBURSEMENT OF THE PURCHASE PRICE OF THE MATERIALS SOLD AFTER PROOF OF PURCHASE IS PROVIDED TO THE SELLER. NOTICE OF ANY ALLEGED FAILURE OR DEFECT IN THE MATERIALS MUST BE GIVEN TO THE SELLER IN WRITING BY CERTIFIED U.S. MAIL WITHIN 15 DAYS OF FIRST NOTICING THE PROBLEM. FAILURE TO GIVE THE REQUIRED NOTICE WITHIN THE TIME PROVIDED CONSTITUTES A WAIVER OF ANY CLAIM. THE MANUFACTURER IS NOT RESPONSIBLE FOR ANY MISREPRESENTATION MADE BY THE DEALER.

Any additional information regarding our products and/or pricing is available through **Richard's Paint Mfg. Co., Inc.**, or through its local area **Richard's Representative**.