

SAFETY DATA SHEET



315 - RICH CLASSIC CEILING PAINT

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name:	315 - RICH CLASSIC CEILING PAINT
Product Code:	315
Product Use:	Paint

Manufacturer
Richard's Paint
200 Paint Street
Rockledge, Florida,
800-432-0983

24 Hour Emergency Telephone Number
CHEMTEL (US): (800)255-3924
CHEMTEL (International): (813)248-0585

2. HAZARDS IDENTIFICATION

Classification:	This material is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200) Carcinogenicity: Category 1A
Signal Word:	Danger
Pictograms:	
Hazard Statements:	H350: May cause cancer
Prevention Precautionary Statements:	P201: Obtain special instructions before use P202: Do not handle until all safety precautions have been read and understood P281: Use personal protective equipment as required
Response Precautionary Statements:	P308+313: IF exposed: Call a POISON CENTER or doctor/physician
Storage Precautionary Statements:	P405: Store locked up
Disposal Precautionary Statements:	P501: Dispose of contents/container to an approved waste disposal plant

Hazards Not Otherwise Classified:	None
--	------

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	Weight %	CAS Number
Titanium dioxide	5% to 10%	13463-67-7
Talc	5% to 10%	14807-96-6
Mica	1% to 5%	12001-26-2
Diatomite	1% to 5%	61790-53-2
Ethylene glycol	0% to 1%	107-21-1
Silicon dioxide	0% to 1%	7631-86-9
Crystalline silica	0% to 1%	14808-60-7
4,4-dimethyloxazolidine	0% to 1%	51200-87-4

4. FIRST AID MEASURES

General Advice:	No hazards requiring special first aid measures
Eyes:	Remove contact lenses, if applicable. Flush eyes with water for at least 15 minutes. Consult a physician.
Skin:	Remove contaminated clothing. Flush affected area with soap and water.
Ingestion:	Remove dentures if applicable and wash out mouth with water. Drink large amounts of water. Consult a physician if necessary.
Inhalation:	Move to fresh air. Consult a physician if necessary.
Most Important Symptoms/Effects:	None known
Notes to Physician:	Treat symptomatically

5. FIRE FIGHTING MEASURES

Suitable Extinguishing Media:	Use measures suitable to the circumstances and environment
Precautions for Firefighters:	Wear self-contained breathing apparatus and protective gear
Specific Hazards:	Sealed containers may rupture if exposed to high temperatures
Mechanical Impact Sensitivity:	No
Static Discharge Sensitivity:	No

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions:	Avoid contact with skin, eyes, and clothing. Avoid breathing vapors.
Other Precautions:	If safe to do so, prevent additional spillage
Clean-Up Method:	Soak up with inert absorbent material. Dispose of used absorbent in suitable containers.

7. HANDLING AND STORAGE

Handling Precautions:	Avoid contact with skin, eyes, and clothing. Avoid breathing vapors, mists, or dust. Wear respiratory equipment if ventilation is insufficient.
Storage Precautions:	Keep container tightly closed and out of reach of children
Incompatible Materials:	None

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ethylene glycol(107-21-1)		
ACGIH C:	100 mg/m3	--
Silicon dioxide(7631-86-9)		
NIOSH TWA:	6 mg/m3	--
OSHA TWA:	20 mil particles/ft3	80 mg/m3/%SiO2
Mica(12001-26-2)		
OSHA TWA:	10 mg/m3/%SiO2+2	--
Titanium dioxide(13463-67-7)		
TWA:	ACGIH: 10 mg/m3	OSHA: 15 mg/m3
Talc(14807-96-6)		
ACGIH TWA:	2 mg/m3	--
NIOSH TWA:	2 mg/m3	--
OSHA TWA:	20 mppcf	--
Crystalline silica(14808-60-7)		
ACGIH TWA:	.025 mg/m3	--
NIOSH TWA:	.05 mg/m3	--
OSHA TWA:	10 mg/m3/%SiO2+2	250 mppcf/%SiO2+5
Diatomite(61790-53-2)		
NIOSH TWA:	6 mg/m3	--
OSHA TWA:	20 mppcf	80 mg/m3/%SiO2

Engineering Measures:	Maintain adequate ventilation to keep exposure to airborne contaminants at safe levels. Use explosion-proof equipment.
Hygiene Measures:	No eating, drinking, or smoking while in use. Avoid contact with skin, eyes, and clothing. Wash hands, forearms, and face after handling. Wash contaminated clothing before re-use.
Eye/Face Protection:	Safety glasses/goggles
Skin Protection:	Protective gloves and protective clothing
Respiratory Protection:	Respiratory equipment if ventilation is inadequate

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State:	Liquid
Color:	Determined by customer (white by default)
Odor:	Little to none
Odor Threshold:	No information available
pH:	No information available
Melting Point (°F):	No information available
Boiling Point (°F):	385.0 -388
Flash Point (°F):	120.00
Flash Point Method:	Closed cup
Evaporation Rate:	No information available

Flammability (Solid/Gas):	No information available
Flammability Limits:	No information available
Vapor Pressure (mm Hg):	No information available
Vapor Density:	No information available
Specific Gravity:	No information available
% Solubility in Water:	No information available
Octanol/Water Partition Coefficient:	No information available
Auto-Ignition Temperature (°F):	No information available
Decomposition Temperature (°F):	No information available
Viscosity (KU):	No information available

10. STABILITY AND REACTIVITY

Reactivity:	Not applicable
Possibility of Hazardous Reactions:	None under normal conditions of use
Hazardous Decomposition Products:	None under normal conditions of use
Stability:	Stable under normal conditions
Incompatible Materials:	None
Conditions to Avoid:	Freezing

11. TOXICOLOGICAL INFORMATION

Ethylene glycol(107-21-1)	
Dermal LD50 (rabbit):	10626 mg/kg
Oral LD50 (rat):	4700 mg/kg
Silicon dioxide(7631-86-9)	
Oral LD50 (rat):	3160 mg/kg
Titanium dioxide(13463-67-7)	
Dermal LD50 (rabbit):	>10000 mg/kg
Oral LD50 (rat):	>10000 mg/kg

Primary Routes of Exposure:	Eye contact, skin contact, inhalation
Acute Toxicity:	No information available

Exposure Effects	
Eye Contact:	Irritation
Skin Contact:	Irritation, drying
Inhalation:	Irritation of respiratory system
Ingestion:	Gastrointestinal irritation, diarrhea, nausea, vomiting

Target Organ (Single Exposure):	No information available
Target Organ (Repeated Exposure):	Prolonged or repeated exposure may cause organ damage and cancer
Sensitization:	No information available
Neurological Effects:	No information available
Mutagenicity:	No information available
Reproductive Effects:	No information available
Developmental Effects:	No information available
Other:	No information available

12. ECOLOGICAL INFORMATION

Ethylene glycol(107-21-1)	
EC50 (water flea, 24 hrs):	74000 mg/L
LC50 (golden orfe, 48 hrs):	>10000 mg/L
LC50 (rainbow trout, 96 hrs):	18500 mg/kg
LC50 (water flea, 48 hrs):	41000 mg/L
NOEC (fathead minnow, 7 days):	32000 mg/L
NOEC (fathead minnow, 96 hrs):	39140 mg/L
NOEC (water flea, 48 hrs):	24000 mg/L
Titanium dioxide(13463-67-7)	
EC50 (water flea, 48 hrs):	>1000 mg/L
LC50 (fish, 96 hrs):	>1000 mg/L

Ecotoxicological Effects:	The environmental impact of this substance has not been fully evaluated
Acute Toxicity to Fish:	No information available
Acute Toxicity to Marine Invertebrates:	No information available
Acute Toxicity to Marine Plants:	No information available
Persistence/Degradability:	No information available
Bioaccumulative Potential:	No information available
Environmental Mobility:	No information available
Ozone:	No information available

13. DISPOSAL CONSIDERATIONS

Disposal Method:	Dispose of in accordance with federal, state, provincial, and local regulations.
-------------------------	--

14. TRANSPORT INFORMATION

DOT:	Not regulated
ICAO/IATA:	Not regulated

IMDG/IMO:	Not regulated
------------------	---------------

15. REGULATORY INFORMATION

TSCA (US):	All components are listed or exempt
DSL (Canada):	All components are listed or exempt

311/312 Hazard Categories	
Fire:	No
Pressure Generating:	No
Reactivity:	No
Acute:	No
Chronic:	Yes

SARA 313
This material does not contain any hazardous components exceeding the reporting thresholds established by SARA Title III, Section 313.


State Right-to-Know					
Chemical Name	CAS Number	MA	NJ	PA	RI
Ethylene glycol	107-21-1	X	X	X	X
Silicon dioxide	7631-86-9	X	X	X	
Mica	12001-26-2	X	X	X	
Titanium dioxide	13463-67-7	X	X	X	X
Talc	14807-96-6	X	X	X	
Crystalline silica	14808-60-7	X	X	X	X
Diatomite	61790-53-2		X		

California Proposition 65:	This product may contain small amounts of materials known to the state of California to cause cancer or reproductive harm
-----------------------------------	---

16. OTHER INFORMATION

HMIS RATING	
Health:	1*
Flammability:	0
Reactivity:	0
Personal Protection:	--

NFPA CODES



PPE rating has been left intentionally blank. Choose appropriate PPE based upon actual conditions of use.

Revision Indicator:	Revised 6/1/2016
----------------------------	------------------

Disclaimer:

The information contained in this Safety Data Sheet (SDS) is provided in good faith and is believed to be accurate as of the effective date listed. The information applies only to the product as provided and may not be valid if combined with other materials. No warranty is implied or given. The user is responsible for complying with all applicable laws and regulations.