



**PRODUCT DATA SHEET**  
**PROD. #6500**  
**RICH PRO 6000**  
**INTERIOR ACRYLIC FLAT WALL PAINT**



**PRODUCT DESCRIPTION**

Rich Pro 6000 Interior Acrylic Flat Wall Paint is quality high-performance interior flat latex paint coating, specifically developed for use by the professional paint contractor, and specially formulated for tinting light to pastel shades of color. It has been specially formulated to offer ease of application, provide excellent hide and one coat coverage, and excellent touch-up qualities. It offers superior durability, is non-yellowing, and is washable. Its product versatility allows for application to a variety of interior substrates and it is VOC compliant.

PRODUCT FEATURES	PRODUCT USES	PERFORMANCE QUALITIES								
<ul style="list-style-type: none"> <li>Durable Flat Finish</li> <li>Ease Of Application</li> <li>Excellent Hide</li> <li>Good Durability</li> <li>Low V.O.C.</li> <li>One Coat Coverage</li> <li>Excellent Touch-Up Qualities</li> <li>Self-Priming</li> <li>Product Versatility</li> </ul>	<p><i>Suitable for the following properly prepared surfaces:</i></p> <p><b>INTERIOR</b></p> <table> <tr> <td>Gypsum Drywall</td> <td>Wood Trim</td> </tr> <tr> <td>Plaster</td> <td>Masonry</td> </tr> <tr> <td>Ceilings</td> <td>Concrete</td> </tr> <tr> <td>Wallboard</td> <td>Primed Metal</td> </tr> </table> <p><b>For Interior Use Only!</b></p>	Gypsum Drywall	Wood Trim	Plaster	Masonry	Ceilings	Concrete	Wallboard	Primed Metal	<p><b>Product Quality:</b> Professional / Best</p> <p><b>Product Use:</b> Interior</p> <p><b>Application:</b> Brush, Roller Cover, &amp; Airless Spray</p> <p><b>Product System:</b> Water-Based</p> <p><b>Finish:</b> Flat</p> <p><b>V.O.C. Compliance:</b> All Areas</p>
Gypsum Drywall	Wood Trim									
Plaster	Masonry									
Ceilings	Concrete									
Wallboard	Primed Metal									

**SURFACE PREPARATION**

**General:** The entire surface area to be painted should be clean, dry, sound, and free from dirt, grease, oils, waxes, mildew, rust, efflorescence, and any other surface contaminants that may adversely affect the performance of this coating material.

- Remove any loose, scaling, cracked, blistering and peeling paint from previously painted surfaces, as well as loose rust, mil scale or white rust from metal surfaces by hand scraping, sanding, wire brushing, or by power tool cleaning methods, such as electric sanders, grinders, etc.
- Repair/replace any damaged and/or delaminated surface areas such as, nail holes, gouges, cracks, etc. with the properly recommended patching compounds. Allow all patch compounds to dry thoroughly before paint application.
- Sand smooth all rough paint edges and surface repairs to adjacent main surface area.
- To effectively dull existing sheen levels, sand all glossy surfaces.
- Prime and/or spot prime all bare or new surface areas with the Manufacturer's properly specified primer/sealers compatible to the surface type before application of finish coating.

**Mildew** - Surface areas affected by mildew should be washed with a commercial mildew removal product carefully following manufacturer's application and safety directions. Rinse thoroughly with clean water, and allow a minimum of 24 hours to dry thoroughly.

- WARNING!** If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and wet mop. Before you start, find out how you can protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-Lead, or log onto [www.epa.gov/lead](http://www.epa.gov/lead).

**PRODUCT ANALYSIS DATA**

**PIGMENT: 34.40%**

**VEHICLE: 65.60%**

*MORE DETAILED PRODUCT ANALYSIS DATA IS AVAILABLE UPON REQUEST.*

**TECHNICAL DATA**

- COLORS:** White & Bases
- TINTING:** Universal Colorants
- VEHICLE TYPE:** Vinyl Acrylic
- VISCOSITY:** 103 KU ± 2
- GLOSS @ 60°:** Flat / 0 – 5 units
- FLASH POINT:** N/A
- VOC:** Not to Exceed 50 g/l – 0.42 lb./gal.
- SOLIDS:** By Volume: 32.07% ± 2%  
By Weight: 48.05% ± 2%
- COVERAGE:** 300 – 400 Sq. Ft. / Gal.  
(Depending on Application & Surface Porosity.)
- MIL FILM:** Estimated @ 350 Sq. Ft. / Gal.  
**Wet:** 4.6 mils      **Dry:** 1.5 mils
- DRY TIME:** (@ 70° F & 50% Relative Humidity)  
To Touch: 1 – 2 Hours  
Recoat: 4 – 6 Hours, or after overnight.
- CLEAN UP:** Warm Soapy Water
- THINNING:** Clean Water

## RECOMMENDED PRIMER COATINGS

Although formulated to be self-priming on sound and properly prepared bare drywall and painted surfaces, the following Richard's primers are recommended for use with this finish coat;

- **New Gypsum Drywall / Plaster:**
  - Self-Priming
  - 26 HOLZOUT 100% Acrylic Primer/Sealer Stain Killer
  - 7-11 HOLZTITE Acrylic Enamel Undercoat
  - 7-22 HOLZTITE Alkyd Enamel Undercoat
- **New Wood:**
  - 26 HOLZOUT 100% Acrylic Primer/Sealer Stain Killer
  - 7-22 HOLZTITE Alkyd Enamel Undercoat
- **New Masonry:**
  - 151/151-A Painter's Pride Latex Masonry Block Filler
  - 1414 Rich Flex Alkali Resistant Masonry Primer
- **Previously Painted Surfaces:**
  - Self-Priming
  - 26 HOLZOUT 100% Acrylic Primer/Sealer Stain Killer

## APPLICATION EQUIPMENT

- **Brush Application:** Apply using a quality nylon, polyester, or combination nylon/polyester bristle brush.
- **Roller Application:** Apply using a  $\frac{3}{8}$ " -  $1\frac{1}{4}$ " nap synthetic or lamb's wool roller cover, depending on the texture and surface porosity.
- **Spray Application:**
  - **Pump:** Gas or Electric Airless Sprayer
  - **Pressure:** Minimum 1500 – 2000 PSI
  - **Tip:** 0.017 – 0.019 Reversible
  - **Hose:**  $\frac{1}{4}$  inch (6.3 mm) -  $\frac{3}{8}$  inch (10 mm)

## PACKAGING & WEIGHT PER GALLON

- **Packaging:**

Quarts – N/A	Gallons – 4/case
2 Gallons – N/A	5 Gallons - Each
- **Weight per Gallon:** 10.91 lbs.

## CLEAN UP & THINNING INSTRUCTIONS

**Clean Up:** Clean up any minor spills and splatters immediately with warm soapy water, as well as all painting tools and airless equipment. More serious spills should be contained and removed with inert absorbent material. Dispose of contaminated absorbent, container, and unused contents in accordance with local, state and federal regulations.

**Thinning:** Stir thoroughly and apply as it comes from the container. Thinning is not necessary. However, if thinning is required, you may add clean water up to  $\frac{1}{2}$  pint per gallon.

## WARRANTY & LIMITATIONS

The technical information contained herein is accurate to the best of our knowledge. All warranties are excluded, whether expressed or implied, by operation of law or otherwise, including all implied warranties of merchantability or fitness for a particular purpose. Seller shall not be liable, directly or indirectly, under any circumstances for consequential, incidental, special or any other type of damages arising or resulting for any reason under the sale, handling, or use of goods sold. Seller's liability hereunder, and buyer's exclusive remedy hereunder, for negligence or any other reason, is expressly limited to reimbursement of the purchase price of the materials sold after proof of purchase is provided to the seller. Notice of any alleged failure or defect in the material must be given to the seller in writing by certified U.S. mail within 15 days of noticing the problem. Failure to give the required notice within the time provided constitutes a waiver of any claim. The Manufacturer is not responsible for any misrepresentation made by the Dealer.

REV 07-22

## PRODUCT APPLICATION – General

Richard's Rich Pro 6000 Interior Acrylic Flat Wall Paint may be easily applied with a quality brush, roller cover, or airless spray equipment as follows;

- Stir thoroughly in a spiral up and down motion before and during application to keep product completely mixed.
- For best results, it is recommended to apply two (2) finish coats.
- To assure color uniformity always intermix multiple containers of custom tinted and stock colors. Apply a small test sample to verify color.
- During application, always paint to a natural break in the surface, such as a corner or edge.
- When applying by brush, apply a smooth and generous coat on smaller surface areas, such as cutting-in larger surfaces and painting trim.
- When applying by roller cover, apply an even and generous coat in a "W" or crisscross motion, avoiding any excessive respraying or reworking.
- When applying by airless spray equipment, use a unit with a minimum of 2000 psi of pressure, with a 0.017 – 0.019 fluid spray tip.
- During spray application, it is recommended to back-roll the surface area to ensure proper adhesion, and an even coat application.
- Maintain a wet edge during application by brushing, rolling or spraying into previously applied coating area.
- Apply when surface and ambient temperatures are above 55° F.

## PRODUCT LIMITATIONS

- Not for use on exterior surfaces.
- Not for use in corrosive or chemical environments.
- Not for use in areas subject to intense heat.
- Not for use on below grade substrates.

## PRECAUTIONARY & SAFETY INFORMATION

**CAUTIONS:** Avoid prolonged contact with skin, and breathing of dust, vapors and/or spray mists. Causes eye irritation. **USE WITH ADEQUATE VENTILATION!** Ensure fresh air entry during application and drying. If you experience eye water, headache or dizziness, or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriately fitted respirator, (NIOSH approved), during and after application. Follow respirator manufacturer's directions for respirator use. Avoid contact with eyes, skin and clothing. Use chemical safety glasses, goggles or a face shield for proper eye protection. Wash thoroughly after handling and before eating or smoking. Close container after each use. **DO NOT TAKE INTERNALLY!**

**FIRST AID:** In case of skin contact, wash thoroughly with plenty of warm soapy water. For eye contact, flush with plenty of water for 15 minutes and get medical attention immediately. If you experience difficulty breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately. If swallowed, do not induce vomiting, get medical attention immediately.

**KEEP OUT OF REACH OF CHILDREN!**