SAFETY DATA SHEET



2100-A - EPOXY - PART A TINTABLE WHITE SEMI GLOSS

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name:	2100-A - EPOXY - PART A TINTABLE WHITE SEMI GLOSS
Product Code:	2100-A
Product Use:	Ероху

Manufacturer

Richard's Paint 200 Paint Street Rockledge, Florida, 800-432-0983

24 Hour Emergency Telephone Number CHEMTEL (US): (800)255-3924

CHEMTEL (US): (800)255-3924 CHEMTEL (International): (813)248-0585

2. HAZARDS IDENTIFICATION

Classification:	This material is considered hazardous by the 2012 OSHA Hazard
	Communication Standard (29 CFR 1910.1200)
	Skin Sensitization: Category 1
	Carcinogenicity: Category 2
Signal Word:	
Pictograms:	
Fictograms.	
Hazard	H317: May cause an allergic skin reaction
Statements:	H351: Suspected of causing cancer
Prevention	
Precautionary	P202: Do not handle until all safety precautions have been read and
Statements:	understood
	P261: Avoid breathing dust/fumes/gas/mist/vapors/spray
	P272: Contaminated work clothing should not be allowed out of the
	workplace
	P280: Wear protective gloves/protective clothing/eye protection/face
	protection
	P281: Use personal protective equipment as required
Response	P302+352: IF ON SKIN: Wash with plenty of water
Precautionary	P308+313: IF exposed: Call a POISON CENTER or doctor/physician
Statements:	P333+313: If skin irritation or a rash occurs: Get medical
	advice/attention
	P363: Wash contaminated clothing before reuse

Storage	P405: Store locked up
Precautionary	
Statements:	
Disposal	P501: Dispose of contents/container to an approved waste disposal plant
Precautionary	
Statements:	
Hazards Not	May cause allergic skin reaction
Otherwise	
Classified:	

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	Weight %	CAS Number
Titanium dioxide	20% to 30%	13463-67-7
Calcium carbonate	10% to 20%	1317-65-3
Talc	5% to 10%	14807-96-6
2-butoxyethanol	5% to 10%	111-76-2
Ethylene glycol monopropyl	1% to 5%	2807-30-9
ether		
Crystalline silica	0% to 1%	14808-60-7
Silica gel	0% to 1%	112926-00-8

4. FIRST AID MEASURES

General Advice:	No hazards requiring special first aid measures	
Eyes:	Remove contact lenses, if applicable. Flush eyes with water for at least	
	10 minutes. Keep eyes wide open while flushing. Consult a physician if symptoms persist.	
Skin:	Remove contaminated clothing. Flush affected area with soap and water. Consult a physician if irritation persists. Wash contaminated	
	clothing before re-use.	
Ingestion:	Remove dentures if applicable and wash out mouth with water. Drink	
	large amounts of water. Consult a physician if symptoms persist.	
Inhalation:	Move to fresh air. If not breathing, give artificial respiration and consult a physician immediately. Consult a physician if symptoms persist.	
Most Important	May cause allergic skin reaction	
Symptoms/Effects:		
Notes to Physician:	Treat symptomatically	

5. FIRE FIGHTING MEASURES

Suitable Extinguishing Media:	Use measures suitable to the circumstances and environment
Precautions for Firefighters:	Wear self-contained breathing apparatus and protective gear
	Sealed containers may rupture if exposed to high temperatures

6. ACCIDENTAL RELEASE MEASURES

Personal	Use proper personal protective equipment. Avoid contact with skin,
Precautions:	eyes, and clothing. Avoid breathing vapors.
Other Precautions:	If safe to do so, prevent additional spillage

Clean-Up Method:	Soak up with non-combustible absorbent material. Dispose of used
	absorbent in suitable containers.

7. HANDLING AND STORAGE

Handling	Avoid contact with skin, eyes, and clothing. Avoid breathing vapors,	
Precautions:	mists, or dust. Wear respiratory equipment if ventilation is insufficient.	
Storage	Keep container upright, properly labeled, tightly closed, and out of reach	
Precautions:	of children in a cool, dry, well-ventilated area.	
Incompatible	None	
Materials:		

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

2-butoxyethanol(111-76-2)			
ACGIH TWA:	20 ppm		
NIOSH TWA:	5 ppm	24 mg/m3	
OSHA TWA:	50 ppm	240 mg/m3	
Calcium carbonate(1317-65-3)			
NIOSH TWA:	5 mg/m3 (respirable fraction)	10 mg/m3 (total dust)	
OSHA PEL:	5 mg/m3 (respirable fraction)	15 mg/m3 (total dust)	
Crystalline silica(14808-60-7)			
ACGIH TWA:	.025 mg/m3		
NIOSH TWA:	.05 mg/m3		
OSHA TWA:	10 mg/m3/%SiO2+2	250 mppcf/%SiO2+5	
Silica gel(112926-00-8)			
OSHA TWA:	6 mg/m3	20 mppcf	
Talc(14807-96-6)			
ACGIH TWA:	2 mg/m3		
NIOSH TWA:	2 mg/m3		
OSHA TWA:	20 mppcf		
Titanium dioxide(13463-67-7)			
TWA:	ACGIH: 10 mg/m3	OSHA: 15 mg/m3	

Engineering Measures:	
Hygiene Measures:	
Eye/Face Protection:	Safety glasses/goggles
Skin Protection:	Protective gloves and protective clothing
Respiratory	Respiratory equipment if ventilation is inadequate
Protection:	

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State:	Liquid	
Color:	Determined by customer (white by default)	
Odor:	Little to none	
Odor Threshold:	No information available	
pH:	7.7-8.3	
Melting Point (°F):	No information available	
Boiling Point (°F):	No information available	

Flash Point (°F):	>141
Flash Point	No information available
Method:	
Evaporation Rate:	No information available
Flammability	No information available
(Solid/Gas):	
Flammability	No information available
Limits:	
Vapor Pressure	No information available
(mm Hg):	
Vapor Density:	No information available
Specific Gravity:	No information available
% Solubility in	No information available
Water:	
Octanol/Water	No information available
Partition	
Coefficient:	
Auto-Ignition	No information available
Temperature (°F):	
Decomposition	No information available
Temperature (°F):	
Viscosity (KU):	100-104
Volatile Organic	158
Compounds (g/L):	

10. STABILITY AND REACTIVITY

Reactivity:	Not applicable		
Possibility of	None under normal conditions of use		
Hazardous			
Reactions:			
Hazardous	None under normal conditions of use		
Decomposition			
Products:			
Stability:	Stable under normal storage conditions		
Incompatible	None		
Materials:			
Conditions to	Freezing		
Avoid:			

11. TOXICOLOGICAL INFORMATION

2-butoxyethanol(111-76-2)			
Dermal LD50 (rabbit):	1060 mg/kg		
Intraperitoneal LD50 (rat):	220 mg/kg		
Intravenous LD50 (rat):	307 mg/kg		
Oral LD50 (rat):	880 mg/kg		
Ethylene glycol monopropyl ether(2807-30-9)			
LC50 (Inhalation - Mouse - 7 h)	1530 ppm		
LD50 (Dermal - Rabbit)	1,337 mg/kg		
LD50 (Oral - Rat)	3,089 mg/kg		
Titanium dioxide(13463-67-7)			
Dermal LD50 (rabbit):	>10000 mg/kg		
Oral LD50 (rat):	>10000 mg/kg		

Primary Routes of	Eye contact, skin contact, inhalation
Exposure:	
Acute Toxicity:	No information available

Exposure Effects	
Eye Contact:	Irritation
Skin Contact:	Irritation, drying
Inhalation:	Irritation of respiratory system
Ingestion:	Gastrointestinal irritation, diarrhea, nausea, vomiting
Target Organ	No information available
(Single Exposure):	
Target Organ	No information available
(Repeated	
Exposure):	
Sensitization:	No information available
Carcinogenicity:	No information available
Mutagenicity:	No information available
Reproductive	No information available
Toxicity:	
Other:	No information available

12. ECOLOGICAL INFORMATION

2-butoxyethanol(111-76-2)			
Biodegradability (aerobic, 28 days):	90.4%		
Growth inhibition EC50 (green algae, 72 hrs):	1840 mg/L		
Immobilization EC50 (water flea, 48 hrs):	1550 mg/L		
Static LC50 (rainbow trout, 96 hrs):	1474 mg/L		
Ethylene glycol monopropyl ether(2807-30-9)			
EC50 (Pseudokirchneriella subcapitata - 72 h)	100 mg/l		
LC50 (fathead minnow - 96 h)	5,000 mg/l		
LC50 (water flea - 48 H)	5,000 mg/l		
Titanium dioxide(13463-67-7)			
EC50 (water flea, 48 hrs):	>1000 mg/L		
LC50 (fish, 96 hrs):	>1000 mg/L		

Ecotoxicological	The environmental impact of this substance has not been fully evaluated
Effects:	
Persistence/	No information available
Degradability:	
Bioaccumulative	No information available
Potential:	
Environmental	No information available
Mobility:	
Other Effects:	No information available

13. DISPOSAL CONSIDERATIONS

Disposal Method: Dispose of in accordance with federal, state, provincial, and local regulations.

14. TRANSPORT INFORMATION

DOT: Not regulated

ICAO/IATA:	Not regulated
IMDG/IMO:	Not regulated

15. REGULATORY INFORMATION

TSCA (US):	Not all components are listed
DSL/NDSL	All components are listed or exempt
(Canada):	

<u>311/312 Hazard</u>	
<u>Categories</u>	
Fire:	No
Pressure	No
Generating:	
Reactivity:	No
Acute:	Yes
Chronic:	Yes

CERCLA Section 302	
Reportable	This material does not contain any hazardous components listed on
Quantities:	Table 302.4

SARA 313

This material does not contain any hazardous components exceeding the reporting thresholds established by SARA Title III, Section 313.

State Right-to-Know					
Chemical Name	CAS Number	MA	NJ	ΡΑ	RI
Titanium dioxide	13463-67-7	Х	Х	Х	Х
Calcium carbonate	1317-65-3	Х	Х	Х	Х
Talc	14807-96-6	Х	Х	Х	Х
2-butoxythanol	111-76-2	Х	Х	Х	Х
Ethylene glycol monopropyl ether	2807-30-9		Х	Х	
Crystalline silica	14808-60-7		Х	Х	Х
Silica gel	112926-00-8	Х	Х	Х	

California	This product does not contain any materials known to the state of	
Proposition 65:	California to cause cancer or reproductive harm.	
	Titanium dioxide and silicon dioxide (airborne, unbound particles of	
	respirable size) are known to the state of California to cause cancer. This	
	listing does not cover titanium dioxide or silicon dioxide when they	
	remain bound within a product matrix.	

16. OTHER INFORMATION

HMIS RATING		
Health:	1*	
Flammability:	0	
Reactivity:	0	
Personal Protection:		

NFPA CODES

PPE rating has been left intentionally blank. Choose appropriate PPE based upon actual conditions of use.

Revision Indicator:	Revised 2/9/2022	
Disclaimer:	The information contained in this Safety Data Sheet (SDS) is provided in	
	good faith and is believed to be accurate as of the effective date listed.	
	The information applies only to the product as provided and may not be valid if combined with other materials. No warranty is implied or given.	
	The user is responsible for complying with all applicable laws and regulations.	