



PRODUCT DATA SHEET

PROD. #51-PT

PAVER SEAL

PAVER HAZE TREATMENT



PRODUCT DESCRIPTION

Richard's Paver Seal Paver Haze Treatment is designed to work in combination with our Paver Re-Sealer to reduce and/or eliminate the blushing or white appearance due to moisture over pavers and concrete substrates. It is formulated with a special solvent that starts the solubility process that combines with the Paver Re-Sealer materials to rejuvenate the existing finish to a glossy "Wet Look" finish. This system provides the superior toughness and durability that protects against the penetration of moisture, oil and grease stains, as well as other damaging or discoloring agents. It is easy to apply, resists hot tire pick-up and is non-yellowing. For Exterior Use Only.

PRODUCT FEATURES	PRODUCT USES	PERFORMANCE QUALITIES
<ul style="list-style-type: none"> Eliminates Blushing Rejuvenates Existing Finish Moisture & Stain Resistant Reinforces Durability Reinforces Wear Resistance Easy To Apply 	<p><i>Suitable for, but not limited to the following properly prepared surfaces;</i></p> <p>EXTERIOR</p> <ul style="list-style-type: none"> Brick Pavers Stamped Concrete Patios Concrete Floors Garage Floors Warehouse Floors Kool Decks Pool Decks Loading Docks Decorative Brick Stone Cobblestone <p>For Exterior Use Only!</p>	<p>Product Quality: Specialty</p> <p>Product Use: Exterior Only</p> <p>Application: Brush, Roller & Spray</p> <p>Product System: Solvent-Based</p> <p>Sheen: N/A</p> <p>MPI Standards: No</p> <p>VOC Compliance: No</p>

SURFACE PREPARATION

GENERAL: The entire surface area to be treated should be clean, dry, sound, and free from dirt, grease, oils, waxes, mildew and any other surface contaminants that may adversely affect the performance of this product. To clean the floor, use a minimum 2000 psi pressure washer, or thoroughly scrub the floor area to be treated with a non-ammoniated detergent cleaner, such as TSP, (Tri-Sodium Phosphate). Rinse thoroughly with clean water and allow the surface to dry thoroughly for up to 12 – 24 hours before beginning haze treatment.

MILDEW: Surface areas affected by mildew should be treated with a commercial mildew removal and/or wash product carefully following manufacturer's application and safety directions. Rinse thoroughly with clean water, and allow a minimum of 24 hours to dry thoroughly.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and wet mop. Before you start, find out how you can protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-Lead, or log onto www.epa.gov/lead.

TECHNICAL DATA

- COLORS:** Clear
- TINTING:** Not Recommended
- VEHICLE TYPE:** Proprietary Solvent
- VISCOSITY:** N/A
- GLOSS @ 60°:** N/A
- FLASH POINT:** 108° F
- COATING VOC:** Not to Exceed 870 g/l – 7.31 lbs./gal
- SOLIDS BY VOLUME:** 00.00% ± 2%
- SOLIDS BY WEIGHT:** 00.00% ± 2%
- ESTIMATED COVERAGE:** 400 – 500 SFPG
(Coverage will vary significantly depending on application method, surface porosity and condition of the surface.)
- RECOMMENDED MIL FILM:** (Estimated @ 400 SFPG)
Wet: 0.0 mils **Dry:** 0.0 mils
- DRY TIME:** (@ 70° F & 50% Relative Humidity)
To Touch: 30 – 45 min.
(Actual dry time may vary according to relative humidity, temperature, color, applied film build and air movement.)
- DRIES BY:** Solvent Evaporation
- CLEAN UP:** Allow To Evaporate
- THINNING:** N/A
- WEIGHT/GAL:** 7.24 lbs.
- SHELF LIFE:** 2 - 3 years unopened.
- PACKAGING:** Qts. – N/A | Gal. – 4/cs. | 5 Gal. - Each

APPLICATION EQUIPMENT

- **Brush Application:** Apply using quality nylon, polyester or combination nylon/polyester, or a quality natural china bristle brush.
- **Roller Application:** Apply using a ¾" - ½" nap synthetic, lamb's wool or mohair roller cover, depending on texture or surface porosity.
- **Spray Application:**
 - **Pump:** Gas or Electric Airless Sprayer
 - **Pressure:** Minimum 1500 PSI
 - **Tip:** 0.011 – 0.013 Reversible
 - **Hose:** ¼ inch (6.3 mm) - ⅜ inch (10 mm)

PRODUCT LIMITATIONS

- Not for use in corrosive or chemical environments.
- Not for use in areas subject to intense heat.
- Not for use on below grade substrates.

CLEAN UP & THINNING INSTRUCTIONS

Clean Up: Any minor spills and/or spatters of Haze Treatment solvent should be allowed to evaporate. No special cleaning procedures are necessary.

Thinning: N/A

PRODUCT APPLICATION – General

Richard's Paver Seal Paver Haze Treatment may be easily applied with a quality brush, roller cover, airless spray equipment or, low-pressure pump-up sprayer as follows;

- Before application to a previously painted surface, apply a test sample to test for adhesion and compatibility.
- If excessive bubbling, wrinkling, lifting, or any other improper conditions occur, the existing coating will need to be completely removed.
- **Brush Applications:** When applying by brush, apply a smooth and generous coat on smaller surface areas, such as cutting-in larger surfaces and painting trim.
- **Roller Application:** When applying by roller cover, use a quality smooth, medium or rough nap roller, depending on surface porosity, and apply an even and generous coat in a "W" or crisscross motion, avoiding any excessive respreading or reworking.
- **Spray Application:** When applying by airless spray equipment, use a unit with a minimum of 1500 psi of pressure, with a 0.011 – 0.013 fluid spray tip.
- During spray application, the surface area should be back-rolled/brushed, to effectively spread product over existing finish and insure an even coat application.
- Apply when surface and ambient temperatures are above 55° F and below 90° F.
- Avoid exterior paint application when weather conditions are threatening, and late in the day when there is a threat of moisture condensing on wet paint.
- **SPECIAL NOTE: Surfaces must be completely dry before applying this product. Do not apply if rain is imminent. A white film may appear if moisture is present immediately before or after application of this product..**

PRECAUTIONARY & SAFETY INFORMATION

CAUTIONS: FLAMMABLE! CONTAINS XYLENE AND TOLUENE! Keep away from heat, sparks, and open flames. Prevent build-up of vapors by opening all windows and doors to achieve proper cross-ventilation. Do not smoke. Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors and other sources of ignition during and until all vapors are gone. **USE WITH ADEQUATE VENTILATION!** Do not breathe dusts, vapors, or spray mists. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness, or if air monitoring demonstrates vapor / mist levels are above applicable levels, wear an appropriately fitted respirator, (NIOSH approved), during and after application. Follow respirator manufacturer's directions for respirator use. Avoid contact with eye, skin and clothing. Use chemical safety glasses, goggles, or a face shield for proper eye protection. Wash thoroughly after handling, and before eating or smoking. Close container after each use. **DO NOT TAKE INTERNALLY!** Refer to MSDS for additional health and safety information.

NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the content herein may be harmful or fatal.

FIRST AID: In case of eye contact, flush immediately with plenty of water for 15 minutes, and get medical attention immediately; for skin contact, wash thoroughly with plenty of soap and water. If you experience difficulty breathing, leave area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately. If swallowed, do not induce vomiting. Get medical attention immediately.

KEEP OUT OF REACH OF CHILDREN!

LIMITED WARRANTY

Richard's Paint Mfg. Co., Inc. warrants our products to meet the application, appearance and performance properties stated on the label. This Limited Warranty shall not apply to any defect or damage resulting from improper surface preparation, structural defects, failure of a previous paint or improper application of the coating, as described in the directions on the label of this container. If this product is found not to perform as specified, Richard's Paint will, at its option and upon presentation of proof-of-purchase (the original receipt), either furnish an equivalent amount of new product or refund the original purchase price of this product to you. **ALL OTHER WARRANTIES ARE EXCLUDED BY RICHARD'S PAINT MFG. CO., INC., EXPRESSED OR IMPLIED, STATUTORY, BY OPERATION OF LAW OR OTHERWISE, INCLUDING MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.**

LIMITATIONS

Seller's liability for any reason is expressly limited to reimbursement of the purchase price of the materials sold after proof of purchase is provided to the seller. **THIS WARRANTY EXCLUDES (1) LABOR AND COSTS ASSOCIATED WITH LABOR FOR THE APPLICATION OR REMOVAL OF ANY PRODUCT, AND (2) ANY INDIRECT, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OR RESULTING FOR ANY REASON UNDER THE SALE, HANDLING, OR USE OF GOODS SOLD.** Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty gives you specific legal rights and you may also have other rights, which vary from state to state. This Limited Warranty may not be transferred or assigned.

REV 08-21