

# SAFETY DATA SHEET



## 1215 - DTM ACRYLIC PRIMER - GRAY


### 1. PRODUCT AND COMPANY IDENTIFICATION

<b>Product Name:</b>	1215 - DTM ACRYLIC PRIMER - GRAY
<b>Product Code:</b>	1215
<b>Product Use:</b>	Paint

**Manufacturer**  
Richard's Paint  
200 Paint Street  
Rockledge, Florida,  
800-432-0983

**24 Hour Emergency Telephone Number**  
CHEMTEL (US): (800)255-3924  
CHEMTEL (International): (813)248-0585

### 2. HAZARDS IDENTIFICATION

<b>Classification:</b>	This material is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200) Skin Sensitization: Category 1 Carcinogenicity: Category 2
<b>Signal Word:</b>	Warning
<b>Pictograms:</b>	
<b>Hazard Statements:</b>	H317: May cause an allergic skin reaction H351: Suspected of causing cancer
<b>Prevention Precautionary Statements:</b>	P201: Obtain special instructions before use P202: Do not handle until all safety precautions have been read and understood P261: Avoid breathing dust/fumes/gas/mist/vapors/spray P272: Contaminated work clothing should not be allowed out of the workplace P280: Wear protective gloves/protective clothing/eye protection/face protection P281: Use personal protective equipment as required
<b>Response Precautionary Statements:</b>	P302+352: IF ON SKIN: Wash with plenty of water P308+313: IF exposed: Call a POISON CENTER or doctor/physician P333+313: If skin irritation or a rash occurs: Get medical advice/attention P363: Wash contaminated clothing before reuse

<b>Storage Precautionary Statements:</b>	P405: Store locked up
<b>Disposal Precautionary Statements:</b>	P501: Dispose of contents/container to an approved waste disposal plant
<b>Hazards Not Otherwise Classified:</b>	May cause allergic skin reaction

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	Weight %	CAS Number
Calcium carbonate	10% to 20%	1317-65-3
Titanium dioxide	5% to 10%	13463-67-7
Talc	1% to 5%	14807-96-6
Dipropylene glycol methyl ether	1% to 5%	34590-94-8
Texanol ester alcohol	1% to 5%	25265-77-4
Ethylene glycol mono-2-ethylhexyl ether	0% to 1%	1559-35-9
Iron oxide black	0% to 1%	1317-61-9
Silicon dioxide	0% to 1%	7631-86-9
Hydrous alumino silicate	0% to 1%	8031-18-3
Alumina trihydrate	0% to 1%	21645-51-2
Polyethylene glycol tert-octylphenyl ether	0% to 1%	9036-19-5
Crystalline silica	0% to 1%	14808-60-7
Ammonium hydroxide	0% to 1%	1336-21-6

### 4. FIRST AID MEASURES

<b>General Advice:</b>	No hazards requiring special first aid measures
<b>Eyes:</b>	Remove contact lenses, if applicable. Flush eyes with water for at least 10 minutes. Keep eyes wide open while flushing. Consult a physician if symptoms persist.
<b>Skin:</b>	Remove contaminated clothing. Flush affected area with soap and water. Consult a physician if irritation persists. Wash contaminated clothing before re-use.
<b>Ingestion:</b>	Remove dentures if applicable and wash out mouth with water. Drink large amounts of water. Consult a physician if symptoms persist.
<b>Inhalation:</b>	Move to fresh air. If not breathing, give artificial respiration and consult a physician immediately. Consult a physician if symptoms persist.
<b>Most Important Symptoms/Effects:</b>	May cause allergic skin reaction
<b>Notes to Physician:</b>	Treat symptomatically

### 5. FIRE FIGHTING MEASURES

<b>Suitable Extinguishing Media:</b>	Use measures suitable to the circumstances and environment
<b>Precautions for Firefighters:</b>	Wear self-contained breathing apparatus and protective gear

<b>Specific Hazards:</b>	Sealed containers may rupture if exposed to high temperatures
--------------------------	---

## 6. ACCIDENTAL RELEASE MEASURES

<b>Personal Precautions:</b>	Use proper personal protective equipment. Avoid contact with skin, eyes, and clothing. Avoid breathing vapors.
<b>Other Precautions:</b>	If safe to do so, prevent additional spillage
<b>Clean-Up Method:</b>	Soak up with non-combustible absorbent material. Dispose of used absorbent in suitable containers.

## 7. HANDLING AND STORAGE

<b>Handling Precautions:</b>	Avoid contact with skin, eyes, and clothing. Avoid breathing vapors, mists, or dust. Wear respiratory equipment if ventilation is insufficient.
<b>Storage Precautions:</b>	Keep container upright, properly labeled, tightly closed, and out of reach of children in a cool, dry, well-ventilated area.
<b>Incompatible Materials:</b>	None

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ammonium hydroxide(1336-21-6)		
ACGIH STEL:	35 ppm	--
ACGIH TWA:	25 ppm	--
NIOSH ST:	35 ppm	27 mg/m <sup>3</sup>
NIOSH TWA:	25 ppm	18 mg/m <sup>3</sup>
Calcium carbonate(1317-65-3)		
NIOSH TWA:	5 mg/m <sup>3</sup> (respirable fraction)	10 mg/m <sup>3</sup> (total dust)
OSHA PEL:	5 mg/m <sup>3</sup> (respirable fraction)	15 mg/m <sup>3</sup> (total dust)
Crystalline silica(14808-60-7)		
ACGIH TWA:	.025 mg/m <sup>3</sup>	--
NIOSH TWA:	.05 mg/m <sup>3</sup>	--
OSHA TWA:	10 mg/m <sup>3</sup> /%SiO <sub>2</sub> +2	250 mppcf/%SiO <sub>2</sub> +5
Dipropylene glycol methyl ether(34590-94-8)		
ACGIH STEL:	150 ppm	--
ACGIH TWA:	100 ppm	--
NIOSH ST:	150 ppm	900 mg/m <sup>3</sup>
OSHA TWA:	100 ppm	600 mg/m <sup>3</sup>
Silicon dioxide(7631-86-9)		
NIOSH TWA:	6 mg/m <sup>3</sup>	--
OSHA TWA:	20 mil particles/ft <sup>3</sup>	80 mg/m <sup>3</sup> /%SiO <sub>2</sub>
Talc(14807-96-6)		
ACGIH TWA:	2 mg/m <sup>3</sup>	--
NIOSH TWA:	2 mg/m <sup>3</sup>	--
OSHA TWA:	20 mppcf	--
Titanium dioxide(13463-67-7)		
TWA:	ACGIH: 10 mg/m <sup>3</sup>	OSHA: 15 mg/m <sup>3</sup>

<b>Engineering Measures:</b>	Maintain adequate ventilation to keep exposure to airborne contaminants at safe levels. Use explosion-proof equipment.
<b>Hygiene Measures:</b>	No eating, drinking, or smoking while in use. Avoid contact with skin, eyes, and clothing. Wash hands, forearms, and face after handling. Wash contaminated clothing before re-use.

<b>Eye/Face Protection:</b>	Safety glasses/goggles
<b>Skin Protection:</b>	Protective gloves and protective clothing
<b>Respiratory Protection:</b>	Respiratory equipment if ventilation is inadequate

## 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>Physical State:</b>	Liquid
<b>Color:</b>	Gray
<b>Odor:</b>	Little to none
<b>Odor Threshold:</b>	No information available
<b>pH:</b>	8.5-9.0
<b>Melting Point (°F):</b>	No information available
<b>Boiling Point (°F):</b>	100.0 -212
<b>Flash Point (°F):</b>	165.00
<b>Flash Point Method:</b>	Closed cup
<b>Evaporation Rate:</b>	No information available
<b>Flammability (Solid/Gas):</b>	No information available
<b>Flammability Limits:</b>	No information available
<b>Vapor Pressure (mm Hg):</b>	No information available
<b>Vapor Density:</b>	No information available
<b>Specific Gravity:</b>	No information available
<b>% Solubility in Water:</b>	No information available
<b>Octanol/Water Partition Coefficient:</b>	No information available
<b>Auto-Ignition Temperature (°F):</b>	No information available
<b>Decomposition Temperature (°F):</b>	No information available
<b>Viscosity (KU):</b>	100-105
<b>Volatile Organic Compounds (g/L):</b>	197.7

## 10. STABILITY AND REACTIVITY

<b>Reactivity:</b>	Not applicable
<b>Possibility of Hazardous Reactions:</b>	None under normal conditions of use
<b>Hazardous Decomposition Products:</b>	None under normal conditions of use
<b>Stability:</b>	Stable under normal storage conditions
<b>Incompatible Materials:</b>	None
<b>Conditions to Avoid:</b>	Freezing

**11. TOXICOLOGICAL INFORMATION**

Alumina trihydrate(21645-51-2)	
Oral LD50 (rat):	>2000 mg/kg
Dipropylene glycol methyl ether(34590-94-8)	
Dermal LD50 (rabbit):	9510 mg/kg
Oral LD50 (rat):	>5000 mg/kg
Ethylene glycol mono-2-ethylhexyl ether(1559-35-9)	
Dermal LD50 (rabbit):	1870 mg/kg
Oral LD50 (mouse):	3898 mg/kg
Oral LD50 (rat):	3080 mg/kg
Iron oxide black(1317-61-9)	
Oral LD50 (rat):	>5000 mg/kg
Polyethylene glycol tert-octylphenyl ether(9036-19-5)	
Dermal LD50 (rabbit):	>3000 mg/kg
Oral LD50 (rat):	1900-5000 mg/kg
Silicon dioxide(7631-86-9)	
Oral LD50 (rat):	3160 mg/kg
Texanol ester alcohol(25265-77-4)	
Dermal LD50 (rabbit):	15200 mg/kg
Oral LD50 (rat):	6500 mg/kg
Titanium dioxide(13463-67-7)	
Dermal LD50 (rabbit):	>10000 mg/kg
Oral LD50 (rat):	>10000 mg/kg

<b>Primary Routes of Exposure:</b>	Eye contact, skin contact, inhalation
<b>Acute Toxicity:</b>	No information available

<b>Exposure Effects</b>	
<b>Eye Contact:</b>	Irritation
<b>Skin Contact:</b>	Irritation, drying
<b>Inhalation:</b>	Irritation of respiratory system
<b>Ingestion:</b>	Gastrointestinal irritation, diarrhea, nausea, vomiting
<b>Target Organ (Single Exposure):</b>	No information available
<b>Target Organ (Repeated Exposure):</b>	No information available
<b>Sensitization:</b>	No information available
<b>Carcinogenicity:</b>	No information available
<b>Mutagenicity:</b>	No information available
<b>Reproductive Toxicity:</b>	No information available
<b>Other:</b>	No information available

**12. ECOLOGICAL INFORMATION**

Alumina trihydrate(21645-51-2)	
Semi-static NOEC (salmo trutta, 96 hrs):	>0.07 mg/L
Static NOEC (algae, 72 hrs):	>0.004 mg/L
Static NOEC (water flea, 48 hrs):	>0.005 mg/L
Dipropylene glycol methyl ether(34590-94-8)	
Biodegradability (aerobic, 28 days):	76%

Growth inhibition EC50 (Pseudokirchneriella subcapitata, 72 hrs):	>969 mg/L
Immobilization EC50 (water flea, 48 hrs):	1919 mg/L
Static LC50 (guppy, 96 hrs):	>1000 mg/L
Polyethylene glycol tert-octylphenyl ether(9036-19-5)	
IC50 (bacteria, 16 hrs):	5000 mg/L
LC50 (fathead minnow, 96 hrs):	4-8.9 mg/L
LC50 (water flea, 48 hrs):	18-26 mg/L
Texanol ester alcohol(25265-77-4)	
Biodegradability (aerobic, 28 days):	>98%
Static EC50 (green algae, 72 hrs):	18.4 mg/L
Static EC50 (water flea, 48 hrs):	147.8 mg/L
Static LC50 (fathead minnow, 96 hrs):	33 mg/L
Titanium dioxide(13463-67-7)	
EC50 (water flea, 48 hrs):	>1000 mg/L
LC50 (fish, 96 hrs):	>1000 mg/L

<b>Ecotoxicological Effects:</b>	The environmental impact of this substance has not been fully evaluated
<b>Persistence/Degradability:</b>	No information available
<b>Bioaccumulative Potential:</b>	No information available
<b>Environmental Mobility:</b>	No information available
<b>Other Effects:</b>	No information available

### 13. DISPOSAL CONSIDERATIONS

<b>Disposal Method:</b>	Dispose of in accordance with federal, state, provincial, and local regulations.
-------------------------	--

### 14. TRANSPORT INFORMATION

<b>DOT:</b>	Not regulated
<b>ICAO/IATA:</b>	Not regulated
<b>IMDG/IMO:</b>	Not regulated

### 15. REGULATORY INFORMATION

<b>TSCA (US):</b>	All components are listed or exempt
<b>DSL/NDSL (Canada):</b>	All components are listed or exempt

<b>311/312 Hazard Categories</b>	
<b>Fire:</b>	No
<b>Pressure Generating:</b>	No
<b>Reactivity:</b>	No
<b>Acute:</b>	Yes
<b>Chronic:</b>	Yes

<b>CERCLA Section 302</b>	
<b>Reportable Quantities:</b>	Ammonium hydroxide, 1000 lbs

**SARA 313**  
This material does not contain any hazardous components exceeding the reporting thresholds established by SARA Title III, Section 313.


<b>State Right-to-Know</b>					
<b>Chemical Name</b>	<b>CAS Number</b>	<b>MA</b>	<b>NJ</b>	<b>PA</b>	<b>RI</b>
Calcium carbonate	1317-65-3	X	X	X	X
Titanium dioxide	13463-67-7	X	X	X	X
Talc	14807-96-6	X	X	X	X
Dipropylene glycol methyl ether	34590-94-8	X	X	X	X
Texanol ester alcohol	25265-77-4		X	X	
Ethylene glycol mono-2-ethylhexyl ether	1559-35-9		X	X	
Iron oxide black	1317-61-9		X	X	
Silicon dioxide	7631-86-9	X	X	X	
Hydrous alumino silicate	8031-18-3		X	X	
Alumina trihydrate	21645-51-2		X	X	
Polyethylene glycol tert-octylphenyl ether	9036-19-5		X	X	
Crystalline silica	14808-60-7		X	X	X
Ammonium hydroxide	1336-21-6	X	X	X	

**California Proposition 65:** This product does not contain any materials known to the state of California to cause cancer or reproductive harm

**16. OTHER INFORMATION**

<b>HMIS RATING</b>	
Health:	1*
Flammability:	0
Reactivity:	0
Personal Protection:	--

**NFPA CODES**



PPE rating has been left intentionally blank. Choose appropriate PPE based upon actual conditions of use.

<b>Revision Indicator:</b>	Revised 6/29/2017
<b>Disclaimer:</b>	The information contained in this Safety Data Sheet (SDS) is provided in good faith and is believed to be accurate as of the effective date listed. The information applies only to the product as provided and may not be valid if combined with other materials. No warranty is implied or given. The user is responsible for complying with all applicable laws and regulations.