SAFETY DATA SHEET



1230 - EXCEL Waterborne Bonding Primer Green

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name:	EXCEL Waterborne Bonding Primer Green	
Product Code:	1230	
Product Use:	Primer	

Manufacturer Richard's Paint 200 Paint Street Rockledge, Florida, 800-432-0983

24 Hour Emergency Telephone Number

CHEMTEL (US): (800)255-3924 CHEMTEL (International): (813)248-0585

2. HAZARDS IDENTIFICATION

Classification:	
	Communication Standard (29 CFR 1910.1200)
	Skin Sensitization: Category 1
	Carcinogenicity: Category 2
Signal Word:	Warning
Pictograms:	
Hazard	H317: May cause an allergic skin reaction
Statements:	H351: Suspected of causing cancer
Prevention	P201: Obtain special instructions before use
Precautionary	P202: Do not handle until all safety precautions have been read and
Statements:	understood
	P261: Avoid breathing dust/fumes/gas/mist/vapors/spray
	P272: Contaminated work clothing should not be allowed out of the workplace
	P280: Wear protective gloves/protective clothing/eye protection/face
	protection
	P281: Use personal protective equipment as required
Response	P302+352: IF ON SKIN: Wash with plenty of water
Precautionary	P308+313: IF exposed: Call a POISON CENTER or doctor/physician
Statements:	P333+313: If skin irritation or a rash occurs: Get medical
	advice/attention
	P363: Wash contaminated clothing before reuse

Date Issued: 3/20/2018 SDS Ref. #: 1230 Page 1 of 7

Storage	P405: Store locked up
Precautionary	
Statements:	
Disposal	P501: Dispose of contents/container to an approved waste disposal plant
Precautionary	
Statements:	
Hazards Not	May cause allergic skin reaction
Otherwise	
Classified:	

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	Weight %	CAS Number
Di(propylene glycol) butyl ether	1% to 5%	29911-28-2
2-butoxyethanol	0% to 1%	111-76-2
Diethylene glycol butyl ether	0% to 1%	112-34-5
4,4-dimethyloxazolidine	0% to 1%	51200-87-4
Ethylene glycol	0% to 1%	107-21-1

4. FIRST AID MEASURES

General Advice:	No hazards requiring special first aid measures
Eyes:	Remove contact lenses, if applicable. Flush eyes with water for at least
	10 minutes. Keep eyes wide open while flushing. Consult a physician if
	symptoms persist.
Skin:	Remove contaminated clothing. Flush affected area with soap and
	water. Consult a physician if irritation persists. Wash contaminated
	clothing before re-use.
Ingestion:	Remove dentures if applicable and wash out mouth with water. Drink
	large amounts of water. Consult a physician if symptoms persist.
Inhalation:	Move to fresh air. If not breathing, give artificial respiration and consult
	a physician immediately. Consult a physician if symptoms persist.
Most Important	May cause allergic skin reaction
Symptoms/Effects:	
Notes to Physician:	Treat symptomatically

5. FIRE FIGHTING MEASURES

Suitable Extinguishing Media:	Use measures suitable to the circumstances and environment
Precautions for	Wear self-contained breathing apparatus and protective gear
Firefighters:	
Specific Hazards:	Sealed containers may rupture if exposed to high temperatures

6. ACCIDENTAL RELEASE MEASURES

Personal	Use proper personal protective equipment. Avoid contact with skin,	
Precautions:	eyes, and clothing. Avoid breathing vapors.	
Other Precautions:	If safe to do so, prevent additional spillage	
Clean-Up Method:	Soak up with non-combustible absorbent material. Dispose of used	
_	absorbent in suitable containers.	

Date Issued: 3/20/2018 SDS Ref. #: 1230 Page 2 of 7

7. HANDLING AND STORAGE

Handling	Avoid contact with skin, eyes, and clothing. Avoid breathing vapors,
Precautions:	mists, or dust. Wear respiratory equipment if ventilation is insufficient.
Storage	Keep container upright, properly labeled, tightly closed, and out of reach
Precautions:	of children in a cool, dry, well-ventilated area.
Incompatible	None
Materials:	

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

2-butoxyethanol(111-76-2)		
ACGIH TWA:	20 ppm	
NIOSH TWA:	5 ppm	24 mg/m3
OSHA TWA:	50 ppm	240 mg/m3
Diethylene glycol butyl ether(112-34-5)		
ACGIH TWA:	10 ppm	
Ethylene glycol(107-21-1)		
ACGIH C:	100 mg/m3	

Engineering	Maintain adequate ventilation to keep exposure to airborne
Measures:	contaminants at safe levels. Use explosion-proof equipment.
Hygiene Measures:	No eating, drinking, or smoking while in use. Avoid contact with skin,
	eyes, and clothing. Wash hands, forearms, and face after handling.
	Wash contaminated clothing before re-use.
Eye/Face	Safety glasses/goggles
Protection:	
Skin Protection:	Protective gloves and protective clothing
Respiratory	Respiratory equipment if ventilation is inadequate
Protection:	

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State:	Liquid
Color:	Green
Odor:	Little to none
Odor Threshold:	No information available
pH:	No information available
Melting Point (°F):	No information available
Boiling Point (°F):	No information available
Flash Point (°F):	215
Flash Point	No information available
Method:	
Evaporation Rate:	No information available
Flammability	No information available
(Solid/Gas):	
Flammability	No information available
Limits:	
Vapor Pressure	No information available
(mm Hg):	
Vapor Density:	No information available
Specific Gravity:	No information available
% Solubility in	No information available
Water:	

Date Issued: 3/20/2018 SDS Ref. #: 1230 Page 3 of 7

Octanol/Water	No information available
Partition	
Coefficient:	
Auto-Ignition	No information available
Temperature (°F):	
Decomposition	No information available
Temperature (°F):	
Viscosity (KU):	No information available
Volatile Organic	103
Compounds (g/L):	

10. STABILITY AND REACTIVITY

Reactivity:	Not applicable
Possibility of	None under normal conditions of use
Hazardous	
Reactions:	
Hazardous	None under normal conditions of use
Decomposition	
Products:	
Stability:	Stable under normal storage conditions
Incompatible	None
Materials:	
Conditions to	Freezing
Avoid:	

11. TOXICOLOGICAL INFORMATION

2-butoxyethanol(111-76-2)	
Dermal LD50 (rabbit):	1060 mg/kg
Intraperitoneal LD50 (rat):	220 mg/kg
Intravenous LD50 (rat):	307 mg/kg
Oral LD50 (rat):	880 mg/kg
Di(propylene glycol) butyl ether(29911-28-2)	
Dermal LD50 (rat):	>2,000 mg/kg
Oral LD50 (rat):	4,000 mg/kg
Diethylene glycol butyl ether(112-34-5)	
Dermal LD50 (rabbit):	2764 mg/kg
Oral LD50 (rat):	7291 mg/kg
Ethylene glycol(107-21-1)	
Dermal LD50 (rabbit):	10626 mg/kg
Oral LD50 (rat):	4700 mg/kg

Primary Routes of	Eye contact, skin contact, inhalation
Exposure:	
Acute Toxicity:	No information available

Exposure Effects	
Eye Contact:	Irritation
Skin Contact:	Irritation, drying
Inhalation:	Irritation of respiratory system
Ingestion:	Gastrointestinal irritation, diarrhea, nausea, vomiting
Target Organ	No information available
(Single Exposure):	

Date Issued: 3/20/2018 SDS Ref. #: 1230 Page 4 of 7

Target Organ	No information available
(Repeated	
Exposure):	
Sensitization:	No information available
Carcinogenicity:	No information available
Mutagenicity:	No information available
Reproductive	No information available
Toxicity:	
Other:	No information available

12. ECOLOGICAL INFORMATION

2-butoxyethanol(111-76-2)		
Biodegradability (aerobic, 28 days):	90.4%	
Growth inhibition EC50 (green algae, 72 hrs):	1840 mg/L	
Immobilization EC50 (water flea, 48 hrs):	1550 mg/L	
Static LC50 (rainbow trout, 96 hrs):	1474 mg/L	
Di(propylene glycol) butyl ether(29911-28-2)		
EC50 (Water flea - 48 h)	1,000 mg/l	
LC50 (other fish - 96 h)	841 mg/l	
Diethylene glycol butyl ether(112-34-5)		
Biodegradability (aerobic, 28 days):	91.7%	
LC50 (Pseudomonas putida, 16 hrs):	1170 mg/L	
Static EC50 (Scenedesmus subspicatus, 96 hrs):	>100 mg/L	
Static EC50 (water flea, 48 hrs):	>100 mg/L	
Static LC50 (Lepomis macrochirus, 96 hrs):	1300 mg/L	
Ethylene glycol(107-21-1)	-	
EC50 (water flea, 24 hrs):	74000 mg/L	
LC50 (golden orfe, 48 hrs):	>10000 mg/L	
LC50 (rainbow trout, 96 hrs):	18500 mg/kg	
LC50 (water flea, 48 hrs):		
NOEC (fathead minnow, 7 days):	32000 mg/L	
NOEC (fathead minnow, 96 hrs):	39140 mg/L	
NOEC (water flea, 48 hrs):		

Ecotoxicological	The environmental impact of this substance has not been fully evaluated
Effects:	
Persistence/	No information available
Degradability:	
Bioaccumulative	No information available
Potential:	
Environmental	No information available
Mobility:	
Other Effects:	No information available

13. DISPOSAL CONSIDERATIONS

Disposal Method:	Dispose of in accordance with federal, state, provincial, and local
	regulations.

Date Issued: 3/20/2018 SDS Ref. #: 1230 Page 5 of 7

14. TRANSPORT INFORMATION

DOT:	Not regulated
ICAO/IATA:	Not regulated
IMDG/IMO:	Not regulated

15. REGULATORY INFORMATION

TSCA (US):	All components are listed or exempt
DSL/NDSL	All components are listed or exempt
(Canada):	

311/312 Hazard	
<u>Categories</u>	
Fire:	No
Pressure	No
Generating:	
Reactivity:	No
Acute:	Yes
Chronic:	Yes

CERCLA Section	
<u>302</u>	
Reportable	Ethylene glycol, 5000 lbs
Quantities:	

SARA 313

This material does not contain any hazardous components exceeding the reporting thresholds established by SARA Title III, Section 313.


State Right-to-Know						
Chemical Name	CAS Number	MA	NJ	PA	RI	
Di(propylene glycol) butyl ether	29911-28-2		Χ	X		
2-butoxythanol	111-76-2	X	Χ	Х	Х	
Diethylene glycol butyl ether	112-34-5		Χ	Х		
4,4-dimethyloxazolidine	51200-87-4		Χ	Х		
Ethylene glycol	107-21-1	X	Χ	Х	Χ	

California	This product contains small amounts of materials known to the state of
Proposition 65:	California to cause cancer or reproductive harm.

Date Issued: 3/20/2018 SDS Ref. #: 1230 Page 6 of 7

16. OTHER INFORMATION

HMIS RATING		
Health:	1*	
Flammability:	0	
Reactivity:	0	
Personal Protection:		



PPE rating has been left intentionally blank. Choose appropriate PPE based upon actual conditions of use.

Revision Indicator:	Revised 3/20/2018	
Disclaimer:	The information contained in this Safety Data Sheet (SDS) is provided in	
	good faith and is believed to be accurate as of the effective date listed.	
	The information applies only to the product as provided and may not be valid if combined with other materials. No warranty is implied or given.	
	The user is responsible for complying with all applicable laws and regulations.	

Date Issued: 3/20/2018 SDS Ref. #: 1230 Page 7 of 7