

SAFETY DATA SHEET



2200-TH - EPOXY THINNER

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name:	2200-TH - EPOXY THINNER
Product Code:	2200-TH
Product Use:	Thinner

Manufacturer
Richard's Paint
200 Paint Street
Rockledge, Florida,
800-432-0983

24 Hour Emergency Telephone Number
CHEMTEL (US): (800)255-3924
CHEMTEL (International): (813)248-0585

2. HAZARDS IDENTIFICATION

Classification:	This material is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200) Skin Corrosion/Irritation: Category 2 Specific Target Organ Toxicity (Single Exposure): Category 3 Aspiration Toxicity: Category 1 Skin Sensitization: Category 1 Reproductive Toxicity: Category 2 Specific Target Organ Toxicity (Repeated Exposure): Category 2 Flammable Liquid: Category 2
Signal Word:	Danger
Pictograms:	
Hazard Statements:	H225: Highly flammable liquid and vapor H304: May be fatal if swallowed and enters airways H315: Causes skin irritation H317: May cause an allergic skin reaction H336: May cause drowsiness or dizziness H361: Suspected of damaging fertility or the unborn child H373: May cause damage to organs through prolonged or repeated exposure

Prevention Precautionary Statements:	P201: Obtain special instructions before use P202: Do not handle until all safety precautions have been read and understood P210: Keep away from heat, hot surfaces, sparks, open flames, and other ignition sources. No smoking. P233: Keep container tightly closed P240: Ground/bond container and receiving equipment P241: Use explosion-proof electrical/ventilating/lighting equipment P242: Use only non-sparking tools P243: Take precautionary measures against static discharge P260: Do not breathe dust/fumes/gas/mist/vapors/spray P264: Wash face, hands and any exposed skin thoroughly after handling P271: Use only outdoors or in a well-ventilated area P280: Wear protective gloves/protective clothing/eye protection/face protection P281: Use personal protective equipment as required
Response Precautionary Statements:	P304+340+312: IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/ physician if you feel unwell. P301+310: IF SWALLOWED: Immediately call a POISON CENTER/doctor/physician P303+361+353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. P308+313: IF exposed: Call a POISON CENTER or doctor/physician P332+313: If skin irritation occurs: Get medical advice/attention P370+378: In case of fire: Use CO2, dry chemical, or foam to extinguish P331: Do NOT induce vomiting
Storage Precautionary Statements:	P405: Store locked up P403+233: Store in a well ventilated place. Keep container tightly closed. P403+235: Store in a well ventilated place. Keep cool.
Disposal Precautionary Statements:	P501: Dispose of contents/container to an approved waste disposal plant
Hazards Not Otherwise Classified:	None

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	Weight %	CAS Number
2-butoxyethanol	30% to 40%	111-76-2
Xylenes (isomers and mixture)	20% to 30%	1330-20-7
Toluene	10% to 20%	108-88-3
n-butanol	5% to 10%	71-36-3
Ethylbenzene	5% to 10%	100-41-4
Benzene	0% to 1%	71-43-2

4. FIRST AID MEASURES

General Advice:	Call a physician if symptoms persist. Show SDS to physician.
Eyes:	Remove contact lenses, if applicable. Flush eyes with water for at least 10 minutes. Keep eyes wide open while flushing. Consult a physician if symptoms persist.

Skin:	Remove contaminated clothing. Flush affected area with soap and water. Consult a physician if irritation persists. Wash contaminated clothing before re-use.
Ingestion:	Remove dentures if applicable and wash out mouth with water. Drink large amounts of water. Do not induce vomiting. Never give anything by mouth to an unconscious person. Consult a physician.
Inhalation:	Move to fresh air. If not breathing, give artificial respiration and consult a physician immediately. Consult a physician if symptoms persist.
Most Important Symptoms/Effects:	None known
Notes to Physician:	Acute exposure to toluene can cause transient hematuria and albuminuria. Acute inhalation may cause cardiac arrhythmias.

5. FIRE FIGHTING MEASURES

Suitable Extinguishing Media:	Foam, dry powder, CO ₂ , water spray. Use measures suitable to the circumstances and environment.
Precautions for Firefighters:	Wear self-contained breathing apparatus and protective gear
Specific Hazards:	Carbon oxides

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions:	Remove all sources of ignition. Use proper personal protective equipment. Avoid contact with skin, eyes, and clothing. Avoid breathing vapors.
Other Precautions:	If safe to do so, prevent additional spillage. Do not allow material to enter ground water, surface water, or sewer system. Consult local authorities if spillage cannot be contained.
Clean-Up Method:	Soak up with non-combustible absorbent material. Dispose of used absorbent in suitable containers.

7. HANDLING AND STORAGE

Handling Precautions:	Avoid contact with skin, eyes, and clothing. Avoid breathing vapors, mists, or dust. Use only in areas with sufficient ventilation. Ground all metal equipment to prevent ignition of vapors by static discharge. Keep away from heat and ignition sources.
Storage Precautions:	Keep container upright, properly labeled, tightly closed, and out of reach of children in a cool, dry, well-ventilated area. Keep away from heat and ignition sources.
Incompatible Materials:	Strong oxidizing agents

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

2-butoxyethanol(111-76-2)		
ACGIH TWA:	20 ppm	--
NIOSH TWA:	5 ppm	24 mg/m ³
OSHA TWA:	50 ppm	240 mg/m ³
Benzene(71-43-2)		
ACGIH STEL:	2.5 ppm	--
ACGIH TWA:	0.5 ppm	--
NIOSH ST:	1 ppm	--

NIOSH TWA:	0.1 ppm	--
OSHA CEIL:	25 ppm	--
OSHA peak:	50 ppm	--
OSHA TWA:	10 ppm	--
Ethylbenzene(100-41-4)		
ACGIH STEL:	125 ppm	--
ACGIH TWA:	20 ppm	--
NIOSH ST:	125 ppm	545 mg/m3
NIOSH TWA:	100 ppm	435 mg/m3
OSHA STEL:	125 ppm	545 mg/m3
OSHA TWA:	100 ppm	435 mg/m3
n-butanol(71-36-3)		
ACGIH TWA:	20 ppm	--
NIOSH C:	50 ppm	150 mg/m3
OSHA TWA:	100 ppm	300 mg/m3
Toluene(108-88-3)		
ACGIH TWA:	20 ppm	--
NIOSH ST:	150 ppm	560 mg/m3
NIOSH TWA:	100 ppm	375 mg/m3
OSHA CEIL:	300 ppm	--
OSHA peak:	500 ppm	--
OSHA STEL:	150 ppm	560 mg/m3
OSHA TWA:	100 ppm	375 mg/m3
Xylenes (isomers and mixture)(1330-20-7)		
ACGIH STEL:	150 ppm	--
ACGIH TWA:	100 ppm	--
OSHA TWA:	100 ppm	435 mg/m3

Engineering Measures:	Maintain adequate ventilation to keep exposure to airborne contaminants at safe levels. Use explosion-proof equipment.
Hygiene Measures:	No eating, drinking, or smoking while in use. Avoid contact with skin, eyes, and clothing. Wash hands, forearms, and face after handling. Wash contaminated clothing before re-use.
Eye/Face Protection:	Safety glasses/goggles
Skin Protection:	Protective gloves and long-sleeved protective clothing
Respiratory Protection:	Respiratory equipment if ventilation is inadequate

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State:	Liquid
Color:	Clear
Odor:	Solvent
Odor Threshold:	No information available
pH:	No information available
Melting Point (°F):	No information available
Boiling Point (°F):	No information available
Flash Point (°F):	40
Flash Point Method:	No information available
Evaporation Rate:	No information available
Flammability (Solid/Gas):	No information available

Flammability Limits:	No information available
Vapor Pressure (mm Hg):	No information available
Vapor Density:	No information available
Specific Gravity:	No information available
% Solubility in Water:	No information available
Octanol/Water Partition Coefficient:	No information available
Auto-Ignition Temperature (°F):	No information available
Decomposition Temperature (°F):	No information available
Viscosity (KU):	No information available
Volatile Organic Compounds (g/L):	875

10. STABILITY AND REACTIVITY

Reactivity:	No information available
Possibility of Hazardous Reactions:	Vapors may form explosive mixture with air
Hazardous Decomposition Products:	Carbon oxides
Stability:	Stable under normal storage conditions
Incompatible Materials:	Strong oxidizing agents
Conditions to Avoid:	Heat, sparks, ignition sources

11. TOXICOLOGICAL INFORMATION

2-butoxyethanol(111-76-2)	
Dermal LD50 (rabbit):	1060 mg/kg
Intraperitoneal LD50 (rat):	220 mg/kg
Intravenous LD50 (rat):	307 mg/kg
Oral LD50 (rat):	880 mg/kg
Benzene(71-43-2)	
Dermal LD50 (rabbit):	8263 mg/kg
Inhalation LC50 (rat, 4 hrs):	43.7 mg/L
Oral LD50 (rat):	5960 mg/kg
Ethylbenzene(100-41-4)	
Dermal LD50 (rabbit):	15433 mg/kg
Oral LD50 (rat):	3500 mg/kg
n-butanol(71-36-3)	
Dermal LD50 (rabbit):	3400 mg/kg
Inhalation LC50 (rat, 4 hrs):	8000 ppm
Oral LD50 (rat):	790 mg/kg
Toluene(108-88-3)	
Dermal LD50 (rabbit):	12196 mg/kg
Inhalation LC50 (rat, 4 hrs):	12500-28800 mg/m3

Oral LD50 (rat):	>5580 mg/kg
------------------	-------------

Primary Routes of Exposure:	Eye contact, skin contact, inhalation
Acute Toxicity:	No information available

Exposure Effects	
Eye Contact:	Irritation
Skin Contact:	Irritation, dermatitis
Inhalation:	Irritation of respiratory system, headaches, dizziness, drowsiness, unconsciousness
Ingestion:	No information available
Target Organ (Single Exposure):	No information available
Target Organ (Repeated Exposure):	No information available
Sensitization:	No information available
Carcinogenicity:	No information available
Mutagenicity:	No information available
Reproductive Toxicity:	Fetotoxic if purposefully inhaled ("solvent sniffing")
Other:	No information available

12. ECOLOGICAL INFORMATION

2-butoxyethanol(111-76-2)	
Biodegradability (aerobic, 28 days):	90.4%
Growth inhibition EC50 (green algae, 72 hrs):	1840 mg/L
Immobilization EC50 (water flea, 48 hrs):	1550 mg/L
Static LC50 (rainbow trout, 96 hrs):	1474 mg/L
Benzene(71-43-2)	
BCF:	10
Bioaccumulation (golden orfe, 3 days):	0.05 mg/L
Biodegradability (aerobic, 28 days):	96%
EC50 (water flea, 48 hrs):	17.2 mg/L
Growth inhibition EC50 (green algae, 72 hrs):	100 mg/L
LC50 (fathead minnow, 96 hrs):	15-32 mg/L
Ethylbenzene(100-41-4)	
Biodegradability (aerobic, 28 days):	70-80%
Flow-through LC50 (Atlantic silverside, 96 hrs):	5.1 mg/L
Static EC50 (Skeletonema costatum, 72 hrs):	4.9 mg/L
Static EC50 (water flea, 48 hrs):	1.8-2.4 mg/L
n-butanol(71-36-3)	
BCF (rainbow trout, 24 hrs, 921 mg/L):	0.38
EC50 (water flea, 48 hrs):	1983 mg/L
LC50 (fathead minnow, 96 hrs):	1840 mg/L
Toluene(108-88-3)	
BCF (golden orfe, 3 days, 0.05 mg/L):	90
EC50 (freshwater algae, 24 hrs):	245 mg/L
EC50 (green algae, 24 hrs):	10 mg/L
EC50 (water flea, 24 hrs):	8 mg/L
Immobilization EC50 (water flea, 48 hrs):	6 mg/L
LC50 (rainbow trout, 96 hrs):	7.63 mg/L

NOEC (fathead minnow, 7 days):	5.44 mg/L
--------------------------------	-----------

Ecotoxicological Effects:	The environmental impact of this substance has not been fully evaluated
Persistence/Degradability:	No information available
Bioaccumulative Potential:	No information available
Environmental Mobility:	No information available
Other Effects:	No information available

13. DISPOSAL CONSIDERATIONS

Disposal Method:	Empty containers may contain flammable residue and vapors. Dispose of in accordance with federal, state, provincial, and local regulations.
-------------------------	---

14. TRANSPORT INFORMATION

DOT	
Shipping Name:	Paint
Hazard Class:	3
UN No:	1263
Packing Group:	II

ICAO/IATA	
Shipping Name:	Paint
Hazard Class:	3
UN No:	1263
Packing Group:	II

IMDG/IMO	
Shipping Name:	Paint
Hazard Class:	3
UN No:	1263
Packing Group:	II

15. REGULATORY INFORMATION

TSCA (US):	All components are listed or exempt
DSL/NDSL (Canada):	All components are listed or exempt

311/312 Hazard Categories	
Fire:	Yes
Pressure Generating:	No
Reactivity:	No
Acute:	Yes
Chronic:	Yes

CERCLA Section 302	
---------------------------	--

Reportable Quantities:	Ethylbenzene, 1000 lbs Xylenes (isomers and mixture), 100 lbs Toluene, 1000 lbs Benzene, 10 lbs n-Butanol, 5000 lbs
-------------------------------	---

SARA 313			
Chemical Name	CAS Number	Max Weight %	de minimis limit
Xylenes (isomers and mixture)	1330-20-7	30	1.0
Toluene	108-88-3	20	1.0
n-butanol	71-36-3	10	1.0
Ethylbenzene	100-41-4	10	0.1
Benzene	71-43-2	1	0.1


State Right-to-Know					
Chemical Name	CAS Number	MA	NJ	PA	RI
2-butoxythanol	111-76-2	X	X	X	X
Xylenes (isomers and mixture)	1330-20-7	X	X	X	X
Toluene	108-88-3	X	X	X	X
n-butanol	71-36-3	X	X	X	X
Ethylbenzene	100-41-4	X	X	X	X
Benzene	71-43-2	X	X	X	X

California Proposition 65:	This product contains small amounts of materials known to the state of California to cause cancer or reproductive harm.
-----------------------------------	---

16. OTHER INFORMATION

HMIS RATING	
Health:	2*
Flammability:	3
Reactivity:	0
Personal Protection:	--

NFPA CODES



PPE rating has been left intentionally blank. Choose appropriate PPE based upon actual conditions of use.

Revision Indicator:	Revised 2/9/2022
Disclaimer:	The information contained in this Safety Data Sheet (SDS) is provided in good faith and is believed to be accurate as of the effective date listed. The information applies only to the product as provided and may not be valid if combined with other materials. No warranty is implied or given. The user is responsible for complying with all applicable laws and regulations.