



1840 - THOR Ultra Premium WB Acrylic Satin White

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
Issue date: 8/4/2023 Version: 1.0

SECTION 1: Identification

1.1. Identification

Product form : Mixture
Product name : 1840 - THOR Ultra Premium WB Acrylic Satin White
Product code : 1840.0

1.2. Recommended use and restrictions on use

No additional information available

1.3. Supplier

Richard's Paint
200 Paint Street
Rockledge, FL, 32955
USA
T 800-432-0983

1.4. Emergency telephone number

Emergency number : VelocityEHS (800) 255-3924 | VelocityEHS International (813) 248-0585

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

Acute toxicity (inhalation:dust,mist) Category 4	H332	Harmful if inhaled.
Carcinogenicity, Category 2	H351	Suspected of causing cancer.
Hazardous to the aquatic environment – Acute Hazard, Category 3	H402	Harmful to aquatic life

Full text of H-statements: see section 16

2.2. GHS Label elements, including precautionary statements

GHS US labelling

Hazard pictograms (GHS US)



Signal word (GHS US) : Warning

Hazard statements (GHS US) : H332 - Harmful if inhaled.
H351 - Suspected of causing cancer.
H402 - Harmful to aquatic life

Precautionary statements (GHS US) : P201 - Obtain special instructions before use.
P202 - Do not handle until all safety precautions have been read and understood.
P261 - Avoid breathing dust/fume/gas/mist/vapours/spray.
P271 - Use only outdoors or in a well-ventilated area.
P273 - Avoid release to the environment.
P280 - Wear protective gloves/protective clothing/eye protection/face protection.
P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing.
P308+P313 - If exposed or concerned: Get medical advice/attention.
P312 - Call a poison center or doctor if you feel unwell.
P405 - Store locked up.

1840 - THOR Ultra Premium WB Acrylic Satin White

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

50.1% of the mixture consists of ingredient(s) of unknown acute toxicity (Oral)

95.67% of the mixture consists of ingredient(s) of unknown acute toxicity (Dermal)

93.35% of the mixture consists of ingredient(s) of unknown acute toxicity (Inhalation (Dust/Mist))

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS US classification
titanium(IV) oxide	CAS-No.: 13463-67-7	20 – 30	Carc. 2, H351 Aquatic Acute 3, H402
kaolin	CAS-No.: 1332-58-7	5 – 10	Acute Tox. 4 (Inhalation:dust,mist), H332
2,2,4-trimethyl-1,3-pentanediol monoisobutyrate	CAS-No.: 25265-77-4	< 5	Aquatic Acute 3, H402

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general	: IF exposed or concerned: Get medical advice/attention. Call a poison center or a doctor if you feel unwell.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Call a poison center or a doctor if you feel unwell.
First-aid measures after skin contact	: Wash skin with plenty of water.
First-aid measures after eye contact	: Rinse eyes with water as a precaution.
First-aid measures after ingestion	: Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects (acute and delayed)

No additional information available

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

1840 - THOR Ultra Premium WB Acrylic Satin White

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

5.2. Specific hazards arising from the chemical

Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Special protective equipment and precautions for fire-fighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. Avoid breathing dust/fume/gas/mist/vapours/spray.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment : Collect spillage.
Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.
Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear personal protective equipment. Use only outdoors or in a well-ventilated area. Avoid breathing dust/fume/gas/mist/vapours/spray.
Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store locked up. Store in a well-ventilated place. Keep cool.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

1840 - THOR Ultra Premium WB Acrylic Satin White

No additional information available

1840 - THOR Ultra Premium WB Acrylic Satin White

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

titanium(IV) oxide (13463-67-7)	
USA - ACGIH - Occupational Exposure Limits	
Local name	Titanium dioxide
ACGIH OEL TWA	0.2 mg/m ³ (Respirable fraction) 2.5 mg/m ³ (Respirable fraction)
Remark (ACGIH)	TLV® Basis: LRT irr; pneumoconiosis. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans)
Regulatory reference	ACGIH 2022
USA - OSHA - Occupational Exposure Limits	
Local name	Titanium dioxide (Total dust)
OSHA PEL TWA [1]	15 mg/m ³
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
kaolin (1332-58-7)	
USA - ACGIH - Occupational Exposure Limits	
Local name	Kaolin
ACGIH OEL TWA	2 mg/m ³ (Respirable fraction. The value is for particulate matter containing no asbestos and < 1% crystalline silica)
Remark (ACGIH)	TLV® Basis: Pneumoconiosis. Notations: A4 (Not classifiable as a Human Carcinogen)
Regulatory reference	ACGIH 2023
USA - OSHA - Occupational Exposure Limits	
Local name	Kaolin
OSHA PEL TWA [1]	15 mg/m ³ (Total dust) 5 mg/m ³ (Respirable fraction)
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
2,2,4-trimethyl-1,3-pentanediol monoisobutyrate (25265-77-4)	
No additional information available	

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.
Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Hand protection:
Protective gloves
Eye protection:
Safety glasses
Skin and body protection:
Wear suitable protective clothing
Respiratory protection:
[In case of inadequate ventilation] wear respiratory protection.

1840 - THOR Ultra Premium WB Acrylic Satin White

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Personal protective equipment symbol(s):



SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Liquid.
Colour	: white
Odour	: No data available
Odour threshold	: No data available
pH	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: No data available
Flash point	: ≥ 200 °F
Relative evaporation rate (butylacetate=1)	: No data available
Flammability (solid, gas)	: Not applicable.
Vapour pressure	: No data available
Relative vapour density at 20°C	: No data available
Relative density	: No data available
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive limits	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

1840 - THOR Ultra Premium WB Acrylic Satin White

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Harmful if inhaled.

1840 - THOR Ultra Premium WB Acrylic Satin White

ATE US (dust,mist)	1.923 mg/l/4h
Unknown acute toxicity (GHS US)	50.1% of the mixture consists of ingredient(s) of unknown acute toxicity (Oral) 95.67% of the mixture consists of ingredient(s) of unknown acute toxicity (Dermal) 93.35% of the mixture consists of ingredient(s) of unknown acute toxicity (Inhalation (Dust/Mist))

titanium(IV) oxide (13463-67-7)

LD50 oral rat	> 2000 mg/kg bodyweight (OECD 401: Acute Oral Toxicity, Rat, Male / female, Experimental value, Oral, 14 day(s))
LC50 Inhalation - Rat	> 5.09 mg/l (OECD 403: Acute Inhalation Toxicity, 4 h, Rat, Male, Experimental value, Inhalation (dust), 14 day(s))

kaolin (1332-58-7)

LD50 oral rat	> 5000 mg/kg Source: HSDB
LD50 dermal rat	> 5000 mg/kg Source: HSDB
LC50 Inhalation - Rat (Dust/Mist)	≥ 5 mg/l Source: OSHRI GLP toxicity test
ATE US (dust,mist)	1.5 mg/l/4h

2,2,4-trimethyl-1,3-pentanediol monoisobutyrate (25265-77-4)

LD50 oral rat	3200 mg/kg (Rat, Oral)
LD50 dermal rabbit	> 15200 mg/kg (Rabbit, Dermal)
LC50 Inhalation - Rat (Vapours)	> 4.4375 mg/l Source: IUCLID
ATE US (oral)	3200 mg/kg bodyweight

Skin corrosion/irritation : Not classified

titanium(IV) oxide (13463-67-7)

pH	7 (aqueous suspension, 10 %)
----	------------------------------

kaolin (1332-58-7)

pH	4.5 Source: hsdh
----	------------------

Serious eye damage/irritation : Not classified

titanium(IV) oxide (13463-67-7)

pH	7 (aqueous suspension, 10 %)
----	------------------------------

1840 - THOR Ultra Premium WB Acrylic Satin White

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

kaolin (1332-58-7)	
pH	4.5 Source: hsdh
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Suspected of causing cancer.
titanium(IV) oxide (13463-67-7)	
IARC group	2B - Possibly carcinogenic to humans
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified
Aspiration hazard	: Not classified
Viscosity, kinematic	: No data available
titanium(IV) oxide (13463-67-7)	
Viscosity, kinematic	Not applicable (solid)
2,2,4-trimethyl-1,3-pentanediol monoisobutyrate (25265-77-4)	
Viscosity, kinematic	13.579 mm²/s

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Harmful to aquatic life.

titanium(IV) oxide (13463-67-7)	
LC50 - Fish [1]	> 100 mg/l (Equivalent or similar to OECD 203, 96 h, Oncorhynchus mykiss, Static system, Fresh water, Experimental value, Nominal concentration)
ErC50 algae	61 mg/l (EPA 600/9-78-018, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, Nominal concentration)
2,2,4-trimethyl-1,3-pentanediol monoisobutyrate (25265-77-4)	
LC50 - Fish [1]	30 mg/l (96 h, Pimephales promelas, Fresh water)
EC50 - Crustacea [1]	147.8 mg/l (48 h, Daphnia sp.)
LC50 - Fish [2]	> 19 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)
EC50 72h - Algae [1]	18.4 mg/l (Selenastrum capricornutum, Growth)

12.2. Persistence and degradability

titanium(IV) oxide (13463-67-7)	
Persistence and degradability	Biodegradability: not applicable.
Chemical oxygen demand (COD)	Not applicable (inorganic)
ThOD	Not applicable (inorganic)
kaolin (1332-58-7)	
Persistence and degradability	Biodegradability: not applicable.
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable

1840 - THOR Ultra Premium WB Acrylic Satin White

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

kaolin (1332-58-7)	
BOD (% of ThOD)	Not applicable
2,2,4-trimethyl-1,3-pentanediol monoisobutyrate (25265-77-4)	
Persistence and degradability	Readily biodegradable in water.
Chemical oxygen demand (COD)	2.1 g O ₂ /g substance
ThOD	2.4 g O ₂ /g substance

12.3. Bioaccumulative potential

titanium(IV) oxide (13463-67-7)	
Bioaccumulative potential	Not bioaccumulative.
kaolin (1332-58-7)	
Bioaccumulative potential	No bioaccumulation data available.
2,2,4-trimethyl-1,3-pentanediol monoisobutyrate (25265-77-4)	
Partition coefficient n-octanol/water (Log Pow)	3.47 (Experimental value)

12.4. Mobility in soil

titanium(IV) oxide (13463-67-7)	
Surface tension	No data available in the literature
Ecology - soil	Low potential for mobility in soil.

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Disposal methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

SECTION 14: Transport information

DOT	IMDG	IATA
14.1. UN number		
Not regulated for transport		
14.2. Proper Shipping Name		
Not applicable	Not applicable	Not applicable
14.3. Transport hazard class(es)		
Not applicable	Not applicable	Not applicable
14.4. Packing group		
Not applicable	Not applicable	Not applicable

1840 - THOR Ultra Premium WB Acrylic Satin White

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

DOT	IMDG	IATA
14.5. Environmental hazards		
Not applicable	Not applicable	Not applicable
No supplementary information available		

14.6. Special precautions for user

DOT

No data available

IMDG

No data available

IATA

No data available

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

ammonium hydroxide, 25%≤conc<35%, aqueous solutions

CAS-No. 1336-21-6

< 5%

15.2. International regulations

CANADA

titanium(IV) oxide (13463-67-7)

Listed on the Canadian DSL (Domestic Substances List)

kaolin (1332-58-7)

Listed on the Canadian DSL (Domestic Substances List)

2,2,4-trimethyl-1,3-pentanediol monoisobutyrate (25265-77-4)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

No additional information available

1840 - THOR Ultra Premium WB Acrylic Satin White

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

National regulations

titanium(IV) oxide (13463-67-7)

Listed on IARC (International Agency for Research on Cancer)
Listed on INSQ (Mexican National Inventory of Chemical Substances)

kaolin (1332-58-7)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

2,2,4-trimethyl-1,3-pentanediol monoisobutyrate (25265-77-4)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

15.3. US State regulations



WARNING:

This product can expose you to Carbon black (airborne, unbound particles of respirable size), which is known to the State of California to cause cancer, and Ethylene glycol (ingested), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Full text of H-statements

H332	Harmful if inhaled.
H351	Suspected of causing cancer.
H402	Harmful to aquatic life

Safety Data Sheet (SDS), USA

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.