



THOR Ultra Premium WB Acrylic Satin Black

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
Issue date: 10/27/2024 Revision date: 2/5/2025 Supersedes: 10/27/2024 Version: 2.0

SECTION 1: Identification

1.1. Identification

Product form : Mixture
Product name : THOR Ultra Premium WB Acrylic Satin Black
Product code : 1840.4

1.2. Recommended use and restrictions on use

No additional information available

1.3. Supplier

Richard's Paint
200 Paint Street
Rockledge, FL, 32955
USA
T 800-432-0983

1.4. Emergency telephone number

Emergency number : VelocityEHS (800) 255-3924 | VelocityEHS International (813) 248-0585

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

Flammable liquids, Category 4	H227	Combustible liquid
Acute toxicity (inhalation:dust,mist) Category 1	H330	Fatal if inhaled.
Carcinogenicity, Category 2	H351	Suspected of causing cancer.
Specific target organ toxicity – Repeated exposure, Category 1	H372	Causes damage to organs through prolonged or repeated exposure.
Hazardous to the aquatic environment – Acute Hazard, Category 3	H402	Harmful to aquatic life

Full text of H-statements: see section 16

2.2. GHS Label elements, including precautionary statements

GHS US labelling

Hazard pictograms (GHS US)



Signal word (GHS US)

: Danger

Hazard statements (GHS US)

: H227 - Combustible liquid
H330 - Fatal if inhaled.
H351 - Suspected of causing cancer.
H372 - Causes damage to organs through prolonged or repeated exposure.
H402 - Harmful to aquatic life

Precautionary statements (GHS US)

: P201 - Obtain special instructions before use.
P202 - Do not handle until all safety precautions have been read and understood.
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260 - Do not breathe dust/fume/gas/mist/vapours/spray.
P264 - Wash hands, forearms and face thoroughly after handling.

THOR Ultra Premium WB Acrylic Satin Black

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P270 - Do not eat, drink or smoke when using this product.
P271 - Use only outdoors or in a well-ventilated area.
P273 - Avoid release to the environment.
P280 - Wear protective gloves/protective clothing/eye protection/face protection.
P284 - [In case of inadequate ventilation] wear respiratory protection.
P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing.
P308+P313 - If exposed or concerned: Get medical advice/attention.
P310 - Immediately call a poison center or doctor.
P314 - Get medical advice/attention if you feel unwell.
P320 - Specific treatment is urgent (see supplemental first aid instruction on this label).
P370+P378 - In case of fire: Use media other than water to extinguish.
P403+P233 - Store in a well-ventilated place. Keep container tightly closed.
P403+P235 - Store in a well-ventilated place. Keep cool.
P405 - Store locked up.
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

37.99% of the mixture consists of ingredient(s) of unknown acute toxicity (Oral)
94.42% of the mixture consists of ingredient(s) of unknown acute toxicity (Dermal)
89.19% of the mixture consists of ingredient(s) of unknown acute toxicity (Inhalation (Dust/Mist))

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS US classification
kaolin	CAS-No.: 1332-58-7	5 – 10	Acute Tox. 4 (Inhalation:dust,mist), H332
2,2,4-trimethyl-1,3-pentanediol monoisobutyrate	CAS-No.: 25265-77-4	< 5	Aquatic Acute 3, H402
carbon black	CAS-No.: 1333-86-4	< 5	Acute Tox. 1 (Inhalation:dust,mist), H330 Carc. 2, H351 STOT RE 1, H372

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general : Call a physician immediately.
First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. Call a physician immediately.
First-aid measures after skin contact : Wash skin with plenty of water.
First-aid measures after eye contact : Rinse eyes with water as a precaution.
First-aid measures after ingestion : Call a poison center or a doctor if you feel unwell.

THOR Ultra Premium WB Acrylic Satin Black

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after inhalation	: Although no appropriate human or animal health effects data are known to exist, this material is expected to be an inhalation hazard.
Symptoms/effects after skin contact	: None under normal conditions.
Symptoms/effects after eye contact	: None under normal conditions.
Symptoms/effects after ingestion	: None under normal conditions.

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media	: Do not use a heavy water stream.

5.2. Specific hazards arising from the chemical

Fire hazard	: Combustible liquid.
Explosion hazard	: No direct explosion hazard.
Hazardous decomposition products in case of fire	: Toxic fumes may be released.

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions	: Fight fire from safe distance and protected location. Do not enter fire area without proper protective equipment, including respiratory protection.
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Stop leak if safe to do so. Notify authorities if product enters sewers or public waters. Absorb spillage to prevent material damage.
------------------	---

6.1.1. For non-emergency personnel

Protective equipment	: Wear recommended personal protective equipment.
Emergency procedures	: No open flames, no sparks, and no smoking. Do not breathe dust/fume/gas/mist/vapours/spray. Only qualified personnel equipped with suitable protective equipment may intervene.

6.1.2. For emergency responders

Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
Emergency procedures	: Evacuate unnecessary personnel. Stop leak if safe to do so.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment	: Collect spillage. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Stop leak without risks if possible.
Methods for cleaning up	: Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.
Other information	: Dispose of materials or solid residues at an authorized site.

THOR Ultra Premium WB Acrylic Satin Black

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed	: Not expected to present a significant hazard under anticipated conditions of normal use.
Precautions for safe handling	: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Wear personal protective equipment. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapours/spray. Use only outdoors or in a well-ventilated area.
Hygiene measures	: Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures	: Keep in a cool, well-ventilated place away from heat.
Storage conditions	: Store in a well-ventilated place. Keep cool. Store locked up. Keep container tightly closed.
Packaging materials	: Store always product in container of same material as original container.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

kaolin (1332-58-7)	
USA - ACGIH - Occupational Exposure Limits	
Local name	Kaolin
ACGIH OEL TWA	2 mg/m ³ (Respirable fraction. The value is for particulate matter containing no asbestos and < 1% crystalline silica)
Remark (ACGIH)	TLV® Basis: Pneumoconiosis. Notations: A4 (Not classifiable as a Human Carcinogen)
Regulatory reference	ACGIH 2024
USA - OSHA - Occupational Exposure Limits	
Local name	Kaolin
OSHA PEL TWA	15 mg/m ³ (Total dust) 5 mg/m ³ (Respirable fraction)
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
carbon black (1333-86-4)	
USA - ACGIH - Occupational Exposure Limits	
Local name	Carbon black
ACGIH OEL TWA	3 mg/m ³ (Inhalable fraction)
Remark (ACGIH)	TLV® Basis: Bronchitis. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans)
Regulatory reference	ACGIH 2024
USA - OSHA - Occupational Exposure Limits	
Local name	Carbon black

THOR Ultra Premium WB Acrylic Satin Black

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

carbon black (1333-86-4)

OSHA PEL TWA	3.5 mg/m ³
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1

8.2. Appropriate engineering controls

Appropriate engineering controls	: Ensure good ventilation of the work station.
Environmental exposure controls	: Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Wear recommended personal protective equipment.

Hand protection:

Protective gloves

Eye protection:

Safety glasses

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

[In case of inadequate ventilation] wear respiratory protection.

Personal protective equipment symbol(s):



SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Liquid.
Colour	: Black
Odour	: No data available
Odour threshold	: No data available
pH	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: No data available
Flash point	: 197 °F
Relative evaporation rate (butylacetate=1)	: No data available
Flammability (solid, gas)	: Not applicable.
Vapour pressure	: No data available
Relative vapour density at 20°C	: No data available
Relative density	: No data available
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available

THOR Ultra Premium WB Acrylic Satin Black

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Viscosity, dynamic	: No data available
Explosive limits	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available

9.2. Other information

VOC content	: 240.7 g/l
-------------	-------------

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Inhalation:dust,mist: Fatal if inhaled.

THOR Ultra Premium WB Acrylic Satin Black	
ATE US (dust,mist)	0.032 mg/l/4h
Unknown acute toxicity (GHS US)	37.99% of the mixture consists of ingredient(s) of unknown acute toxicity (Oral) 94.42% of the mixture consists of ingredient(s) of unknown acute toxicity (Dermal) 89.19% of the mixture consists of ingredient(s) of unknown acute toxicity (Inhalation (Dust/Mist))
kaolin (1332-58-7)	
LD50 oral rat	> 5000 mg/kg Source: HSDB
LD50 dermal rat	> 5000 mg/kg Source: HSDB
LC50 Inhalation - Rat (Dust/Mist)	≥ 5 mg/l Source: OSHRI GLP toxicity test
ATE US (dust,mist)	1.5 mg/l/4h

THOR Ultra Premium WB Acrylic Satin Black

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

2,2,4-trimethyl-1,3-pentanediol monoisobutyrate (25265-77-4)	
LD50 oral rat	3200 mg/kg (Rat, Oral)
LD50 dermal rabbit	> 15200 mg/kg (Rabbit, Dermal)
LC50 Inhalation - Rat (Vapours)	> 4.4375 mg/l Source: IUCLID
ATE US (oral)	3200 mg/kg bodyweight
carbon black (1333-86-4)	
LD50 oral rat	> 10000 mg/kg (Equivalent or similar to OECD 401, Rat, Male / female, Experimental value, Oral, 28 day(s))
LD50 dermal rabbit	> 8000 mg/kg Source: ECHA
LC50 Inhalation - Rat	> 4.6 mg/m³
ATE US (dust,mist)	0.005 mg/l/4h
Skin corrosion/irritation	: Not classified
kaolin (1332-58-7)	
pH	4.5 Source: hsdh
carbon black (1333-86-4)	
pH	4 – 10 (5 %, 20 °C)
Serious eye damage/irritation	: Not classified
kaolin (1332-58-7)	
pH	4.5 Source: hsdh
carbon black (1333-86-4)	
pH	4 – 10 (5 %, 20 °C)
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Suspected of causing cancer.
carbon black (1333-86-4)	
IARC group	2B - Possibly carcinogenic to humans
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
STOT-repeated exposure	: Causes damage to organs through prolonged or repeated exposure.
carbon black (1333-86-4)	
LOAEC (inhalation, rat, dust/mist/fume, 90 days)	0.0071 mg/l air Animal: rat, Animal sex: male
NOAEL (oral, rat, 90 days)	> 1000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)
NOAEC (inhalation, rat, dust/mist/fume, 90 days)	0.0011 mg/l air Animal: rat, Animal sex: male
STOT-repeated exposure	Causes damage to organs through prolonged or repeated exposure.
Aspiration hazard	: Not classified
Viscosity, kinematic	: No data available
2,2,4-trimethyl-1,3-pentanediol monoisobutyrate (25265-77-4)	
Viscosity, kinematic	13.579 mm²/s

THOR Ultra Premium WB Acrylic Satin Black

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

carbon black (1333-86-4)	
Viscosity, kinematic	Not applicable (solid)
Symptoms/effects after inhalation	: Although no appropriate human or animal health effects data are known to exist, this material is expected to be an inhalation hazard.
Symptoms/effects after skin contact	: None under normal conditions.
Symptoms/effects after eye contact	: None under normal conditions.
Symptoms/effects after ingestion	: None under normal conditions.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Harmful to aquatic life.

2,2,4-trimethyl-1,3-pentanediol monoisobutyrate (25265-77-4)	
LC50 - Fish [1]	30 mg/l (96 h, Pimephales promelas, Fresh water)
EC50 - Crustacea [1]	147.8 mg/l (48 h, Daphnia sp.)
LC50 - Fish [2]	> 19 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)
EC50 72h - Algae [1]	18.4 mg/l (Selenastrum capricornutum, Growth)

carbon black (1333-86-4)	
LC50 - Fish [1]	> 1000 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Danio rerio, Static system, Fresh water, Experimental value, Lethal)
EC50 - Crustacea [1]	> 5600 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 24 h, Daphnia magna, Static system, Fresh water, Experimental value, Locomotor effect)
EC50 72h - Algae [1]	> 10000 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)
EC50 72h - Algae [2]	> 10000 mg/l Test organisms (species):
ErC50 algae	> 10000 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Desmodesmus subspicatus, Static system, Fresh water, Experimental value, Nominal concentration)

12.2. Persistence and degradability

THOR Ultra Premium WB Acrylic Satin Black	
Persistence and degradability	Rapidly degradable
kaolin (1332-58-7)	
Persistence and degradability	Biodegradability: not applicable.
Chemical oxygen demand (COD)	Not applicable (inorganic)
ThOD	Not applicable (inorganic)
2,2,4-trimethyl-1,3-pentanediol monoisobutyrate (25265-77-4)	
Persistence and degradability	Readily biodegradable in water.
Chemical oxygen demand (COD)	2.1 g O ₂ /g substance
ThOD	2.4 g O ₂ /g substance
carbon black (1333-86-4)	
Persistence and degradability	Biodegradability in soil: not applicable, Biodegradability: not applicable.

THOR Ultra Premium WB Acrylic Satin Black

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

carbon black (1333-86-4)	
Chemical oxygen demand (COD)	Not applicable (inorganic)
ThOD	Not applicable (inorganic)

12.3. Bioaccumulative potential

kaolin (1332-58-7)	
Bioaccumulative potential	No bioaccumulation data available.

2,2,4-trimethyl-1,3-pentanediol monoisobutyrate (25265-77-4)

Partition coefficient n-octanol/water (Log Pow)	3.47 (Experimental value)
---	---------------------------

carbon black (1333-86-4)	
Bioaccumulative potential	Not bioaccumulative.

12.4. Mobility in soil

kaolin (1332-58-7)	
Ecology - soil	No (test)data on mobility of the substance available.

carbon black (1333-86-4)	
Surface tension	Not applicable (solid)
Ecology - soil	No (test)data on mobility of the substance available. Not toxic to plants. Not toxic to animals.

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Disposal methods

Regional waste regulation	: Disposal must be done according to official regulations.
Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Sewage disposal recommendations	: Disposal must be done according to official regulations.
Product/Packaging disposal recommendations	: Disposal must be done according to official regulations.
Additional information	: Do not re-use empty containers.

SECTION 14: Transport information

DOT	IMDG	IATA
14.1. UN number		
Not regulated for transport		
14.2. Proper Shipping Name		
Not regulated	Not regulated	Not regulated
14.3. Transport hazard class(es)		
Not regulated	Not regulated	Not regulated

THOR Ultra Premium WB Acrylic Satin Black

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

DOT	IMDG	IATA
14.4. Packing group		
Not regulated	Not regulated	Not regulated
14.5. Environmental hazards		
Not regulated	Not regulated	Not regulated
No supplementary information available		

14.6. Special precautions for user

DOT

Not regulated

IMDG

Not regulated

IATA

Not regulated

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

ammonium hydroxide, 25%≤conc<35%, aqueous solutions

CAS-No. 1336-21-6

< 5%

15.2. International regulations

CANADA

kaolin (1332-58-7)

Listed on the Canadian DSL (Domestic Substances List)

2,2,4-trimethyl-1,3-pentanediol monoisobutyrate (25265-77-4)

Listed on the Canadian DSL (Domestic Substances List)

carbon black (1333-86-4)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

No additional information available

THOR Ultra Premium WB Acrylic Satin Black

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

National regulations

kaolin (1332-58-7)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

2,2,4-trimethyl-1,3-pentanediol monoisobutyrate (25265-77-4)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

carbon black (1333-86-4)

Listed on IARC (International Agency for Research on Cancer)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

15.3. US State regulations



WARNING:

This product can expose you to Carbon black (airborne, unbound particles of respirable size), which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date : 2/5/2025

Full text of hazard classes and H-statements

H227	Combustible liquid
H330	Fatal if inhaled.
H332	Harmful if inhaled.
H351	Suspected of causing cancer.
H372	Causes damage to organs through prolonged or repeated exposure.
H402	Harmful to aquatic life

Safety Data Sheet (SDS), USA

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.