



Barn & Fence latex Solid Wood Stain Black

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
Issue date: 11/4/2024 Version: 1.0

SECTION 1: Identification

1.1. Identification

Product form : Mixture
Product name : Barn & Fence latex Solid Wood Stain Black
Product code : 5900.4

1.2. Recommended use and restrictions on use

No additional information available

1.3. Supplier

Richard's Paint
200 Paint Street
Rockledge, FL, 32955
USA
T 800-432-0983

1.4. Emergency telephone number

Emergency number : VelocityEHS (800) 255-3924 | VelocityEHS International (813) 248-0585

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

Acute toxicity (inhalation:dust,mist) Category 1	H330	Fatal if inhaled.
Carcinogenicity, Category 1B	H350	May cause cancer.
Specific target organ toxicity – Repeated exposure, Category 1	H372	Causes damage to organs through prolonged or repeated exposure.
Hazardous to the aquatic environment – Acute Hazard, Category 2	H401	Toxic to aquatic life

Full text of H-statements: see section 16

2.2. GHS Label elements, including precautionary statements

GHS US labelling

Hazard pictograms (GHS US)



Signal word (GHS US)

: Danger

Hazard statements (GHS US)

: H330 - Fatal if inhaled.
H350 - May cause cancer.
H372 - Causes damage to organs through prolonged or repeated exposure.
H401 - Toxic to aquatic life

Precautionary statements (GHS US)

: P201 - Obtain special instructions before use.
P202 - Do not handle until all safety precautions have been read and understood.
P260 - Do not breathe dust/fume/gas/mist/vapours/spray.
P264 - Wash hands, forearms and face thoroughly after handling.
P270 - Do not eat, drink or smoke when using this product.
P271 - Use only outdoors or in a well-ventilated area.
P273 - Avoid release to the environment.
P280 - Wear protective gloves/protective clothing/eye protection/face protection.

Barn & Fence latex Solid Wood Stain Black

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P284 - [In case of inadequate ventilation] wear respiratory protection.
P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing.
P308+P313 - If exposed or concerned: Get medical advice/attention.
P310 - Immediately call a poison center or doctor.
P314 - Get medical advice/attention if you feel unwell.
P320 - Specific treatment is urgent (see supplemental first aid instruction on this label).
P403+P233 - Store in a well-ventilated place. Keep container tightly closed.
P405 - Store locked up.
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

49.13% of the mixture consists of ingredient(s) of unknown acute toxicity (Oral)
97.88% of the mixture consists of ingredient(s) of unknown acute toxicity (Dermal)
94.62% of the mixture consists of ingredient(s) of unknown acute toxicity (Inhalation (Dust/Mist))

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS US classification
carbon black	CAS-No.: 1333-86-4	< 5	Acute Tox. 1 (Inhalation:dust,mist), H330 Carc. 2, H351 STOT RE 1, H372
ethylene glycol	CAS-No.: 107-21-1	< 5	Acute Tox. 4 (Inhalation:dust,mist), H332
distillates (petroleum), hydrotreated heavy paraffinic	CAS-No.: 64742-54-7	< 5	Carc. 1B, H350

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general : Call a physician immediately.
First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. Call a physician immediately.
First-aid measures after skin contact : Wash skin with plenty of water.
First-aid measures after eye contact : Rinse eyes with water as a precaution.
First-aid measures after ingestion : Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects (acute and delayed)

No additional information available

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

Barn & Fence latex Solid Wood Stain Black

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

5.2. Specific hazards arising from the chemical

Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Special protective equipment and precautions for fire-fighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Only qualified personnel equipped with suitable protective equipment may intervene. Do not breathe dust/fume/gas/mist/vapours/spray.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment. Notify authorities if product enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

For containment : Collect spillage.
Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.
Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Take all necessary technical measures to avoid or minimize the release of the product on the workplace. Limit quantities of product at the minimum necessary for handling and limit the number of exposed workers. Provide local exhaust or general room ventilation. Wear personal protective equipment. Floors, walls and other surfaces in the hazard area must be cleaned regularly. Do not breathe dust/fume/gas/mist/vapours/spray.
Hygiene measures : Separate working clothes from town clothes. Launder separately. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store locked up. Store in a well-ventilated place. Keep container tightly closed. Keep cool.

Barn & Fence latex Solid Wood Stain Black

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

ethylene glycol (107-21-1)

USA - ACGIH - Occupational Exposure Limits

Local name	Ethylene glycol
ACGIH OEL TWA	25 ppm (Vapor fraction)
ACGIH OEL STEL	10 mg/m ³ (Inhalable fraction, Aerosol only)
	50 ppm (Vapor fraction)
Remark (ACGIH)	TLV® Basis: URT irr. Notations: A4 (Not classifiable as a Human Carcinogen)
Regulatory reference	ACGIH 2024

carbon black (1333-86-4)

USA - ACGIH - Occupational Exposure Limits

Local name	Carbon black
ACGIH OEL TWA	3 mg/m ³ (Inhalable fraction)
Remark (ACGIH)	TLV® Basis: Bronchitis. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans)
Regulatory reference	ACGIH 2024

USA - OSHA - Occupational Exposure Limits

Local name	Carbon black
OSHA PEL TWA	3.5 mg/m ³
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1

8.2. Appropriate engineering controls

Appropriate engineering controls	: Ensure good ventilation of the work station.
Environmental exposure controls	: Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Hand protection:
Protective gloves
Eye protection:
Safety glasses
Skin and body protection:
Wear suitable protective clothing
Respiratory protection:
[In case of inadequate ventilation] wear respiratory protection.

Personal protective equipment symbol(s):



Barn & Fence latex Solid Wood Stain Black

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Liquid.
Colour	: Black
Odour	: No data available
Odour threshold	: No data available
pH	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: No data available
Flash point	: ≥ 200 °F
Relative evaporation rate (butylacetate=1)	: No data available
Flammability (solid, gas)	: Not applicable.
Vapour pressure	: No data available
Relative vapour density at 20°C	: No data available
Relative density	: No data available
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive limits	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available

9.2. Other information

VOC content	: 91.7 g/l
-------------	------------

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Barn & Fence latex Solid Wood Stain Black

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Inhalation:dust,mist: Fatal if inhaled.

Barn & Fence latex Solid Wood Stain Black	
ATE US (dust,mist)	0.016 mg/l/4h
Unknown acute toxicity (GHS US)	49.13% of the mixture consists of ingredient(s) of unknown acute toxicity (Oral) 97.88% of the mixture consists of ingredient(s) of unknown acute toxicity (Dermal) 94.62% of the mixture consists of ingredient(s) of unknown acute toxicity (Inhalation (Dust/Mist))

ethylene glycol (107-21-1)	
LD50 oral rat	7712 mg/kg bodyweight (according to BASF-internal standards, Rat, Male / female, Experimental value, Aqueous solution, Oral, 7 day(s))
LD50 dermal	> 3500 mg/kg bodyweight (Mouse, Male / female, Experimental value, Dermal)
LC50 Inhalation - Rat	> 2.5 mg/l (6 h, Rat, Male / female, Experimental value, Inhalation (aerosol))
ATE US (oral)	7712 mg/kg bodyweight
ATE US (dust,mist)	1.5 mg/l/4h

carbon black (1333-86-4)	
LD50 oral rat	> 10000 mg/kg (Equivalent or similar to OECD 401, Rat, Male / female, Experimental value, Oral, 28 day(s))
LD50 dermal rabbit	> 8000 mg/kg Source: ECHA
LC50 Inhalation - Rat	> 4.6 mg/m ³
ATE US (dust,mist)	0.005 mg/l/4h

Skin corrosion/irritation : Not classified

ethylene glycol (107-21-1)	
pH	No data available in the literature

carbon black (1333-86-4)	
pH	4 – 10 (5 %, 20 °C)

Serious eye damage/irritation : Not classified

ethylene glycol (107-21-1)	
pH	No data available in the literature

carbon black (1333-86-4)	
pH	4 – 10 (5 %, 20 °C)

Respiratory or skin sensitisation : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : May cause cancer.

carbon black (1333-86-4)	
IARC group	2B - Possibly carcinogenic to humans

Reproductive toxicity : Not classified
STOT-single exposure : Not classified

Barn & Fence latex Solid Wood Stain Black

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

STOT-repeated exposure : Causes damage to organs through prolonged or repeated exposure.

carbon black (1333-86-4)	
LOAEC (inhalation, rat, dust/mist/fume, 90 days)	0.0071 mg/l air Animal: rat, Animal sex: male
NOAEL (oral, rat, 90 days)	> 1000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)
NOAEC (inhalation, rat, dust/mist/fume, 90 days)	0.0011 mg/l air Animal: rat, Animal sex: male
STOT-repeated exposure	Causes damage to organs through prolonged or repeated exposure.

Aspiration hazard : Not classified

Viscosity, kinematic : No data available

ethylene glycol (107-21-1)	
Viscosity, kinematic	18.86 mm²/s (20 °C)
carbon black (1333-86-4)	
Viscosity, kinematic	Not applicable (solid)

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Toxic to aquatic life.

ethylene glycol (107-21-1)	
LC50 - Fish [1]	> 72860 mg/l (EPA 600/4-90/027, 96 h, Pimephales promelas, Static system, Fresh water, Experimental value, Nominal concentration)
EC50 - Crustacea [1]	> 100 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, Daphnia magna, Static system, Fresh water, Experimental value)
EC50 96h - Algae [1]	6500 – 13000 mg/l Source: ECHA
NOEC (chronic)	≥ 1000 mg/l Test organisms (species): Americamysis bahia (previous name: Mysidopsis bahia) Duration: '23 d'

carbon black (1333-86-4)	
LC50 - Fish [1]	> 1000 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Danio rerio, Static system, Fresh water, Experimental value, Lethal)
EC50 - Crustacea [1]	> 5600 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 24 h, Daphnia magna, Static system, Fresh water, Experimental value, Locomotor effect)
EC50 72h - Algae [1]	> 10000 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)
EC50 72h - Algae [2]	> 10000 mg/l Test organisms (species):
ErC50 algae	> 10000 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Desmodesmus subspicatus, Static system, Fresh water, Experimental value, Nominal concentration)

12.2. Persistence and degradability

Barn & Fence latex Solid Wood Stain Black	
Persistence and degradability	Rapidly degradable
ethylene glycol (107-21-1)	
Persistence and degradability	Readily biodegradable in the soil, Readily biodegradable in water.

Barn & Fence latex Solid Wood Stain Black

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

ethylene glycol (107-21-1)	
Biochemical oxygen demand (BOD)	0.47 g O ₂ /g substance
Chemical oxygen demand (COD)	1.24 g O ₂ /g substance
ThOD	1.29 g O ₂ /g substance
carbon black (1333-86-4)	
Persistence and degradability	Biodegradability in soil: not applicable, Biodegradability: not applicable.
Chemical oxygen demand (COD)	Not applicable (inorganic)
ThOD	Not applicable (inorganic)
distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	
Persistence and degradability	Rapidly degradable

12.3. Bioaccumulative potential

ethylene glycol (107-21-1)	
Partition coefficient n-octanol/water (Log Pow)	-1.36 (Experimental value)
Bioaccumulative potential	Not bioaccumulative.
carbon black (1333-86-4)	
Bioaccumulative potential	Not bioaccumulative.

12.4. Mobility in soil

ethylene glycol (107-21-1)	
Mobility in soil	0.2 Source: HSDB
Surface tension	48.4 mN/m (20 °C)
Organic Carbon Normalized Adsorption Coefficient (Log K _{oc})	0 (log K _{oc} , SRC PCKOCWIN v2.0, QSAR)
Ecology - soil	Highly mobile in soil.
carbon black (1333-86-4)	
Surface tension	Not applicable (solid)
Ecology - soil	No (test)data on mobility of the substance available. Not toxic to plants. Not toxic to animals.

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Disposal methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

Barn & Fence latex Solid Wood Stain Black

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 14: Transport information

DOT	IMDG	IATA
14.1. UN number		
Not regulated for transport		
14.2. Proper Shipping Name		
Not regulated	Not regulated	Not regulated
14.3. Transport hazard class(es)		
Not regulated	Not regulated	Not regulated
14.4. Packing group		
Not regulated	Not regulated	Not regulated
14.5. Environmental hazards		
Not regulated	Not regulated	Not regulated
No supplementary information available		

14.6. Special precautions for user

DOT
Not regulated

IMDG
Not regulated

IATA
Not regulated

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.		
ethylene glycol	CAS-No. 107-21-1	< 5%
ammonium hydroxide, 25%≤conc<35%, aqueous solutions	CAS-No. 1336-21-6	< 5%

ethylene glycol (107-21-1)	
Listed on EPA Hazardous Air Pollutant (HAPS)	
CERCLA RQ	5000 lb

Barn & Fence latex Solid Wood Stain Black

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

15.2. International regulations

CANADA

ethylene glycol (107-21-1)

Listed on the Canadian DSL (Domestic Substances List)

carbon black (1333-86-4)

Listed on the Canadian DSL (Domestic Substances List)

distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

No additional information available

National regulations

ethylene glycol (107-21-1)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

carbon black (1333-86-4)

Listed on IARC (International Agency for Research on Cancer)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

15.3. US State regulations



WARNING:

This product can expose you to chemicals including Carbon black (airborne, unbound particles of respirable size), which is known to the State of California to cause cancer, and Ethylene glycol (ingested), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Full text of hazard classes and H-statements

H330	Fatal if inhaled.
H332	Harmful if inhaled.
H350	May cause cancer.
H351	Suspected of causing cancer.
H372	Causes damage to organs through prolonged or repeated exposure.
H401	Toxic to aquatic life

Safety Data Sheet (SDS), USA

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.