



PRODUCT DATA SHEET

PROD. 8900 SERIES

DECK-PRO ALKYD SEMI-TRANSPARENT PENETRATING WOOD SEALER



PRODUCT DESCRIPTION

Deck-Pro Alkyd Semi-Transparent Penetrating Wood Sealer is a semi-transparent wood stain/sealer specially formulated to enrich and protect the natural beauty of both new and old exterior wood surfaces. Its special formulation penetrates and seals wood fibers, enhancing the natural beauty of the wood grain, adding depth and warmth to the grain pattern. It provides excellent protection from wood rot, mildew, sunlight, and wood degradation. Easy to apply, it helps restore old wood surfaces to its once natural color and beauty, and will not blister, peel or crack.



MEETS MPI STANDARD #33 OF THE MASTER PAINTERS INSTITUTE'S APPROVED PRODUCTS LIST.

PRODUCT FEATURES	PRODUCT USES	PERFORMANCE QUALITIES
- Semi-Transparent Finish - Penetrates & Seals - Enhances Woods Natural Beauty - Superior Coverage - Mildew Resistant - Superior Durability - Easy To Apply	<i>Suitable for, but not limited to the following properly prepared surfaces;</i> EXTERIOR - New Wood Decks - Old Wood Decks - Wood Siding - Porch Decking - Wood Fencing - Wood Trim & Fascia - Wood Shutters - Log Homes For Exterior Use Only.	Product Quality: Premium / Best Product Use: Exterior Application: Brush, Roller, Spray Product System: Solvent-Based Sheen: Semi-Transparent MPI Standards: MPI #33 VOC Compliance: EPA AIM

SURFACE PREPARATION

GENERAL: The entire surface area to be painted should be clean, dry, sound, and free from dirt, grease, oils, waxes, mildew and any other surface contaminants that may adversely affect the performance of this coating material.

- New Wood Surfaces** – All new wood surfaces should be allowed to go through two (2) wet/dry cycles by rain or regular water rinsing to open wood grain and to remove excess surface tannins during cleaning.
- NEW PRESSURE TREATED WOOD:** New uncoated pressure treated wood, (PTW), should be allowed to weather for approximately 4 – 6 weeks or until water droplets can penetrate the wood surface within 20 seconds. Wood surfaces with a mill glaze or a slick, shiny appearance, must be scuff sanded or allowed to weather sufficiently to allow surface pores to open before staining. Wet woods, such as Cedar and Redwood, should be allowed approximately 6 months to weather sufficiently prior to staining.
- OLD WOOD SURFACES:** Thoroughly clean the entire surface area as stated above. It is recommended to power wash the surface area using a unit with a minimum of 1500 psi of pressure to sufficiently remove existing stain powder, and deteriorated wood fibers. Allow a minimum of 48 hours of good drying condition before application of sealer. Wood surfaces that are excessively gray or weathered should be cleaned with a restorative wood cleaner or brightener, rinsed thoroughly, and allowed to dry for 48 hours before sealing.
- PREVIOUSLY STAINED WOOD:** Previously stained and/or painted surfaces must be completely stripped to reveal the bare wood surface, and treated as a new wood surface. Repair/remove all damaged, deteriorated, and surface imperfections with the proper patching or building materials.
- SPECIAL NOTE:** Some wood, such as Cedar and Redwood contain natural Tannic Acids. These acids have a tendency to migrate to the surface when painted, thus discoloring most coatings. If this occurs during application of this particular product, allow application to completely dry, then wash the affected surface areas with a mild detergent solution and rinse thoroughly..
- MILDEW:** Surface areas affected by mildew should be treated with a commercial mildew removal and/or wash product carefully following manufacturer's application and safety directions. Rinse thoroughly with clean water, and allow a minimum of 24 hours to dry thoroughly.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and wet mop. Before you start, find out how you can protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-Lead, or log onto www.epa.gov/lead.

TECHNICAL DATA

- COLORS:** Clear Base & Stock Colors
8900.10 – Natural 8900.20 – Cedartone
8900.30 – Dark Oak 8900.50 – Sienna
8900.60 – Walnut
- TINTING:** Universal Colorant – Clear Base Only.
- VEHICLE TYPE:** Alkyd
- VISCOSITY:** 21 – 23 Sec. / #2 Zahn Cup
- GLOSS @ 60°:** 18-21 Units
- FLASH POINT:** 107° F
- COATING VOC:** Not to Exceed 550 g/l – 4.62 lb/gal
(Meets EPA AIM Standards)
- SOLIDS BY VOLUME:** 29.04% ± 2%
- SOLIDS BY WEIGHT:** 36.68% ± 2%
- ESTIMATED COVERAGE:** 100 – 400 SFPG
(Coverage will vary significantly depending on application method, surface porosity and condition of the surface.)
- RECOMMENDED MIL FILM:** (Estimated @ 300 SFPG)
Wet: 5.3 mils **Dry:** 1.7 mils
- DRY TIME:** (@ 70° F & 50% Relative Humidity)
Touch: 2 - 4 hrs. | **Recoat:** Wet-on-Wet Only. Do Not apply a second coat after the first coat is dry. | **Foot Traffic:** 72 hrs.
(Actual dry time may vary according to relative humidity, temperature, color, applied film build and air movement.)
- DRIES BY:** Oxidation / Solvent Evaporation
- CLEAN UP:** Mineral Spirits
- THINNING:** Do Not Thin
- WEIGHT/GAL:** 7.32 lbs.
- SHELF LIFE:** Unopened 2 - 3 years on average.
- PACKAGING:** Qts. – 6/cs. | Gal. – 4/cs. | 5 Gal. – Each
(Stock Colors N/A in Qts.)

RECOMMENDED PRIMER COATINGS

This penetrating wood stain is applied directly to properly prepared wood surfaces and requires no primer.

APPLICATION EQUIPMENT

Brush Application: Apply using quality nylon, polyester or combination nylon/polyester, or a quality natural china bristle brush.

Roller Application: Apply using a smooth - medium nap synthetic, lamb's wool or mohair roller cover, depending on texture or surface porosity.

Spray Application:

- **Pump:** Gas or Electric Airless Sprayer
- **Pressure:** Minimum 2000 PSI
- **Tip:** 0.011 – 0.013 Reversible
- **Hose:** ¼ inch (6.3 mm) - ¾ inch (10 mm)

PRODUCT LIMITATIONS

- Not for use in corrosive or chemical environments.
- Not for use in areas subject to intense heat.
- Not for use on below grade substrates.

CLEAN UP & THINNING INSTRUCTIONS

Clean Up: Clean up any minor spills and spatters immediately with **Mineral Spirits**, as well as all painting tools and airless equipment. More serious paint spills should be contained and removed with inert absorbent material. Dispose of contaminated absorbent, container, and unused contents in accordance with local, state and federal regulations.

Thinning: Stir thoroughly and apply as it comes from the container. Thinning is not necessary. However, if thinning is required, you may add **Mineral Spirits**.

PRODUCT APPLICATION – General

Richard's Deck-Pro Alkyd Semi-Transparent Penetrating Wood Sealer may be easily applied with a quality natural bristle brush, roller cover, airless spray equipment, or a low-pressure pump-up sprayer as follows;

- Stir thoroughly in a spiral up and down motion before and during application to keep product completely mixed.
- For best results, it is recommended to apply by brush, pad or roller to effectively work sealer into wood pores.
- To assure color uniformity always intermix multiple containers of custom tinted and stock colors. Apply a small test sample to verify color.
- When applying by brush or roller, apply an even and generous coat with the direction of the wood grain.
- When staining vertical wood siding, start at the top, applying sealer to two or three boards, and work down to the bottom of the boards or until you come to a natural break in the surface, such as a corner or edge.
- When staining horizontal wood siding, start at the top corner, applying sealer to two or three boards, and work across to the other end of the boards or until you come to a natural break in the surface, such as a corner or edge.
- When applying by low-pressure pump up sprayer, prime the tank by pumping until resistance is met. The tip should be adjusted to achieve an even and continuous fan spray of approximately 4" – 6" inches. Begin spraying material in a continuous manner, saturating the surface area but avoiding any puddling. If puddling occurs, use a brush, roller or pad to distribute excess material evenly. When applying by airless spray equipment use a unit with a minimum of 1500 - 2000 psi of pressure with a 0.011" – 0.013" spray tip.
- During spray application, it is recommended to back-roll the surface area to ensure an even coat application, and to effectively work sealer into wood pores.
- Apply when surface and ambient temperatures are above 55°F and below 90°F. Avoid exterior paint application when weather conditions are threatening, and late in the day when there is a threat of moisture condensing on wet paint..

PRECAUTIONARY & SAFETY INFORMATION

CAUTIONS: COMBUSTIBLE! Keep away from heat, sparks and open flames. **INSURE PROPER CROSS-VENTILATION UNTIL COATING HAS DRIED!** Where ventilation is inadequate, use a suitable respirator. Turn off main gas valve until after coating has dried, then have pilot lights re-lighted by a responsible person. Avoid prolonged contact with skin and breathing of vapors and/or spray mists. When spraying this material, use an **OSHA** approved cartridge respirator. Use chemical safety glasses, goggles, or a face shield for proper eye protection. Wash thoroughly after handling and before eating or smoking. Close container after each use. **DO NOT TAKE INTERNALLY!**

FIRST AID: In case of skin contact, wash thoroughly with plenty of warm soapy water. For eye contact, flush with plenty of water for 15 minutes and get medical attention immediately. If you experience difficulty breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately. If swallowed, do not induce vomiting, get medical attention immediately.

NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents herein may be harmful or fatal.

KEEP OUT OF REACH OF CHILDREN!

LIMITED WARRANTY

Richard's Paint warrants our products to meet the application, appearance and performance properties stated on the label. This Limited Warranty shall not apply to any defect or damage resulting from improper surface preparation, structural defects, failure of a previous paint or improper application of the coating, as described in the directions on the label of this container. If this product is found not to perform as specified, Richard's Paint will, at its option and upon presentation of proof-of-purchase (the original receipt), either furnish an equivalent amount of new product or refund the original purchase price of this product to you. **ALL OTHER WARRANTIES ARE EXCLUDED BY RICHARD'S PAINT, EXPRESSED OR IMPLIED, STATUTORY, BY OPERATION OF LAW OR OTHERWISE, INCLUDING MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.**

LIMITATIONS

Seller's liability for any reason is expressly limited to reimbursement of the purchase price of the materials sold after proof of purchase is provided to the seller. **THIS WARRANTY EXCLUDES (1) LABOR AND COSTS ASSOCIATED WITH LABOR FOR THE APPLICATION OR REMOVAL OF ANY PRODUCT, AND (2) ANY INDIRECT, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OR RESULTING FOR ANY REASON UNDER THE SALE, HANDLING, OR USE OF GOODS SOLD.** Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty gives you specific legal rights and you may also have other rights, which vary from state to state. This Limited Warranty may not be transferred or assigned.

REV 05-25